

RL113

High Brightness LED Bright Field Ring Light

- **∢i**) 24,000 lux from 12"
- (4i) High intensity from a long working distance
- ◄i) IP67 compliant design




Ordering Information

Standard Product: Shipped Next Day

RL113-WHIIC

Configured with in-line current source

Optimal working distance: 300mm (12") Effective Working Range: 225mm - 600mm (9" - 24") Standard Product Variation: Shipped Within Two Weeks



IC = iCS (requires 24v power supply)

IS = iSU (requires 24v power supply)


C2 = Ai Connector

C3 = Pulsar 710 Connector

C5 = Pulsar 320 Connector

Available with IC, IS, and 24v options only
Not available in 24v version

Intensity Distribution



Working Distance: 300mm (12")


advancedillumination.com


For design help, accessories or pricing, please contact: sales@avsupply or call: 1-858-565-1101



1-800-284-2288 sales@avsupply.com www.avsupply.com

Dimensional Information Click for Installation Models & Drawings





Cable Length: 1.5 Meter (59")

DIMENSIONS ARE IN MILLIMETERS (INCHES)

Ai / iCS 700 700 700 700 700 ma Working Distance: 300mm (12") Lifetime 50,000 hrs Weight: 680.4 g (1.5 lb) Warking 300mm (12") Lifetime 50,000 hrs White Max. Illumination Irradiance (mW/cm²) (Lu	Standard Variation Current Specifications						Standar	Standard Product Information				
Ai / iCS 700 700 700 700 700 ma Working 300mm Distance: 300mm (12") 2.6 5,2 Lifetime 50,000 hrs		blue	areen	red infr	ra-red white	<u>.</u>		Red	Max. Illumination	_	Illuminance (Lux)	
General Specifications Weight: 680.4 g (1.5 lb) Finish: Black Anodized Operating Temperature: 0-60° C White Max. Illumination Irradiance (mW/cm²) (Lu	Ai / iCS		J				5		Distance: 300mm	2.6	5,200	
Weight: 680.4 g (1.5 lb) Finish: Black Anodized Operating Temperature: 0-60° C White Max. Illumination (mW/cm²) (LL Working 300mm Distance: (12") 5.9 24,0									Lifetime	50,000 hrs		
Finish: Black Anodized Working 300mm Distance: (12") 5.9 24,0	General Specifications					White	Max. Illumination		Illuminance (Lux)			
Meets Specifications: CE, RoHS Lifetime 50,000 hrs	Finish:	Finish: Black Anoc			ck Anodize				_	5.9	24,000	
	Meets	Meets Specifications: CE, RoHS						Lifetime	50,00	00 hrs		

Additional Information

