


RLI27 High Brightness LED Ring Light

- Ai) Intense illumination in a compact (4.6" diameter) housing
- ∠ii) IP67 Compliant Design





Ordering Information

Stock Product: Shipped Next Day


RL127-WHIIC

Configured with inline Current Source

RL127-WHIC5

Configured for use with the Pulsar 320

Standard Product Variation: Shipped Within Two Weeks



- IC = iCS (requires 24v power supply)
- i3 = Combined continuous-on and strobe over-drive (24 volt PS required.)
- C2 = Ai Connector
- C5 = Pulsar 320 Connector
- * Available with IC, i3, and 24v options only
- Not available in 24v

Dimensional Information

Ø (4.60)

Ø (4.60)

Ø (2.61)

M4x4 PLACES (56)

67mm X 0.75mm
INTERNAL THREADING

76.2
(3.0)

76.2
(3.0)

Click for Installation Models & Drawings

The RL127 can be mounted using brackets: LB101, LB103, or LB105 (not included)

> Click for Brackets Spec Sheet

Click to visit Midwest Optical's Website

STANDARD CABLE LENGTH: 1.5 Meter (59")

DIMENSIONS ARE IN MILLIMETERS (INCHES)

Mounting adapter rings for the RL127 are available at Midwest Optical's web site at: www.midopt.com/acc_steprings.html

Current Specifications

@24 320 320 320 mA

General Specifications

Weight: Finish: 304 g (11 oz.) Black Anodized

Operating Temperature: Meets Specifications: 0-60 C

1-800-284-2288 sales@avsupply.com www.avsupply.com