

## 6. Specification

According to the camera purchased, select and refer to the appropriate specification below:

<b>Model No.</b>	<b>BSS7212 / BSS7550</b>	
<b>Image Device</b>	1/3" Color SONY Super HAD CCD II Image Sensor	
<b>Picture Elements</b>	NTSC:976(H) × 494(V)	
<b>Resolution</b>	700 TVL	
<b>Min. Illumination</b>	0.1Lux / B&W	
<b>S/N Ratio</b>	More than 58 dB	
<b>Scanning System</b>	2:1 Interlace	
<b>Electronic Shutter</b>	1/60s~1/100,000s	
<b>Gamma</b>	0.45	
<b>Sync System</b>	Internal	
<b>Lens Furnished</b>	2.8-12mm or 5-50mm Varifocal	
<b>White Balance</b>	Automatic Tracking	
<b>2DNR</b>	NR-MODE / Y Level / C Level	
<b>Backlight</b>	OFF / HLC / BLC	
<b>D-WDR</b>	ON / OFF	
<b>Motion Detection</b>	ON / OFF	
<b>Privacy</b>	ON / OFF	
<b>Day / Night</b>	EXT1 / B&W / Color / Auto / EXT2	
<b>Pict Adjust</b>	OSD Key control	
<b>OSD</b>	OSD Key control	
<b>Gain Control</b>	Auto	
<b>Video Output</b>	1 Vp-p/ 75 Ohms, BNC	
<b>IR LEDES</b>	42 IR LED	
<b>IR Range</b>	More than 30m(100ft)	
<b>Power Supply</b>	DC12V±10% or AC 24V±10%	
<b>Power Consumption</b>	<b>IR LED OFF</b>	140 mA max.
	<b>IR LED ON</b>	650 mA max.
<b>System Device</b>		
<b>Operating Temp.</b>	-10°C to 50°C (14°F to 122°F)	
<b>Operating Humidity</b>	0% RH~80%RH	
<b>Waterproofing Criterion</b>	IP 66	
<b>Construction</b>	Aluminum Case	
<b>Dimensions</b>	97(W)x 81 (H) x 168(L)mm (Body only)	

(Note: Design and specifications are subject to change without prior notice.)