



LA-Series LCD Monitor 27" | 24" | 22"

Essential Displays for Both Workplace and Home



Eye comfort characterises the LA-Series, an array of displays crafted to accommodate daily usage. Multiple connectivity options—DisplayPort, HDMI, and VGA—and hence diverse multimedia applications are complemented by the flexibility of settling for a 4:3 or 16:9 aspect ratio. Also featuring a wide viewing angle, an outstanding contrast ratio, and exceptional colour performance, they promise to deliver a pleasantly rewarding visual experience either at work or at home.






LOW BLUE LIGHT

Eye Comfort

Eye comfort figures high on the list of strengths that define the LA-Series. The flicker-free backlight and blue light filter of the LA-Series ensure a comfortable viewing experience by reducing eyestrain after long periods of use. A finely tuned overdrive circuit greatly reduces ghosting and blurring to ensure videos look clean and sharp.

Flexible Connectivity and Multimedia Options

Connectivity versatility brings immense flexibility. Given its HDMI, DisplayPort, and VGA input options, you can easily connect an LA-Series display to your current or older peripherals, like PCs, laptops, or media players at the workplace or home.



HDMI



Audiovisual Multimedia Enjoyment

A 20,000,000:1 contrast ratio, precise colour temperature and preset picture mode settings for reading texts, browsing webpages, or watching videos make the LA-Series a competent multimedia platform. Whether watching videos or listening to music, you can either count on its built-in speakers or plug in your earphones.

Features

- Full HD 1920 x 1080 resolution
- Crisp 20,000,000:1 dynamic contrast ratio
- DisplayPort and HDMI inputs for Full HD connectivity with a variety of devices
- Blue-light filter and Flicker-free display technology reduces eye discomfort
- Selectable aspect ratio
- Built-in speakers and audio mini-jack in/out connection
- VESA mount compatibility for flexible installation



Specifications

LA-27

LA-24

LA-22

Panel	Panel Type	LED-Backlit TFT LCD (VA Technology)	LED-Backlit TFT LCD (IPS Technology)	LED-Backlit TFT LCD (TN Technology)
	Panel Size	27.0"	23.8"	21.5"
	Max. Resolution	FHD 1920 x 1080	FHD 1920 x 1080	FHD 1920 x 1080
	Pixel Pitch	0.314 mm	0.275 mm	0.248 mm
	Brightness	280 cd/m ²	270 cd/m ²	300 cd/m ²
	Contrast Ratio	20,000,000:1 (DCR)	20,000,000:1 (DCR)	20,000,000:1 (DCR)
	Viewing Angle (H/V)	178°/178°	178°/178°	170°/160°
	Display Colour	16.7M	16.7M	16.7M
	Response Time	5 ms	5 ms	3 ms
Frequency (H/V)	H Freq. V Freq.	30 kHz-83 KHz 56 Hz-75 Hz	30 kHz-83 KHz 56 Hz-75 Hz	30 kHz-83 KHz 56 Hz-75 Hz
Input	DisplayPort HDMI VGA	x 1 1.3 x 1 15-Pin D-Sub x 1	x 1 1.3 x 1 15-Pin D-Sub x 1	x 1 1.3 x 1 15-Pin D-Sub x 1
Audio	Audio In Audio Out Internal Speakers	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (3.5 mm) 2W x 2	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (3.5 mm) 2W x 2	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (3.5 mm) 2W x 2
Power	Power Supply Power Requirement On Mode Stand-by Mode Off Mode	Internal AC 100-240V, 50/60 Hz 25W (On) < 0.5W < 0.5W	Internal AC 100-240V, 50/60 Hz 18W (On) < 0.5W < 0.5W	Internal AC 100-240V, 50/60 Hz 18W (On) < 0.5W < 0.5W
Operating Conditions	Temperature Humidity	5°C-35°C (41°F-95°F) 20%-85% (non-condensing)	5°C-35°C (41°F-95°F) 20%-85% (non-condensing)	5°C-35°C (41°F-95°F) 20%-85% (non-condensing)
Storage Conditions	Temperature Humidity	-20°C-60°C (-4°F-140°F) 5%-85% (non-condensing)	-20°C-60°C (-4°F-140°F) 5%-85% (non-condensing)	-20°C-60°C (-4°F-140°F) 5%-85% (non-condensing)
Mounting	VESA FPM/PMI	Yes (100 x 100 mm)	Yes (100 x 100 mm)	Yes (100 x 100 mm)
Stand	Tilt	-5° to 20°	-5° to 20°	-5° to 15°
Security	Kensington Security Slot	Yes	Yes	Yes
Dimensions	w/Base (W x H x D) Packaging (W x H x D)	612.0 x 452.0 x 226.0 mm (24.1" x 17.8" x 8.9") 678.0 x 545.0 x 134.0 mm (26.7" x 21.5" x 5.3")	555.0 x 433.0 x 226.0 mm (21.9" x 17.0" x 8.9") 620.0 x 418.0 x 157.0 mm (24.4" x 16.5" x 6.2")	511.0 x 377.0 x 183.0 mm (20.1" x 14.8" x 7.2") 561.0 x 426.0 x 103.0 mm (22.1" x 16.8" x 4.1")
Weight	w/Base Packaging	4.3 kg (9.5 lb) 5.9 kg (13.0 lb)	3.5 kg (7.7 lb) 5.0 kg (11.0 lb)	3.4 kg (7.5 lb) 4.6 kg (10.1 lb)
Regulation Approval	Certification & Compliance	CE, LVD, WEEE, RoHS, REACH, CCC, CEL	CE, LVD, FCC, WEEE, RoHS, REACH	CE, LVD, FCC, WEEE, RoHS, REACH, BSMI
Accessories	Supplied	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card
Optional Accessories		Wall Mount: PMK-01 Desk Mount: DMC-01 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, WMK-01, WMK-03	Wall Mount: PMK-01 Desk Mounts: DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, WMK-01, WMK-03	Wall Mount: PMK-01 Desk Mounts: DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, WMK-01, WMK-03

All specifications are subject to change without prior notice.

Copyright © 2019 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC.

All other trademarks are the property of their respective owners.

P/C: LA2700/LA2400/LA2200 Version 1.3, 20190924



Global Headquarters

Taipei, Taiwan

EMEA Regional Headquarters

Capelle a/d IJssel, The Netherlands

North & South America Regional Headquarters

San Jose, CA, U.S.A.

Asia-Pacific Regional Headquarters

Taipei, Taiwan

Canada Sales Office

Vancouver, B.C., Canada

China Sales Office

Shanghai, China

Czech Republic Sales Office

Brno, Czech Republic

Denmark Sales Office

Støvring, Denmark

Germany Sales Office

Mechernich, Germany

Italy Sales Office

Livorno, Italy

Poland Sales Office

Warsaw, Poland

Spain Sales Office

Barcelona, Spain

Ukraine Sales Office

Lviv, Ukraine

displays.agneovo.com