



LED 

PS-46

A high brightness 46" LED-backlit display with an OPS slot suitable for professional digital signage applications.

Featuring LED backlighting and 700 nits high brightness for vivid images, the PS-46 public signage display equipped with an OPS slot, built-in scheduler and RS-232/RJ45 remote control function allows easy digital signage installation and management. Flexible landscape or portrait display orientation fulfills different applications. On top of premium-grade LCD panel, the Anti-Burn-in™ technology and HeatControl Sensor prolong product lifespan and ensure reliable operations.

- > LED-backlit technology with FHD 1920 x 1080 resolution
- > 700 nits high brightness
- > Premium-grade panel for high reliability and long product lifetime
- > Anti-Burn-in™ technology
- > AIP technology: 3D Comb Filter/ Deinterlace/ Noise Reduction/PIP and PBP
- > Versatile connectivity: VGA, DVI, HDMI, CVBS, YPbPr, DisplayPort
- > Daisy chain availability: VGA, DVI, RS-232
- > RS-232 and RJ45 allow programmable remote control
- > 15.8 mm bezel width and tiling function for easy video wall setup (support up to 5 x 5)
- > Built-in scheduler allows different programme scheduling
- > HeatControl Sensor automatically activates the internal cooling fan to cool down the temperature
- > OPS slot ready for easy media player integration
- > Built-in speakers
- > Quick switch between internal and external speakers
- > Flexible display orientation: portrait and landscape
- > Rigorous screening of the components for mission-critical 24/7 applications



PS-46

Specifications

PS-46

Panel	Panel Type	LED-Backlit TFT LCD (MVA panel)
	Panel Size	46"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.53 mm
	Brightness	700 cd/m ² (Typical)
	Contrast Ratio	4000 : 1 (Typical)
	Viewing Angle (H/V)	178°/178° (Typical)
	Display Colour	1.07 B
Frequency (H/V)	Response Time (GTG)	6.5 ms
Frequency (H/V)	H.Freq	31kHz – 91kHz
	V.Freq	50Hz – 85Hz
Input	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	HDMI	HDMI
	Component (YPbPr)	BNC x 3
	CVBS	BNC
	DisplayPort	DisplayPort
Output	DVI/VGA	29-Pin DVI-I
External Control	RS-232 in/out	9-Pin D-Sub
	RJ45	RJ45
Audio	Audio In	1 x Stereo audio in for PC (audio jack, 3.5ø)
		1x Stereo audio in (RCA)
	Audio Out	1 x Stereo audio out (RCA)
	Internal Speaker	10W x 2
Other Connectivity	External Speaker Out	10W x 2
	OPS Slot	Yes
Power	Power Supply	Internal
	Power Requirements	100 - 240V, 50 - 60Hz
	Consumption	< 170W (On) < 0.5W (Active Off/Off)
Operating Conditions	Temperature	0°C ~ 40°C (32°F~104°F)
	Humidity	20%~80% (No condensation)
Storage Conditions	Temperature	-20°C ~ 60°C (-4°F~140°F)
	Humidity	5%~95% (No condensation)
Mounting	VESA FPMPI	Yes (400 x 400mm/ 400 x 200mm/ 200 x 200mm)
Dimensions	w/o Base (W x H x D)	1053 x 607 x 69 mm (41.5" x 23.9" x 2.7")
	with Base (W x H x D)	1053 x 663 x 400 mm (41.5" x 26.1" x 15.7")
	Packaging (W x H x D)	1309 x 843 x 250 mm (51.5" x 33.2" x 9.8")
Weight	w/o Base	22.0 kg (48.4 lbs)
	with Base	24.0 kg (52.8 lbs)
	Packaging weight	27.5 kg (60.5 lbs)
Regulation Approval	Certifications & Compliance	CB, CE, FCC, RoHS, WEEE, REACH, GOST-R
Accessories	Supplied	CD ROM (user manual), Remote control with AAA batteries, Power cord, 15-Pin D-Sub cable, Power switch cover and screw, Cable tie
	Optional	Stand base (STD-05)



700 nits high brightness panel assures image clarity even under high-ambient light.



Versatile connectivity: VGA, DVI, HDMI, CVBS, YPbPr, DisplayPort, RS-232, RJ45 and audio.



The flexibility in display orientation—either landscape or portrait—means user freedom in fitting whatever setting.



OPS compliant design simplifies digital signage installation and maintenance.



All specifications are subject to change without prior notice.
Copyright © 2013 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC.
All other trademarks are the property of their respective owners.
P/C: PS4600 Version 1.2, 20131104

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com