



THE DISPLAY CHOICE
OF PROFESSIONALS™



LED

RX-24

A 24" LED-backlit display with NeoV™ Optical Glass immaculately welded onto metal casing designed for advanced security environments.

Built on an LED-backlit panel delivering 1920 x 1080 Full HD resolution, the RX-24 presents life-like contrast, colours and nuances on its Advanced Image Platform™ (AIP). Its Smart Omni Viewer offers such options as Picture-in-Picture (PIP) and selectable aspect ratios. Features include Anti-Burn-in™ and EcoSmart Sensor ensure the mission-critical 24/7 round-the-clock operations. With NeoV™ Optical Glass backed by metal casing, this sturdy display delivers the performance expected of a high-end security display.

- > LED-backlit technology with high FHD 1920 x 1080 resolution
- > NeoV™ Optical Glass
- > Anti-Burn-in™ technology
- > AIP technology: PIP and PBP functions; 3D Comb Filter/ Deinterlace/ Noise Reduction; Image rotation function / Freeze
- > Horizontal resolution up to 620TVL(NTSC), 625TVL(PAL)
- > Quick signal-switching time (≤ 0.8 sec.)
- > Selectable aspect ratio for ultimate image
- > EcoSmart Sensor for low watt power consumption
- > Black-level alignment
- > Versatile inputs: VGA, DVI, HDMI, S-Video, CVBS in/out (BNC x 2), Audio in/out
- > Built-in speakers (2W x2)
- > BNC video out passive looping
- > Power DC-out design to power connected peripherals
- > Durable metal housing
- > Rigorous screening of the components for mission-critical 24/7 applications



NeoV™ Optical Glass - The most
trusted hard glass protection available.
Only on AG Neovo displays



Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

www.agneovo.com

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101

AUDIOVIDEO SUPPLY

1-800-284-2288 sales@avsupply.com
www.avsupply.com

RX-24

Specifications

RX-24

Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time	LED-backlit TFT LCD 23.6" FHD 1920 x 1080 0.2715 mm 300 cd/m2 (Typical) 1,000 : 1 (Typical) 170°/160° (Typical) 16.7M 3 ms (GTG)
Horizontal Resolution	TV Lines	620TVL (NTSC), 625TVL (PAL)
Frequency (H/V)		H: 24 kHz - 83 kHz V: 50 Hz - 85 Hz
Input	VGA DVI CVBS S-Video HDMI	15-Pin D-Sub 24-Pin DVI-D BNC x 2 4-Pin mini DIN HDMI x 1
Output	CVBS DC Output	BNC x 2 12V/500mA, DC jack 2.5Ø
Audio	Audio In Audio Out Speaker	1 x stereo audio in for PC (audio jack, 3.5 Ø) RCA L+R for video RCA L+R 2W x 2
Power	AC-DC Adaptor Power Consumption	External DC 12V 100 - 240V, 50 - 60Hz <27W (On) <0.5W (Active Off) <0.5W (Off)
Sync Format	Video System	NTSC/PAL/SECAM
NeoV™ Optical Glass	Thickness Reflection Rate Coating Hardness	3.0 mm (0.18") < 1% > 9H
Operating Conditions	Temperature Humidity	0°C ~ 40°C (32°F~104°F) 10%~90% (No condensation)
Storage Conditions	Temperature Humidity	-20°C ~ 60°C (-4°F~140°F) 5%~95% (No condensation)
Mounting	VESA FPMPI	Yes (100mm x 100mm & 75mm x 75 mm)
Dimensions	Product (W x H x D) Packaging (W x H x D)	562 x 397 x 155 mm (22.1" x 15.6" x 6.1") 676 x 525 x 213 mm (26.6" x 20.7" x 8.4")
Weight (net)	Product Weight Packaging Weight	7.9 kg (17.4 lbs) 10.6 kg (23.4 lbs)
Regulation Approval	Certifications & Compliance	FCC, CB, CE, BSMI, RoHs, WEEE, REACH
Accessories	Supplied	Quick Guide, CD ROM(user manual), power cord, power adapter, 15-Pin D-Sub cable, audio cable



Available in black or white



NeoV™ Optical Glass protects against scratches, impacts and other physical damage



On top of PIP and PBP, Smart Omni Viewer offers selectable aspect ratios and the option of 180° image rotation



Multiple video inputs (HDMI, DVI, VGA, CVBS, S-Video) make possible effortless system integration



EcoSmart Sensor and versatile capabilities ensure round-the-clock operations



All specifications are subject to change without prior notice.
Copyright © 2013 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC.
All other trademarks are the property of their respective owners.
P/C: RX2400, Version 1.2, 20130101

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com