

SC-19



LED 

A value 19" surveillance display with rapid response time, quick signal-switching and robust video support for security and control centre environments.

For a cost-effective surveillance display solution, look no further than the AG Neovo SC-19. A bright, high resolution full colour screen with quick signal-switching and 3ms response time ensures sharp, smooth video playback. Looping BNC video inputs and NTSC/PAL support maximise flexibility for system integration. And with built-in speakers, stylishly slim profile and VESA mountability, the SC-19 will look just as attractive as its amazingly affordable price.

- > High 1280 × 1024 SXGA resolution
- > Anti-Burn-in™ technology
- > Video inputs (BNC in x 1, BNC out x 1)
- > Looping video inputs for multiple connections
- > Quick signal-switching time (≤ 0.8 sec.)
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Key lock function
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount



SC-19

Specifications

SC-19

Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time	LED-Backlit TFT LCD 19.0" (483 mm) SXGA 1280 x 1024 0.294 mm 250 cd/m ² (Typical) 1000:1 (Typical) 170°/160° (Typical) 16.7 M 3 ms (GTG)
Horizontal Resolution	TV Lines	550TVL (NTSC), 550TVL (PAL)
Frequency (H/V)		H: 31 kHz - 80 kHz V: 50 Hz - 75 Hz
Input	Analogue Digital CVBS S-Video	15-Pin D-Sub 24-Pin DVI-D BNC x 1 4-Pin mini DIN
Out	CVBS	BNC x 1
Audio	Audio In Audio Out Speaker	3.5 mm Audio Line-in 3.5 mm Audio Line-in 1W x 2
Power	Power Supply Power Requirements Consumption	External DC 12V < 25W (On) < 1.5W (Stand-by) < 1W (Off)
Plug & Play	VESA	DCC 2B
Operating Conditions	Temperature Humidity	0 °C ~ 40 °C 10% ~ 85%
Storage Conditions	Temperature Humidity	-20 °C ~ 60 °C 10% ~ 95%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Tilt	Tilt	-5° ~ +15°
Dimensions	Product (W x H x D) Packaging (W x H x D)	420 x 408 x 164mm (16.5" x 16.1" x 6.5") 461 x 489 x 164mm (18.1" x 19.3" x 6.5")
Weight	Product Weight Packaged Weight	5.5 kg (12.1 lbs) 5.7 kg (12.5 lbs)
Regulation Approval	Certifications & Compliance	UL/CUL, CB, FCC, CE, BSMI, GOST-R, WEEE, RoHS
Accessories	Supplied	User manual, power cord, power adaptor, 15-Pin D-Sub cable, audio cable, warranty card



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping video inputs allow multiple display connections



Video versatility, including VGA, DVI, S-Video, and BNC In/Out

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com



All specifications are subject to change without prior notice.
Copyright © 2014 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC.
All other trademarks are the property of their respective owners.
P/C: SC19C0 Version 6.1, 20140324

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101