



## SX-17

An incredibly versatile sharp surveillance display with durable, high performance features designed expressly for today's security environments.

The SX-17 is a security-specific display featuring quick signal-switching time, Anti-Burn-in™ technology and NeoV™ Optical Glass which protects against scratches and other incidental damage during the lifetime of the display. The VESA compatible mounts, thin profile, durable metal casing and built in BNC connectors allow multiple SX-17 displays to be easily installed in any surveillance configuration for security environments.

- > NeoV™ Optical Glass
- > Distinctive bezel design and durable metal casing
- > Anti-Burn-in™ technology to prevent image sticking
- > Mask Mode to reduce image distortion
- > Quick signal-switching time ( $\leq 0.8$  sec.)
- > Real-time image display with no time lag
- > Automatic recovery of video settings after power interruptions
- > Video looping output supports auto termination
- > Supports NTSC/PAL/SECAM video systems
- > Auto-adjustment when VGA input is selected
- > Kensington® security socket
- > VESA standard wall mount



NeoV™ Optical Glass - The most trusted hard glass protection available.  
Only on AG Neovo displays



# SX-17


## Specifications

## SX-17

Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time Panel Life Time	TFT LCD 17.0" (432 mm) SXGA 1280 x 1024 0.264 mm 300 cd/m <sup>2</sup> (Typical) 800:1 (Typical) 160°/160° (Typical) 16.2M 3 ms (GTG) 50,000 hrs (Minimum)
Frequency (H/V)		H: 30 kHz - 80 kHz V: 56 Hz - 75 Hz
Max. Pixel Clock		140 MHz
Input	Analogue Digital BNC Security	15-Pin D-Sub 24-Pin DVI-D BNC Connector
Input Signal	Analogue Digital Composite	RGB H.V Sync TMDS NTSC/PAL/SECAM
Output Connector	BNC Security	BNC Connector
Power	AC-DC Adaptor Power Consumption	External AC 100 - 240 V, 50 - 60 Hz < 42 W (On) < 2 W (Off)
NeoV™ Optical Glass	Thickness Reflection Rate Transmission Rate Coating Hardness	3.0 mm (0.12") < 1% > 96% > 9H
Plug & Play	VESA	DCC 2B , DCC/CI
Operating Conditions	Temperature Humidity	0 °C ~ 40 °C 10% ~ 90%
Storage Conditions	Temperature Humidity	-20 °C ~ 60 °C 5% ~ 95%
Mounting	VESA FPMPI	Yes (100 mm)
Tilt	Tilt	0° ~ +15°
Dimensions	Product (W x H x D) Packaging (W x H x D)	408 x 398 x 175 mm (16.1" x 15.7" x 6.9") 493 x 513 x 226 mm (19.4" x 20.2" x 8.9")
Weight	Product Weight Packaged Product Weight	6.8 kg (14.9 lbs) 9.5 kg (20.9 lbs)
Regulation Approval	Certifications & Compliance	UL/CUL, TUV/Baurt, CB, GOST-R, FCC, CE, BSMI, WEEE, RoHS, Vista/Basic, REACH
Accessories	Supplied	Quick Guide, CD ROM (user manual and drivers), power cord, power adaptor, 15-Pin D-Sub cable, 24-Pin DVI-D cable, CVBS BNC connector cable



NeoV™ Optical Glass for hard glass protection and strong metal casing for secure mounting



Anti-Burn-in™ technology prevents image sticking



Specifically designed and tested for commercial video security applications



Looping BNC video connector for multiple display connections

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- [www.avsupply.com](http://www.avsupply.com)



All specifications are subject to change without prior notice.  
Copyright © 2010 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC.  
All other trademarks are the property of their respective owners.  
P/C: SX17F0\_SX7F1 Version 23.0, 20100701

For design help, accessories or pricing, please contact:  
[sales@avsupply](mailto:sales@avsupply) or call: 1-858-565-1101