



Overview

AL1012ULM multi-output access control power supply/charger is specifically designed for use with access control systems and accessories. This unit converts a 115VAC, 60Hz input into five (5) individually PTC protected Class 2 Rated power-limited 12VDC outputs. Each output will route power to a variety of access control hardware devices including Mag Locks, Electric Strikes, Magnetic Door Holders, etc. These outputs will operate in both Fail-Safe and Fail-Secure modes. Controlled trigger input is achieved through normally open (N.O.) or normally closed (N.C.) supervised input or the polarity reversal from an FACP (Fire Alarm Control Panel). A form "C" dry output relay enables HVAC Shutdown, Elevator Recall or it may be used to trigger auxiliary devices.

Specifications

Input:

- Input 115VAC, 60Hz, 2.6 amp.
- Input fuse rated @ 3.5 amp/250V.
- Fire Alarm Panel or Access Control System trigger inputs. N.O. or N.C. supervised trigger input and polarity reversal trigger input.

Output:

- 12VDC outputs.
- 10 amp supply current.
- Five (5) PTC protected Class 2 Rated power-limited outputs, rated @ 2 amp.
- Output relay energizes when unit is triggered (form "C" contact rated 1 amp @ 28VDC).
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.
- Maximum charge current 0.7 amp.

Supervision:

- AC fail supervision (form "C" contacts).
- Low battery supervision (form "C" contacts).
- Battery presence supervision (form "C" contacts).
- Power fail supervision relay (form "C" contacts).

Visual Indicators:

- AC input and DC output LED indicators (power supply board).
- Red LEDs indicate condition of power outputs (multi-output board).
- Power & input trigger LEDs (multi-output board).

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 61.42 BTU/Hr.
- System AC input VA requirement: 299VA.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm)
 - Accommodates up to two (2) 12VDC/12AH batteries.
- Product weight (approx.): 8.95 lbs. (4.06 kg).
- Shipping weight (approx.): 10.25 lbs. (4.65 kg).

Agency Approvals



UL 294 UL Listed for Access Control System Units.



CUL Listed - CSA Standard C22.2 No.205-M1983, Signal Equipment.

Enclosure Dimensions (H x W x D approximate):
 15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm)

