



ALTV1224DC2

### **Overview**

ALTV1224DC2 is designed to power CCTV Cameras and accessories. It provides 12VDC or 24VDC distributed via sixteen (16) fuse protected outputs with a total of 6 amp total supply current.

### **Specifications**

#### ***Input:***

- Input 115VAC, 50/60 Hz, 2.55 amp.

#### ***Output:***

- Sixteen (16) fuse protected outputs.
- 12VDC or 24VDC.
- 6 amp total continuous supply current  
(0.375 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Filtered and electronically regulated outputs.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 36.85 or 74.73 BTU/Hr.
- System AC input VA requirement: 293.25VA.

#### ***Features:***

- AC input and DC output LED indicators.
- Power ON/OFF switch.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

#### ***Mechanical:***

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.):  
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)
- Product weight (approx.): 7.9 lbs. (3.58 kg).
- Shipping weight (approx.): 8.8 lbs. (3.99 kg).

**Enclosure Dimensions (H x W x D approximate):**  
 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)

