



## **R248ULCBi** **Isolated Rack Mount CCTV Power Supply**

Rev. DSR248ULCBi\_10252012



R248ULCBi

### **Overview**

R248ULCBi provides 24VAC distributed via eight (8) isolated PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

### **Specifications**

#### ***Input:***

- 115VAC, 50/60Hz, 2.7 amp.

#### ***Output:***

- Eight (8) isolated PTC protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current  
(1.56 amp per device, 2.5 amp max.)
- Outputs are rated @ 2.5 amp.
- Surge suppression.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 114 BTU/Hr.
- System AC input VA requirement: 310.5VA.

#### ***Features:***

- Eight (8) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.

#### ***Mechanical:***

- 2U rack mount chassis for use in standard EIA 19" rack.
- Enclosure Dimensions (H x W x D approx.):  
3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)
- Product weight (approx.): 17.2 lbs. (7.80 kg).
- Shipping weight (approx.): 18.2 lbs. (8.26 kg).

### **Agency Approvals**



UL Listed for Commercial CCTV Equipment  
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,  
Audio, Video and Similar Equipment.



European Conformity

**Enclosure Dimensions** (*H x W x D approximate*):  
3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)

