



Indoor and Outdoor
Dome Housing



Vandal Resistant
Indoor and Outdoor
Dome Housing

VideoEdge IP SpeedDome

Indoor and Outdoor Dome Housings

Features That Make a Difference:

- Precision-crafted bubbles maintain the integrity of light and image
- Reinforced high impact design with vandal resistant option
- Four alarm inputs, one output
- Surge and lightning protection of video, data, alarm input and output, and power
- Plug and play connectors enable easy servicing of environmental board
- Ceiling, pole, roof, wall, and corner mounts available

OUTDOOR HOUSING-SPECIFIC FEATURES

- Temperature-controlled interior environment
- Automatic defog and defrost heater cycle modes
- Thermostatically controlled heater and blower prevent excessive buildup of ice and removes any that does accumulate in one hour
- On-demand menu through the web interface displays housing temperature and humidity
- Meets IP66/NEMA 4 specifications

The VideoEdge IP SpeedDome indoor and outdoor housings allow the IP Dome to be installed in virtually any environment. The superior optics within the bubble have been designed to maintain the integrity of light, producing images that are optically correct.

The housings have been designed to provide maximum protection to the internal camera in various conditions. In extreme temperatures, the outdoor housing's built-in thermostatically controlled heater and blower prevent excessive ice from forming on the outside bubble.

Both indoor and outdoor housings are constructed with a reinforced fiberglass high impact polycarbonate material along with a UV stabilized sun shade, trim ring, and top cover. The bubble assembly is affixed to the top via tamper-proof screws.

For applications where vandalism is a concern, a vandal resistant model is available which includes an aluminum sunshield cover and a high impact bubble which meets ANSI-87.1 impact safety standards. For additional protection, a steel bubble cage is also provided.

The housings are equipped with four alarm inputs and one alarm output and surge protection is provided to all video and external lines. The housings are available with your choice of a clear or smoked bubble and a variety of mounts make it easy for you to install it in nearly any application.

An optional end cap assembly is ideal for cable interconnection.

features

Outdoor Housings

Model Numbers

| | |
|-------------|--|
| ADVESDHOC | Housing with Clear Bubble (f0) |
| ADVESDHOS | Housing with Smoked Bubble (f1.0) |
| ADVESDHOVRC | Vandal Resistant Housing with High Impact Clear Bubble (f0) |
| ADVESDHOVRS | Vandal Resistant Housing with High Impact Smoked Bubble (f1.0) |

Electrical (for heater blower)

| | |
|-------------------|---|
| Input Voltage | 24 VAC @ 50/60 Hz, NEC Class 2, Certified Limited Power Source |
| Design Tolerance | 20 to 30 VAC @ 50/60 Hz, |
| Power Consumption | 60W Max: 2.5A @ 24VAC |
| Surge Protection | Power Line TVS rated at 60V, 1.5 joules; Gas discharge tube rated at 8/20 us Impulse Discharge Current: 5kA |

Environmental

| | |
|-----------------------|------------------------------|
| Weatherproof Standard | NEMA 4, IP66 |
| Operating Temperature | -40° to 50°C (-40° to 122°F) |
| Storage Temperature | -10° to 50°C (14° to 122°F) |
| Humidity | 0% to 95% RH (noncondensing) |

Mechanical

| | |
|-----------------------------------|--------------------|
| Height | 32.1 cm (12.5 in) |
| Diameter | 24.4 cm (9.6 in) |
| Weight (ADVESDHOC, ADVESDHOS) | |
| Without dome | 2.22 kg (4.89 lbs) |
| With dome | 3.38 kg (7.45 lbs) |
| Weight (ADVESDHOVRC, ADVESDHOVRS) | |
| Without dome | 2.82 kg (6.21 lbs) |
| With dome | 3.98 kg (8.77 lbs) |

Regulatory

| | |
|-----------------------|--|
| Safety | |
| US and Canada | UL 60950-1/CSA C22.2 No. 60950 and UL50 (Type 4) |
| European Union | EN60950 -1 and EN60529 IP 66 EMC |
| US | FCC Part 15 Class A |
| Canada | ICES-003/NMB-003 Class A |
| Europe | EN55022 Class A, EN50130-4 |
| Australia/New Zealand | AS/NZS CISPR22 Class A |

Maximum Distances from Power Source

Dome and housing to be connected to a Class 2 LPS, 24 VAC, 80 VA power source (do not exceed maximum outdoor Class 2 ratings of 30 VAC, 100 VA).

| | 18 AWG | 16 AWG | 14 AWG |
|---------------------------------|---------------|----------------|----------------|
| Low Line Voltage 102/204 VAC | 60 m (200 ft) | 100 m (320 ft) | 160 m (520 ft) |
| Low Line Voltage 90/180 VAC | 30 m (100 ft) | 50 m (160 ft) | 80 m (260 ft) |

ADSPOT Features and Specifications



- Single Position Outdoor Power Supply
- Supports both 120 VAC and 230 VAC
- Small, compact design
- Weatherproof design: NEMA 4 and IP66 rated
- Euro-style terminal blocks for quick and simple installation

Mechanical

| | |
|------------------------|---|
| Dimensions (H x W x D) | 75 x 125 x 75 mm (6.9 x 4.9 x 3.0 in) |
| Weight | 3.7 kg (8.2 lbs) |
| Enclosure Material | Impact-resistant polycarbonate |
| Color | Light gray |
| Wall Mounting Options | Concrete, wood or sheet rock |
| Mounting Area (H x W) | 281 x 200 mm (11.1 x 7.9 in) |
| Cover Fasteners | Four captive screws |
| Cable Access Knockouts | Eight 21 mm or 15.5 mm (0.83 in or 0.61 in) Four 29 mm or 23 mm (1.14 in or 0.91 in) |

Electrical

| | |
|--------------------------------|---------------------------------------|
| Power Source | 100-120 VAC or 200-240 VAC @ 50/60 Hz |
| Operational Limits | 90-135 VAC or 180-265 VAC @ 50/60 Hz |
| Input Current | 1.0 A/0.5 A |
| Output | 4 VAC, 2.5 A max. |
| UL Listed Class | 2 |
| Certified Limited Power Source | |

Environmental

| | |
|-----------------------|------------------------------|
| Weatherproof Standard | NEMA 4, IP66 |
| Operating Temperature | -40° to 50°C (-40° to 122°F) |
| Storage Temperature | -40° to 50°C (-40° to 122°F) |
| Humidity | 0% to 95% RH (noncondensing) |

Regulatory

| | |
|--------|---|
| Safety | UL 60950 CSA C22.2 No. 60950 EN60950 IEC 60950 |
|--------|---|

Indoor Housings

Model Numbers

| | |
|-------------|---|
| ADVESDHIC | Indoor Housing with Clear Bubble (f0) |
| ADVESDHIS | Indoor Housing with Smoked Bubble (f0) |
| ADVESDHICVR | Indoor Vandal Resistant Housing with High Impact Clear Bubble (f0) |
| ADVESDHISVR | Indoor Vandal Resistant Housing with High Impact Smoked Bubble (f1.0) |

Environmental

| | |
|-----------------------|-------------------------------|
| Operating Temperature | -10°C to 50°C (14°F to 122°F) |
| Storage Temperature | -10°C to 50°C (14°F to 122°F) |
| Humidity | 0% to 95% RH (noncondensing) |

Mechanical

| | |
|-----------------------------------|--------------------|
| Height | 32.1 cm (12.5 in) |
| Diameter | 24.4 cm (9.6 in) |
| Weight (ADVESDHIC, ADVESDHIS) | |
| Without dome | 1.7 kg (3.75 lbs) |
| With dome | 2.86 kg (6.3 lbs) |
| Weight (ADVESDHICVR, ADVESDHISVR) | |
| Without dome | 2.3 kg (5.07 lbs) |
| With dome | 3.46 kg (7.63 lbs) |

Regulatory

| | |
|----------------|--------------------------------|
| Safety | |
| US and Canada | UL 60950-1/CSA C22.2 No. 60950 |
| European Union | EN60950 -1 |










ADVESDHRDCLGC, ADVESDHRDCLGS Features and Specifications

Ceiling mounts used to mount the American Dynamics VideoEdge IP SpeedDome to 2x2 suspended ceilings or tile ceilings. For installations in a 2'x2' drop tile ceiling also order RH2x2.

ADVESDBASE Features and Specifications

Ceiling mount used to install an American Dynamics VideoEdge IP SpeedDome to a ceiling, a 3x3 (RHIU3x3) or 4x4 (RHIU4x4) electrical box, or in conjunction with wall/corner mounts (ADSDICM), 2x2 tile pendant mounts (RHIU2x2P), indoor pendant mount (RHOPN), I-Beam Mount (RHIUIBM). The mount makes PoE installation easy.

mounts and accessories

| Mounting Options | | | | |
|---|---|--|---|-----------------------|
| Mount | Description | Construction | Dimensions | Weight |
| RHOSW: Short Wall Mount with End Cap Assembly  | This mounting structure attaches directly to a flat wall. When used with the RHOWCA corner bracket adapter or RHOWPA pole strap adapter it can be affixed to corners as well as poles. A mounting cover conceals the mounting plate for a more attractive appearance. | Powder-coated aluminum, ABS plastic and fiber-filled PVC | With dome installed 366 x 218 x 282 mm (14 x 9 x 11 in) | 1.3 kg (3 lbs) |
| RHOLW: Long Wall Mount with End Cap Assembly  | This mount attaches directly to a flat wall, positioning the dome away from the wall, so that it can see over furniture, shelving and displays. When used with the RHOWCA corner bracket adapter or RHOWPA pole strap adapter it can be affixed to corners as well as poles. A mounting cover conceals the mounting plate for a more attractive appearance. | Powder-coated aluminum, ABS plastic and fiber-filled PVC | With dome installed 366 x 218 x 587 mm (14 x 9 x 23 in) | 1.7 kg (3.9 lbs) |
| RHOPN: Outdoor Pendant Mount  | This mount suspends an outdoor dome housing from an outdoor ceiling or horizontal surface. It can be installed using either new or existing 1.25" NPT threaded pipe or rigid conduit up to 10 feet (3 meters) in length. | Powder-coated aluminum, ABS plastic | 115 x 120 x 120 mm (4.5 x 5 x 5 in) | 1.8 kg (4 lbs) |
| RHOTR: Over-the-Roof Mount with End Cap Assembly  | This mount affixes directly to any wall, rooftop wall or parapet, positioning the dome away from the wall, so that it can see over awnings, soffits and landscaping. Opposing wing brackets secure installation to the roof surface, while allowing the pole to be repositioned for easy service access. | Powder-coated aluminum, ABS plastic and fiber-filled PVC | 1098 x 243 x 473 mm (43 x 10 x 19 in) | 5.7 kg (12.7 lbs) |
| Adapter Options | | | | |
| Adapter | Description | Construction | Dimensions | Weight |
| RHOWCA: Corner Bracket Adapter  | This adapter attaches the long and short wall mounts (RHOSW & RHOLW) to affix to outside corners. Powder-coated aluminum construction ensures an extremely sturdy installation. | Powder-coated aluminum | 185 x 210 x 125 mm (7 x 8 x 5 in) | .79 kg (1.75 lbs) |
| RHOWPA: Pole Strap Adapter  | This adapter attaches the long and short wall mounts (RHOSW & RHOLW) to outside corners. This kit contains stainless steel straps that can be daisy-chained to accommodate any size pole and all the necessary mounting hardware. | Powder-coated aluminum and stainless steel | 138 x 79 x 27 mm (5 x 3 x 1 in) Straps support 53 to 951 mm (2 to 30 in) pole diameter | .5 kg (1.1 lbs) |
| ROTRF: Floor Adapter for RHOTR  | This adapter installs the RHOTR over-the-roof mount on horizontal and vertical roof/parapet surfaces. Multiple fastening positions provide versatility for mounting on any combination of surfaces and angles. | Powder-coated aluminum | 369 x 240 x 240 mm (15 x 10 x 10 in) | 2.59 kg (5.75 lbs) |
| ROENDC: End Cap Assembly  | This mounting assembly retrofits any existing outdoor SpeedDome wall, pole, corner, or over-the-roof mount to accommodate newer outdoor housings. A modular design lets you mount the housing to the end cap on the ground, before installing it on the mounting pole, making the process safe and easy. | Fiber-filled PVC | 64 x 103 x 194 mm (3 x 4 x 8 in) | .32 kg (.7 lbs) |
| RHIUBM: Indoor I-beam Clamp Assembly  | This assembly allows the dome to be suspended from an I-beam; and includes a clamp, pipe tee nipple and flange. The clamp attaches to a 1.25" pipe, provided by the customer, then affixes to the pendant hardware. The housing or dome assembly also mounts to the structure. | Steel and Galvanized steel | N/A | 2.9 kg (6.4lbs) |

Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative. Certain product names mentioned herein may be trade names and/or registered trademarks of other companies.

© 2010 Tyco International Ltd. and its respective companies. All rights reserved. AD0158-DS-201002-R01-LT-EN

www.americandynamics.net

