

Orchestra² - Ref. ORC50

NEW

Powerful Intuitive and Ergonomic Remote Controller for Rental and Staging/
Multi-venues/Integration



Special tips

The Orchestra² can be controlled by an external controller from CRESTRON®, AMX® or any other major control system.

Orchestra² at a glance

- ▶ User-friendly and powerful Remote Controller
- ▶ Controls simultaneously up to 6 screens in single or multiple display configuration
- ▶ Can store up to 64 presets per screen selection
- ▶ Controls a large number of Analog Way's Seamless Switchers
- ▶ Off-Line Programming
- ▶ Snap Function
- ▶ Equipped with a USB port, the complete configuration of the event can be saved for future use

To control the following Seamless Switchers

- | | |
|---------------------------|------------------------------------|
| ▶ DVX8044: Di-VentiX II | ▶ STE100: Smart Edge |
| ▶ EKS500: Eikos | ▶ EKS550: Eikos ² |
| ▶ EKS400: Eikos LE | ▶ SPX450: Saphyr |
| ▶ SMX200: Smart MatriX | ▶ PLS350: Pulse ² |
| ▶ SMX100: Smart MatriX LE | ▶ PLS350: Pulse ² -3G |
| ▶ PLS300: Pulse | ▶ QVU150: QuickVu |
| ▶ PLS200: Pulse LE | ▶ QVU150: QuickVu-3G |
| ▶ SQD200: Smart Quad | ▶ QMX150: QuickMatriX |
| ▶ STE200: Smart Edge FX | ▶ SMX250: SmartMatriX ² |

Technical Specifications

- ▶ **User Controls**
 - TFT touch screen, 7" (18 cm)
 - Buttons for direct access to inputs
 - Buttons for direct access to effects
 - User preset buttons
 - Take, Freeze, Main and Preview selection
 - T-Bar for smooth manually controlled transitions
 - Joystick for easy and fast set up of image or effect parameters
- ▶ **Connectors**
 - RJ45 for TCP/IP Ethernet connection
 - USB port
 - Auxiliary VGA
 - BNC for desk light

External Programming

All Presets can be prepared on the Orchestra² and recalled by Control Systems. Templates can be selected and filled by chosen source. Simple and affordable, the Orchestra² saves time and money by programming complicated presets which can be recalled by a third party controller and later changed without reprogramming the third-party controller.

Dimensions:

- ▶ Compatible 19", 6U
- ▶ D 17.7" x W 17.7" x H 7"
- ▶ D 450 mm x W 450 mm x H 180 mm

Weight:

- ▶ 9 kg
- ▶ 20 lbs

Power Supply:

Internal, universal, automatic 100-250 VAC; 50/60 Hz (100W) (UL, CSA, GS, CE) On/Off power switch

Supplied with:

- ▶ 1 x Power Supply Cord
- ▶ 1 x Rack mount plate and screws
- ▶ 2 x Adjustable feet
- ▶ 1 x User Manual (PDF version)*
- ▶ 1 x Quick Start Guide*

Warranty:

3-year warranty on parts and labor back to factory.



* The Quick Start Guide and the User Manual are also available on www.analogway.com

Specifications subject to change without prior notice

All technical specifications are available on our website

Follow us

