Arecont Vision **AV3110** 3 Megapixel JPEG IP MegaVideo® Camera

AV3110 (Color) AV3110DN (Day/Night)



The AV3110 series network camera is part of Arecont Vision's full line of MJPEG megapixel cameras. It delivers full motion progressive scan 2048 x 1536 video at 15 fps featuring MegaVideo[®] image processing and associated functions such as multiple zoom windows and motion detection in a compact package.

Arecont Vision Advantages:

Superior Low

• 1/2" CMOS Sensor

- eled High Definition Resolution 2048x1536
 Ten times the resolution of IP VGA or analog cameras
- Fastest **A**
 - Up to 15fps in 3 megapixel mode
- Forensic
 - Zoom live or after-event while recording full field of view in HD ... replace PTZ devices
- Reduced
 - Less cameras to install, less wiring, no external
 - power (POE), less NVR licensing fees
- Cost Effic
 - Comparable cost to IP VGA & analog cameras
- Full or 1/4
- Can be selected for either live viewing or archiving purposes Other ke
 - Simultaneous full field of view and Region-of-Interest (ROI)
 - Image cropping allows streaming of full density partial images
 - On-camera motion detection
 - Mechanical IR Cut Filter (DN Version) and more

megapixel technology... beyond imagination

Learn more about our products at WWW.arecontvision.com

www.arecontvision.com

avsales@arecontvision.com +1.818.937.0700 877.CAMERA.8

Model Numbers:

AV3110 - Color AV3110DN - Day/Night

Imaging

- 3 megapixel CMOS image sensor
- 2048(H) x 1536(V) pixel array
- 1/2" optical format
- 3.2 um pixel pitch
- Bayer mosaic RGB filter
- Minimum illumination of:
 - Color: 0.2 Lux @ F1.4
 - Day/Night: 0 Lux, IR sensitive
- Dynamic range 61 dB
- Maximum SNR 49 dB

Full Field of View (FOV) Resolutions

- 2048(H)x1536(V) 3 megapixel 1/4 resolution
- 1024(H)x 768(V)

Cropped Field of View Resolutions

•1920x1200	WUXGA
•1920x1080	HDTV-1080p
•1600x1200	2 MP
•1280x1024	1.3 MP
•1280x720	HDTV-720p
•1024x768	XGA
• 800x600	SVGA
• 704x570	PAL
• 704x480	NTSC
• 640x480	VGA
• 352x288	CIF
• 320x240	SIF

Data Transmission

- Video frame rate up to:
 - 15fps @ 2048x1536
 - 20fps @ 1920x1200
 - · 22fps @ 1920X1080
 - 24fps @ 1600x1200
 - 32fps @ 1280x1024
- Motion JPEG with 21 levels of quality
- TFTP and HTTP image transmission protocols
- 100Base-T Ethernet Network Interface
- Data rate up to 55Mbps
- Multi-streaming: 8 non-identical streams

Programmability

- Auto Exposure (AE) and Gain Control (AGC) >120dB
- On-camera motion detection with 64 detection zones
- Auto backlight compensation
- · Auto multi-matrix white balance
- 50/60Hz selectable flicker control
- Electronic pan, tilt, zoom (PTZ)
- Electronic image rotation 180° flip
- Resolution windowing down to 32x32 pixels window
- Programmable shutter to minimize motion blurring for low-light mode
- Moonlight[™] mode extended exposure and proprietary noise cancellation
- Programmable resolution, brightness, saturation, gamma, sharpness, tint
- Picture-in-Picture: simultaneous delivery of full field of view and zoomed images
- Bandwidth & storage savings by running at 1/4 resolution

Made in USA

Electrical

- General purpose opto-coupled input and output
- Power over Ethernet (PoE): PoE 802.3af
- Power consumption 3 Watts maximum

Regulatory Approvals


- FCC, Class A
- CE and RoHS compliant

Environmental

- Operating temperature 0°C (32 °F) to +50°C (122 °F)
- Storage temperature -20°C (-4 °F) to +60°C (140 °F)
- Humidity 0% to 90% (non condensing)

Mechanical

- 3"W (76 mm) x 2.5"H (63.5 mm) x 1.25"D (31.7mm) (w/o lens)
- 5.8oz (164 grams) (w/o lens)
- C/CS lens mount



Housing Accessories:

Dome 4-I Indoor 4" Vandal Dome Dome 4-O Outdoor 4" Vandal Dome Dome 5-1 Indoor 5" Recessed Dome HSG1-O-W Outdoor Environmental Housing w/Heater/Blower

Lenses:

- MPL4-10 MPL8-16 MPL4.0 MPL6.0 MPL8.0 LENS4-13
- * Other megapixel lenses are also available with Arecont Vision's housing options.



Revised on 12/10/09

avsales@arecontvision.com 818.937.0700 877.CAMERA.8

Arecont Vision reserves the right to change products or specifications without notice

^{©2009} Arecont Vision