

BOLIDE

TECHNOLOGY GROUP

3 Axis Computerized Surveillance Controller



Features

- 3-Axis Joystick control (PTZ)
- Compact, Ergonomic Design
- Various Speed for PTZ control
- LCD Screen with backlight
- Multi Protocol Built-in

Specifications

Communication Port	RS-485/RJ45
Baud Rate	2400/4800/9600bps
System Settings	DIP Less OSD Software
P/T/Z Control	left/right: up/down Iris: up/down Focus: far/near Zoom: in/out Save/Call Preset/Tour/Pattern
Joystick	Three Axis (Left, Right, Zoom In/Out)
Power Supply	DC 12V 200mA
Dimension	218 × 180 × 55.5 mm

Features

- Compact Design, attractive appearance
- Control Pan/Tilt, Focus, Zoom, Iris
- 1200m maximum range
- Controls up to 32 PTZ Dome Cameras

Specifications

Communication Port	RS-485
Baud Rate	2400/4800/9600bps
System Settings	One 8-bit DIP Swither
P/T/Z Control	left/right: up/down Iris: up/down Focus: far/near Zoom: in/out Save/Call Preset
Joystick	Two Axis (Left, Right)
Power Supply	DC 12V 500mA
Dimension	188 × 97 × 70 mm



BE-KB03E