SECURITY MONITOR



BE8009 9" Color CRT Security Monitor



14" Color CRT Security Monitor





Security Monitors

Bolide Security Monitors are perfect for standard security purposes. They are compatible with most input source and features BNC connections for easy installation. Universal voltage function allows input from 90-250V and also compatible with NTSC or PAL. Great for a variety of uses such as store front displays, home security, monitoring a warehouse, etc.



BE8009/BE8043/BE8021

High Resolution 9" /14" /21" Color Monitor with Metal Case

MAIN FEATURES:					
• 0.56MM Stripe Pite	ch				
• High Resolution up	o to 720 lines				
• One Channel Audi	o (Video) Input/Output				
• Auto Adapting AC	Power				
• Worldwide Multipl	e System (NTSC, PAL)				
Specification		Specification		Specification	
9" Color Monitor with Metal Case		14" Color Monitor with Metal Case		21" Color Monitor with Metal Case	
Teletron	9 Inches	Teletron	14 Inches	Teletron	21 Inches
Video In/Output	BNC Interface	Video In/Output	BNC Interface	Video In/Output	BNC Interface
Control Mode	Contrast, Brightness,	Control Mode	Contrast, Brightness	Control Mode	Contrast, Brightness
	Color Saturation,		Color Saturation,		Color Saturation,
	Tint, Volume, Power		Tint, Volume, Power		Tint, Volume, Power
Power Source	Ranged from 90-250V	Power Source	Ranged from 90-250V	Power Source	Ranged from 90-250V
Resolution	720 Lines	Resolution	420 Lines	Resolution	420 Lines
Video System	NTSC, PAL	Video System	NTSC, PAL	Video System	NTSC, PAL
Convergence	Maximum 0.4mm	Convergence	Maximum 0.4mm	Convergence	Maximum 0.4mm
Operating Temp.	0°C ~ 40°	Operating Temp.	0°C ~ 40°	Operating Temp.	0°C ~ 40°
Operating Humid.	10 ~ 90%	Operating Humid.	10 ~ 90%	Operating Humid.	10 ~ 90%
*Specifications are subject to change w	vithout notice. Please call for up-to-date inform	ation.			

BE8001/BE8012/BE8017

High Resolution 10" /14" /17" B/W Monitor with Metal Case MAIN FEATURES:

- With 1000 lines resolution
- Universal Power
- Auto Adapting AC Power
- Worldwide Multiple System (NTSC, PAL)

Specification	, , , , , ,	Specification		Specification			
10" B/W Monitor with Metal Case		14" B/W Monitor with Metal Case		17" B/W Monitor with Metal Case			
Teletron	10 Inches	Teletron	14 Inches	Teletron	17 Inches		
Video In/Output	BNC Interface	Video In/Output	BNC Interface	Video In/Output	BNC Interface		
Control Mode	Contrast, Brightness,	Control Mode	Contrast, Brightness	Control Mode	Contrast, Brightness		
	Color Saturation,		Color Saturation,		Color Saturation,		
	Tint, Volume, Power		Tint, Volume, Power		Tint, Volume, Power		
Power Source	Ranged from 90-250V	Power Source	Ranged from 90-250V	Power Source	Ranged from 90-250V		
Resolution	1000 Lines	Resolution	1000 Lines	Resolution	1000 Lines		
Video System	NTSC, PAL	Video System	NTSC, PAL	Video System	NTSC, PAL		
Convergence	Maximum 0.4mm	Convergence	Maximum 0.4mm	Convergence	Maximum 0.4mm		
Operating Temp.	0°C ~ 40°	Operating Temp.	0°C ~ 40°	Operating Temp.	0°C ~ 40°		
Operating Humid.	10 ~ 90%	Operating Humid.	10 ~ 90%	Operating Humid.	10 ~ 90%		
*Specifications are subject to change without notice. Please call for up-to-date information.							



For Technical Support, Please Call: 1-800-355-355-0895

18605 East Gale Ave. Suite #168 City of Industry, CA 91748 Email: sales@bolideco.com • WEBSITE: www.bolideco.com