

BN5002M

IPAC MEGA PIXEL SERIES IP BOX CAMERA



iPac™

Features:

- 1/3" Ex-view 1.3 Mega Pixel CCD
- High Resolution: 1280 x 960 pixels
- H.264 Video Compression, Mult-Stream
- Audio compression: G723.1/6.3kbps
- RS-485 for external device control
- Built-in SD Card (MiniSD Supported) for local recording
- Advanced Digital Zoom In/Out, Slow Shutter
- Advanced Mechanical IR Cut-Filter for low light condition
- Support FTP/SMTP email support
- BNC output for external monitor
- Built-in Web Server and network interface



Specification:

Model No.	BN5002M
Video Compression	H.264
Image Sensor	1/3" Exview 1.3 Mega Pixel CCD
Minimum Illumination	0.02 lux
Day/Night	Mechanical IR-Cut Filter
Resolution	1280 x 960 @ 22fps, 640 x 480 @ 30fps MJPEG 1280 x 960 @ 4fps
Stream Range	VBR/CBR 50kb - 6M
Motion Detection	Built-in
Network Protocol	RTP/RTSP, TCP/UDP, IPv4/IPv6, HTTP, DHCP, PPPoE, DDNS, SMTP, FTP
Onvif	v1.01/v1.02
Audio	G723.1/6.3kbps Two Audio
Video	1 x BNC 75ohm
Alarm	1 channel alarm in/out
S/N Ratio	More than 50dB
White Balance	AWB/Push
AGC	Auto
BLC	On/Off
Electronic Shutter	Auto/Manual
Gamma	0.45
SD Card	mini SD, up to 32GB
Power	DC12V / POE
Power Consumption	420mA

For more information or technical support, please call (909) 305-8889 or log on to www.bolideco.com

468 South San Dimas Avenue, San Dimas CA 91773 | Tel: (909) 305-8889 Fax: (909) 305-0999

Bolide Technology Group makes no representation concerning the legality of certain product application. We encourage you to check and comply with all applicable local state, and federal laws. Specification and availability are subject to change without notice. All trademarks, registered trademarks, and names are the property of their respective owners.