

COHU

Series 7510^{HD} H.264 1080p30 Fixed Camera System



- ▶ HDTV 1080p30 Image Quality
- ▶ H.264 Main Profile Video Compression
- ▶ RTP/RTSP Streaming Protocol
- ▶ Sensitive Day/Night Technology
- ▶ On-Board Recording using SDHC
- ▶ Flexible Event Management Programming
- ▶ Digital I/O Connections
- ▶ Pre-Post Event Recording
- ▶ Power-over-Ethernet 802.3af Support
- ▶ Send Snapshots and Video to FTP Site
- ▶ Automated Event Timer with Snapshot Capture
- ▶ Web Configuration, Viewing and Control

The 7510^{HD} series is the latest addition to Cohu's expanding family of HDTV products, offering best-in-class image quality, event management processing and network stability you can rely on.

The performance standards of the 7510^{HD} series are ideal for requirements encountered in security surveillance and remote monitoring applications. Its robust design insures years of continuous operation even in the most demanding environments.

Using a powerful encoding engine, the 7510^{HD} is capable of streaming multiple, individually configured H.264 and MJPEG streams.

Features include full HD resolution video of 1080p30 (1920 x 1080), H.264 and MJPEG video compression codecs, on-board SDHC recording, configurable image settings, and powerful event

management processing.

Event triggers include external sensor inputs, video motion detection, user commands and periodic timers.

Event actions include activating an alarm output, store video recordings, send snapshots and video clips to an FTP site, as well as email event notifications.

Designed with the installer in mind, an analog video output, along with remote back focus, makes installation easy.

Using the One-Touch-Focus feature for sharp images greatly reduces installation time and allows fine focus adjustments from a remote computer, eliminating the need for manual focus adjustments at the camera.

Network and security features include static or dynamic IP addressing, domain name, bandwidth limit setting,

authentication rules and network time server support.

The 7510^{HD} provides a full function web server interface, allowing complete administrative and operator control capabilities. Administrative features include configuring network settings, user password assignments, setting video streaming properties, event management programming and assigning camera ID labels.

Access to the camera is fully protected by username/password authentication.

Cohu delivers years of clean, reliable images and backs it with a world-class three year warranty.



Series 7510^{HD}

H.264 1080p30 Fixed Camera System



Camera

SENSOR CHARACTERISTICS

Sensor Type: 1/3" CMOS
Scanning Mode: Progressive
Active Pixels: 1920 x 1080
Resolution/Frame Rate: 1080p30
Shutter: Rolling
Camera Format: Day/Night [IR filter]
IR Range (nm): 800 to 940
Dynamic Range: 70dB

SENSITIVITY (SCENE, F1.4, USABLE VIDEO)

Color Mode: 0.02 fc (0.2 lux)
Mono Mode: 0.005 fc (0.05 lux)

LENSES

Mount: CS, C with Adaptor Ring
Formats: 1/3", 1/2", 2/3" and 1"
Iris Drive: Manual Iris Only
Focus: Manual [One Touch-Remote-Focus]

IMAGE CONFIGURATION PROPERTIES

Shutter: Auto, Optimize Speed, Optimize Quality
Saturation: Manual [0-1.98]
Contrast: Manual [0.00 -1.00]
Brightness: Manual [0.2 to 1.0]
White Balance: Auto [Selectable Region of Interest]
Integration Level: Disabled, 2x, 4x
Sharpness: High, Medium, Low, XLow
Orientation: Normal, 180°, Horizontal, Vertical
Gain: Peak Detect, Dark Detect, Average, Average Clip
AC Lighting Flicker Adjustment: 50Hz, 60Hz
Cropping: Yes

Encoding

VIDEO STREAMS

Compression Types: H.264 or MJPEG
Video Streams:
Three (3) Individually Configurable Streams
Each Stream Configurable for H264 or MJPEG
Video Stream Resolutions:
Stream 1: [1080p, 2M, 1.2M, 720p, 480p, VGA, SIF, QVGA]
Stream 2: [480p, SIF]

Stream 3: [480p, SIF]

Video Stream Frame Rate: 30, 15, 10, 7.5, 5, 4, 3, 2, 1

Video Stream Data Rate: 256Kb to 11Mb

Video Stream Latency: 4 frames (133 msec)
(Does not include network routing or client rendering latency)

Analog Video: NTSC or PAL [Enabled/Disabled]

AUDIO

Codec: Two-way, G.711 PCM 8K Hz
Built-in Microphone, Mic/Line in, Line out

Event Input/Output

DIGITAL I/O

Sensor Input: One (1) dry contact, NO or NC
Control Output: One (1) Open Collector

VIDEO MOTION DETECTION

VMD Array: 12 x 8 Detection Cell Grid
Windows: Up to 4 Monitored Simultaneously
Regions of Interest: [1 x 1 up to 12 x 8]
Region of Interest Modes: Include, Exclude, Disable
Sensitivity: [1-255]
Size: [0-100]

Event Management

EVENT TRIGGERS

External Alarm Input
Video Motion Detection
User Command
Timer

EVENT ACTIONS

Activate Alarm Output
Record Pre/Post Event Snapshots and Video
FTP Snapshot, Video or Both
Email Snapshot, Video or Both

ON-BOARD RECORDING

Type: Class 6 SDHC flash cards
Memory: Up to 32GB
Format: mp4
Playback: Download to client

Web Server Capabilities

CONFIGURATION SETTINGS

Network, Video Stream, Image Properties, OSD, Security and Upgrades

AUTHENTICATION

None, Basic [User/Password], Access Hours, HTTPS, Certificate

BROWSER SUPPORT

Internet Explorer™, Firefox™, Safari™, Chrome™, Opera™, or Mozilla

MEDIA PLAYER SUPPORT

VLC Player, Apple QuickTime, Windows Media Player, and Core Player

Communication Interfaces

NETWORK

Ethernet: 10/100BaseT, 802.3u
Network Protocols:
TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP, DNS, ARP, ICMP, NTP, UPnP, ZeroConf, APIPA, CIFS, SNMP, UDP multicast, FTP, SMTP, Telnet,

VIDEO

ONVIF, PSIA, Cohu 7500 SDK

On Screen Display (OSD)

ELEMENTS

Camera Description ID: Up to 31 Characters
Time/Date: Time Zone Setting [Disable/Enable]



COHU ELECTRONICS

12367 Crosthwaite Circle
Poway CA 92064-1245
Tel. +1 (858) 391-1800
Fax: +1 (858) 513-1094

Series 7510^{HD}

H.264 1080p30 Fixed Camera System



Electrical

INPUT VOLTAGE

PoE 802.3af, 24 Vac, 12-24 Vdc

POWER

8 watts

Connections

SDHC CARD SLOT

Used for on-camera recording. [SDHC card not included]

NETWORK CONNECTOR

RJ-45, [Ethernet and Power-over-Ethernet]

POWER CONNECTOR

Captive 2-pin screw terminal for 12-24 Vdc or 24 Vac power

ANALOG VIDEO OUT

2.8mm connector. Use analog video cable adapter 7411550-004 [not included]

RESET BUTTON

Sets camera back to factory default settings

MICROPHONE

Built-in mono microphone

AUDIO/TRIGGER CONNECTOR

For connecting an external microphone, amplified loudspeakers, alarm trigger input, and outputs to external devices

Mechanical

WEIGHT

12.45 oz (353g)

DIMENSIONS {D X H X W}

6.136" [155.9mm] x 2.3" [58.6mm] x 3.039" [77.2mm]

CONSTRUCTION/FINISH

Powder coated aluminum

MOUNTING

1/4 - 20 mounting thread. Provided on top and bottom of camera for attachment to camera mount.

Environmental

TEMPERATURE RANGE

50° to 122° (10°C to 50°C)

Certifications

EMISSIONS

FCC, class B part 15

EN 55022: 1998 with A1: 2000, A2: 2003; Class A

CISPR 22: 1997 with A1: 2000, A2: 2002; Class A

AS/NZS CISPR 22: 2002; Class A

IMMUNITY

EN 55024: 1998 with A1: 2001, A2: 2003

CISPR 24: 1997 with A1: 2001, A2: 2002

SAFETY

EN 60950-1: 2001 with A11: 2004

IEC 60950-1: 2001

ROHS

All material and/or components used in the manufacture of the product are in compliance with the EU Directive 2002/95/EC Restriction of Hazardous Substance (RoHS).

Accessories

LENSES

7411549-001 Lens, 1/2", 12-40mm, f1.8, manual iris, CS mount

7411549-002 Lens, 1/2", 4-12mm, f1.4, manual iris, CS mount

7411549-003 Lens, 1/3", 2.8-12mm F1.4, manual iris, CS mount

7411549-004 Lens, 1/2", 1.8-3mm F1.8, manual iris, CS mount

MOUNTS

7411522-001 Universal wall/ceiling mount, adjustable head, 3.5" extension

POE INJECTOR

8180-4 PoE 802.af Injector, US Plug

POE ADAPTER PLUGS

7411555-001 Plug Adapter, Brazil

7411555-002 Plug Adapter, Europe

7411555-003 Plug Adapter, India

7411555-004 Plug Adapter, UK

7411555-005 Plug Adapter, US

ANALOG VIDEO CABLE

7411550-004 Analog Video Cable Adapter, 2.8mm jack to BNC

COHU



COHU ELECTRONICS

12367 Crosthwaite Circle
Poway CA 92064-1245
Tel. +1 (858) 391-1800
Fax: +1 (858) 513-1094

Series 7510^{HD}

H.264 1080p30 Fixed Camera System



Camera Modeling Structure

751 X - X X X X	MODEL OPTIONS	OPTION DESCRIPTION
	PRODUCT SERIES	
	751	Box Camera System, 1080p30 H.264/MJPEG, Digital I/O, Audio
	Power Options	
	1	PoE, 12-24VDC, 24VAC
	Sensor Options	
	2	Day/Night 1920 X 1080 CMOS Sensor
	Unassigned	
	0	None
	Unassigned	
	0	None
	Lens Options	
	0	No Lens
	1	Varifocal, 12-40MM, F1.8, IR corrected
	2	Varifocal, 2.8-12MM, F1.4, IR corrected
	3	Varifocal, 1.8-3MM, F1.4, IR corrected

Camera Views



COHU



H.264

HD 1080

MJPEG



Onvif

COHU ELECTRONICS

12367 Crosthwaite Circle
Poway CA 92064-1245
Tel. +1 (858) 391-1800
Fax: +1 (858) 513-1094