

CCT2L00

2 Megapixel Box TVI Camera





Description:	Features:
The CCT2L00 mini box camera provides high quality video at 2 megapixel resolution over existing coaxial cable. Costar's new line of HDTVI	 2 Megapixel Resolution 1/2.8" CMOS Image Sensor Back Light Compensation (BLC)
cameras are compatible with the ET Series DVRs and StarNET Video Management Software.	 Digital Noise Reduction (DNR) True Wide Dynamic Range (TWDR) Up-the-Coax (UTC)
StarNET is the remote access software that allows users to remotely view live and recorded video. StarNET incorporates features such as advanced event notification, map monitoring, system status monitoring and many more.	• Up-the-Coax (UTC) • 12VDC or 24VAC



CCT2L00 Specifications

Model	Lens	Resolution
CCT2L00	Not included	2 Megapixel

Power		
Source	12VDC or 24VAC	
Consumption	2.5 watts (375mA)	
Sensor and General Information		
Image Sensor	1/2.8" Sony CMOS	
Signal System	PAL/NTSC	
Resolution (H x V)	1920x1080	
Lens Focal Length		
Iris Control	DC Auto Iris	
Frame Rate	PAL:25fps ,NTSC:30fps	
IR LED		
IR Wavelength		
IR Range		
	Color DSS: 0.00008 Lux	
Minimum Illumination	BW DSS: 0.00008 Lux	
	BW D33. 0.00008 Lux	
Shutter Speed	Auto/ 1/50 ~ 1/60,000sec	
S/N Ratio	More than 42dB(AGC off)	
Up the Coax	Pelco C, UTC (H)	
Video Features		
Max Distance	UTP:985 FEET (300m)	
	HD-TVI(1080P), HD-AHD(1080P)	
Video Output	CVBS(960H)1Vp-p Composite	
	Output(75 Ω /BNC)	
Camera Functions		
Auto Gain Control	0-20 steps	
Brightness	0-20 steps	
Day & Night	IR Cut Filter	
Defog	Yes	
Motion Detection	Yes	
Digital Noise Reduction	3D-NR	
Wide Dynamic Range	WDR 120dB	

General Information		
Material	Metal Casing	
Humidity	90% RH Max	
Temperature	-4°F ~ 122°F	
Dimensions WxHxD	2.05" x 2.20" x 3.86"	
Weight	0.48lbs	
Approvals	FCC, CE	

Dimensions



