

Costar

CRINEXSN04
CRINEXSN08
CRINEXSN16

4, 8 or 16 Channel iNEX Network Video Recorder



- Linux embedded Network Area Storage (NAS) System
- Multiple recording server solution for 4, 8 or 16 channels
- Includes Federation Lite to allow remote connections to up to 256 sites
- Centralized monitoring for Costar Digital Video Recorders , IP Cameras and Web-servers
- High quality mega pixel recording performance in H.264, MPEG4, and MJPEG
- High quality real time recording at 2 mega pixel resolution
- Supports up to 10 LAN and 2 WAN remote connections
- No annual per camera license
- Powerful event handling and log management
- iNEX Client remote software upgrade and system setup
- Self-recovery operating system
- Multiple tab based user interface for scalable operation
- Map integration
- SN system supports...

up to 8 iNEX Lite servers that each record up to 16 cameras per server for a total of 128 IP cameras
up to 16 EVRs that each record up to 16 cameras for a total of 256 analog cameras



Costar
VIDEO SYSTEMS

	CRINEXSN04	CRINEXSN08	CRINEX16
Monitoring			
Video Inputs	4 Network	8 Network	16 Network
Video Outputs	Network-iNEX Client		
Display Resolution	Network-iNEX Client		
Display Rate	Network-iNEX Client		
Record & Playback			
Compression	MPEG4, MJPEG, H.264		
Recording Rate	120 ips @ 2M	240 ips @ 2M	480 ips @ 2M
Playback Rate	N/A		
Recording Mode	Time-Lapse, Event, Pre-Event		
Search Mode	Date/Time, Calendar, Event, Motion, Museum		
System			
Operating System	Embedded Linux		
Storage	Max 4TB, RAID 0,1		
Data Export Medium	Network-iNEX Client		
Network			
Connection	2x Gigabit Ethernet		
Protocols	Manual, ADSL, DHCP, DVRNS		
Remote Software	iNEX Client		
Interface			
Audio In/Out	Network-iNEX Client		
Alarm In/Out	Network-iNEX Client		
External Interface	1 UBS 2.0 Rear (Reserved for firmware upgrade)		
User Interface	N/A		
General			
Dimensions (W x H x D, mm)	8.66"x3.5"x11.69" (220x88x297mm)		
Operating Temperature (°F)	41°F to104°F	41°F to104°F	41°F to104°F
Operating Humidity	90% RH Max	90% RH Max	90% RH Max
Power	AC100-240V~, 50/60 Hz, 8-4A		
Approvals	FCC, CE, UL		



101 Wrangler, Suite 201 • Coppell, Texas 75019 • Phone: 469-635-6800 • Fax: 469-635-6822 • Toll Free: 1-888-694-STAR (7827)

www.costarvideo.com

Specifications and design are subject to change without notice. Conversions: 1" = 25.4mm Measurement conversions are approximate.