8 or 16 Channel Standard Series
iNEX Network Video Recorder

- Enterprise level solution for recording multiple channels and managing analog digital video recorders

- Multiple recording server solution for 8 or 16 channel servers

- Centralized monitoring for Costar Digital Video Recorders , IP Cameras and Web-servers

- High quality mega pixel recording performance in H.264, MPEG4, and MJPEG

- Supports up to 64 LAN and 20 WAN remote connections

- No annual per camera license

- Powerful event handling and log management

- iNEX Client remote software upgrade and system setup

- Multiple tab based user interface for scalable operation

- Map integration

- Standard system supports…

    up to 2,048 IP channels using up to 64 record servers

    up to 1,024 Costar Video Analog DVRs using edgelink technology

CRINEX08R & CRINEX16R Specifications

	CRINEX16R	CRINEX08R
onitoring		
Video Inputs	16 Network i5	08 Network i3
Video Outputs	VGA, DVI, HDMI	VGA, DVI, HDMI
Display Resolution	1920 x 1200	1920 x 1200
Display Rate	480 ips @ 2M	240 ips @ 2M
Record & Playback		
Compression	MPEG4, MJPEG, H.264	
Recording Rate	480 ips @ 2M	80 ips @ 2M, 240 ips @ D1
Playback Rate	64 ips @ 2M	32 ips @ 2M
Recording Mode	Time-Lapse, Event, Pre-Event	
Search Mode	Date/Time, Calendar, Evnet, Motion, Museum, Text-in (DVR)	
System		
Operating System	Windows 7 Pro	
Storage	Up to 4TB (6TB without DVD)	Up to 4TB (6TB without DVD)
Data Export Medium	USB(HDD, CD-RW, Flash Drive, DVD¡¾RW), SATA DVD±RWArchiving	
Network		
Connection	10/100/1000 Ethernet	10/100/1000 Ethernet
Protocols	Manual, DHCP	Manual, DHCP
Remote Software	iNEX Client	iNEX Client
Interface		
External Interface	6 x USB 2.0	6 x USB 2.0
User Interface	Mouse, PC Keyboard, Remote Keyboard	
General		
Dimensions (W x H x D, mm)	227 x 272 x 345	227 x 272 x 345
Unit Weight (kg)	14.8 kg	14.8 kg
Operating Temperature (ºF)	41ºF to 104ºF	41ºF to104ºF
Operating Humidity	90% RH Max	90% RH Max
Power	AC100-240V~, 50/60 Hz, 3.0-1.5A	
Approvals	FCC, CE, UL*, KCC, KC	

Specifications and design are subject to change without notice. Conversions: 1" = 25.4mm Measurement conversions are approximate.