
ASPIRE IC8DT

Aspire[™] 8" 2-Way Single-Point Stereo In-Ceiling Speaker

- > Audiophile performance 2-way in-ceiling loudspeaker
- > Designed for single-point stereo applications
- > Dual voice coil 8" woven poly-glass composite woofer
- > Dual 1" advanced synthetic polymer dome tweeters
- > 4th order stereo crossover
- > Steel composition woofer basket
- > Vented pole piece
- > "Zero-bezel" frameless steel grille, paintable
- > Three-point spring-loaded toggle clamp mounting system
- > 100 Watts/Ch program power handling
- > 48Hz-20kHz frequency response
- > 8 Ohms nominal impedance per channel



The Aspire line strikes a perfect balance between performance and price, delivering pristine, impactful sound quality, with minimal impact on your decor thanks to paintable zero-bezel grilles. Streamlined installation is facilitated through a three-point, spring-loaded toggle clamp mounting system optimized to minimize interference with obstructions within the ceiling space.

The Aspire IC8DT model is a single in-ceiling loudspeaker featuring an 8 inch dual voice coil woofer and dual 1 inch dome tweeters. It is designed to produce stereo sound in the space of a single speaker, perfect for bathrooms and other small spaces. Its high-end, woven poly-glass composite woofer and advanced synthetic polymer tweeters afford rich, impactful low end and crisp, soaring highs. A precisely tuned stereo 4th order crossover ensures a full, warm and detailed response across the spectrum. Power handling is an impressive 100 Watts (program) per channel, with a wide frequency response from 48 Hz to 20 kHz (±3 dB).

SPECIFICATIONS

Features & Performance

Woofer: Dual voice coil 8 inch (203 mm) woven poly-glass composite

w/rubber surround, vented pole piece & steel basket

Tweeter: (2) 0.98 inch (25 mm) advanced synthetic polymer dome,

ferrofluid cooling, post-mounted

Crossover: 4th order

Crossover Frequency: 2.5 kHz

Impedance: 8 Ohms nominal per channel





Frequency Response: 48 Hz to 20 kHz (±3 dB) Frequency Range: 40 Hz to 20 kHz (-10 dB) Power Handling: 100 Watts program per channel Sensitivity: 89.5 dB @ 1W/1m per channel

Connections

Input: (2 sets of 2) spring terminals; Maximum Wire Size: 10 AWG

Environmental

Temperature: 41° to 104°F (5° to 40°C) Humidity: 10% to 90% RH (non-condensing)

For indoor use only

Construction

Baffle: ABS plastic, black

Grille: Steel with textured finish, paintable, magnetically-held "zero-bezel"

frameless

Mounting: Flush ceiling mount using 3 integral spring-loaded toggle clamps, 1.35 in (34 mm) maximum surface thickness, 4.47 in (114 mm) minimum mounting depth, 10.8 in (275 mm) diameter recommended

cutout

Dimensions

Diameter: 11.64 in (296 mm) **Depth:** 4.66 in (119 mm)

Weight

7.55 lb (3.43 kg)



ASPIRE IC8DT Aspire™ 8" 2-Way Single-Point Stereo In-Ceiling Speaker

MODELS & ACCESSORIES

Available Models

ASPIRE_IC8DT-W-T-EACH: Aspire™ 8" 2-Way Single-Point Stereo In-Ceiling Speaker, White Textured, Single

Available Accessories

SPKA-NCTP-IC800: New-Construction Speaker Templates for Excite[™], Aspire[™], & Essence[™] IC8 & IC8DT, 1 Pair

Notes:

Crestron warrants to the original end purchaser that this Crestron Speaker Product, when purchased directly from Crestron or an authorized Crestron Dealer, will be free from defects in material and workmanship for the life of the product except for speaker grills and outdoor rated speakers, which are warranted for five (5) years. Crestron will at its option and expense either repair the defect or replace the Speaker Product with a new or remanufactured Product or a reasonable equivalent. In cases where a new model is substituted, a modification to the mounting surface may be required. If mounting surface modification is required, Crestron assumes no responsibility or liability for such modifications.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

Specifications subject to change without notice. Crestron is not responsible for errors in typography or photography.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, Aspire, and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others.

©2012 Crestron Electronics, Inc.



