

# 8-Port PoDM Power Supply for DM® Switchers

- > Provides a centralized power source for up to 8 PoDM powered devices<sup>[2]</sup>
- > Designed for use with modular DigitalMedia™ switchers using DM 8G+™ I/O cards
- > Compatible with PoH powered HDBaseT™ devices<sup>[2]</sup>
- > Includes front panel indicators for easy troubleshooting
- > Single-space 19" rack-mountable



Power over DM® (PoDM) is a feature of Crestron® DigitalMedia 8G+™ technology that enables operating power for DM 8G+™ transmitters and receivers to be carried alongside video, audio, and data signals over a single CAT5e cable. As part of a complete DM system, PoDM can be used to deliver a centralized power distribution solution for a facility full of transmitter and receiver devices, eliminating all the bulky power packs and reducing the number of AC power outlets normally required at every device location.

The DM-PSU-8 provides power for up to eight PoDM powered devices. It is designed to install at the central switcher location, occupying just a single rack space and requiring just one AC power outlet. Each of its eight POWER ports connects to the POE IN port<sup>[1]</sup> of a [DMC-C](#) input card, [DMC-C-DSP](#) input card, or [DMCO-5 Series](#) output card. A full 15.4 Watts is supplied by each port to handle eight Class 0-3 PoDM devices simultaneously. Connections between the DM-PSU-8 and switcher are made using ordinary CAT5e cables terminated with RJ45 connectors (not included). Front panel LEDs indicate when each port is supplying power to a PoDM powered device.

The DM-PSU-8 is also compatible with HDBaseT™ specifications, and may be used to power PoH (Power over HDBaseT) powered devices that are connected to the DM switcher in the same manner as a PoDM powered device.<sup>[2]</sup> PoDM is intended specifically for use with DM 8G+ based systems.

## SPECIFICATIONS

### Indicators

**PWR:** (1) green LED, indicates operating power supplied via main power input  
**POWER 1 – 8:** (8) green LEDs, each indicates PoDM is active and a PoDM (or PoH) powered device is connected to the corresponding port (via a DM® Switcher I/O card)

### Connectors

**POWER MAX 15.4W/PORT 1 – 8:** (8) 8-wire RJ45, female; PoDM and PoH PSE (Power Sourcing Equipment) ports; Each port connects to the POE IN port of DM Switcher I/O Card; Each port supports one PoDM/PoH PD (Powered Device) up to 15.4W (Class 0-3)

**100-240V~50/60Hz 2.2-1.0A:** (1) IEC 60320 C14 main power inlet; Mates with removable power cord, included

**G:** (1) 6-32 screw, chassis ground lug

### Power Requirements

**Main Power:** 2.2-1.0 Amps @ 100-240 Volts AC, 50/60 Hz

### Environmental

**Temperature:** 32° to 104°F (0° to 40°C)

**Humidity:** 10% to 90% RH (non-condensing)

**Heat Dissipation:** 97 BTU/Hr

### Enclosure

**Chassis:** Metal, black finish, fan-cooled, vented sides

**Faceplate:** Metal, black finish with polycarbonate label overlay

**Mounting:** Freestanding or 1U 19-inch rack-mountable (adhesive feet and rack ears included)

### Dimensions

**Height:** 1.73 in (44 mm)

**Width:** 17.28 in (439 mm);

19.00 in (483 mm) with ears

**Depth:** 6.56 in (167 mm)

### Weight

3.8 lb (1.8 kg)

# DM-PSU-8 8-Port PoDM Power Supply for DM® Switchers



DM-PSU-8 – Rear View

## MODELS & ACCESSORIES

### Available Models

#### DM-PSU-8: 8-Port PoDM Power Supply for DM® Switchers

##### Notes:

1. PoDM interfaces connected to these ports are for intra-building use only and should not be connected to lines that run outside of the building in which the PoDM switch is located.
2. PoDM is only compatible with DM 8G+ and HDBaseT devices. Consult the spec sheet for each individual device to verify its PoDM or PoH capabilities.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron, the Crestron logo, DigitalMedia 8G+, DM, and DM 8G+ are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. HDBaseT is either a trademark or registered trademark of the HDBaseT Alliance in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2013 Crestron Electronics, Inc.

# DM-PSU-8 8-Port PoDM Power Supply for DM<sup>®</sup> Switchers

