

# DigitalMedia 8G™ Fiber Transmitter 201

- > DigitalMedia 8G™ Fiber transmitter and multimedia interface
- > Built-in 2x1 AV switcher with auto-switching and analog audio-breakaway
- > QuickSwitch HD® technology achieves fast, reliable switching
- > Connects to a DM® switcher or receiver over one multimode fiber strand<sup>[1]</sup>
- > Supports cable lengths up to 1000 ft (300 m) using CresFiber® 8G, or 500 ft (150 m) using other multimode fiber<sup>[1]</sup>
- > Provides HDMI® and RGB/component video inputs<sup>[3]</sup>
- > Also supports DVI and DisplayPort Multimode sources<sup>[2]</sup>
- > Handles video resolutions up to Full HD 1080p
- > Handles computer resolutions up to WUXGA
- > Handles Dolby Digital®, DTS®, and uncompressed 7.1 linear PCM audio
- > HDCP compliant
- > Includes a mini-TRS stereo analog audio input
- > Includes a local HDMI monitor output
- > Detects and reports detailed video and audio input information
- > Performs automatic AV signal format management via EDID
- > Provides a 10/100 Ethernet LAN connection
- > Enables device control via CEC and Ethernet
- > Enables USB HID signal extension for a local computer
- > Compatible with Crestron USB over Ethernet Extenders<sup>[4]</sup>
- > Allows quick, easy setup and diagnostics
- > Low-profile surface-mount design
- > Universal power pack included

The DM-TX-201-S provides a simple interface for computers and high-definition AV sources as part of a complete Crestron® DigitalMedia™ system. Its low-profile, surface-mountable design makes it ideal for installation beneath a conference table, inside a lectern or equipment rack, or at virtually any other location in a boardroom, classroom, auditorium, or residence. It functions as a DM 8G® Fiber transmitter and switcher, providing HDMI®, VGA, and analog audio inputs along with Ethernet and USB HID ports for a total connectivity solution. It connects to the head end or display location using a single multimode fiber strand.<sup>[1]</sup>

## DigitalMedia 8G™ Fiber

As the leader in HDMI and control system technologies, Crestron developed DigitalMedia (DM®) to deliver the first complete HD AV distribution system to take HDMI to a higher level. DigitalMedia allows virtually any mix of HDMI and other AV sources to be distributed throughout a home, office, school, or virtually any other facility. The latest generation of DM is called DigitalMedia 8G (DM 8G). Engineered for ultra high-bandwidth and ultimate scalability, DM 8G provides a true one-wire lossless transport for moving high-definition video, audio, Ethernet, and control signals over a choice of low-cost twisted pair or fiber optic cable.

DM 8G Fiber uses multimode fiber to enable signal distribution between buildings and over lengthy wire runs. DM 8G Fiber handles uncompressed



Full HD 1080p video signals with support for HDCP, as well as computer signals up to WUXGA. All signals are transported over one strand of multimode fiber, supporting distances up to 1000 feet (300 m) using CresFiber® 8G, or 500 feet (150 m) using other multimode fiber optic cable.<sup>[1]</sup>

## Multimedia Computer/AV Interface

The DM-TX-201-S provides simple switching between two inputs. The inputs can be configured to switch automatically or be controlled through a Crestron control system. Inputs include:


- **HDMI** — Provides a digital multimedia input for mobile devices, computers, and AV sources with resolutions up to HD 1080p60 and WUXGA. Also handles DVI and DisplayPort Multimode signals using an appropriate adapter or interface cable<sup>[2]</sup>.
- **RGB** — This VGA type input handles analog RGB signals up to WUXGA 1920x1200 pixels, as well as analog video up to 1080p60<sup>[3]</sup>. A 1/8" (3.5mm) stereo audio input is included to accommodate the analog audio signal from an unbalanced line-level source or headphone output.

Note: Audio breakaway capability enables the analog audio input to be used with either video input.

A single fiber strand connects the DM-TX-201-S to a DM switcher or receiver, transporting video, audio, control, and networking signals all through one simple SC type optical connection.<sup>[1]</sup> Used with a single DM 8G Fiber Receiver/Room Controller and optional Crestron control system, the DM-TX-201-S affords a simple solution for extending a computer or AV signal to a single display. As part of a larger system using a DM-MD series switcher, multiple DM-TX-201-Ss may be installed to enable the distribution of several sources at different locations to feed multiple displays throughout any room or larger facility.

In addition to its DM 8G Fiber output, there is also an HDMI output provided to feed a local HDMI or DVI monitor, eliminating the need for an extra outboard distribution amp or other hardware.

# DM-TX-201-S DigitalMedia 8G™ Fiber Transmitter 201



DM-TX-201-S – Top, Front, and Bottom Views

## LAN Connectivity

Along with high-definition AV and control, DigitalMedia also integrates high-speed Ethernet networking for a total signal distribution solution. The DM-TX-201-S includes a 10/100 Ethernet port, providing a convenient LAN connection for a local network device.

## USB Extender

The DM-TX-201-S also functions as a keyboard/mouse extender, allowing the connected computer (or other USB HID-compliant host) to be controlled by a mouse and/or keyboard located at a presentation lectern, conference table, or some other remote location. Expanded USB signal routing capability is available using Crestron [USB over Ethernet Extenders](#)<sup>[4]</sup>.

## CEC Embedded Device Control

The primary objective of every Crestron system is to enable precisely the control desired for a seamless user experience. DigitalMedia provides an alternative to conventional IR and RS-232 device control by harnessing the CEC (Consumer Electronics Control) signal embedded in HDMI. Through its connection to the control system, the DM-TX-201-S provides a gateway for controlling the connected source device right through the HDMI connection, potentially eliminating the need for any dedicated control wires or IR emitters.

## Compact and Versatile

The DM-TX-201-S is designed to be mounted to a flat surface or placed on a shelf. It is compact enough to fit discreetly inside a presentation lectern or beneath a table, and can even be attached to a rack rail in the back of an equipment cabinet. An array of indicators is provided for easy setup and troubleshooting.

## A Digital Upgrade for Legacy Systems

The DM-TX-201-S also affords a perfect signal converter for integrating DigitalMedia with analog-based systems like Crestron [MPS](#), [QuickMedia](#)<sup>®</sup>, and the CEN-RGBHV Series. A simple HD15 VGA cable connected between the output of an MPS system and the input of the DM-TX-201-S allows every RGB, component, S-Video, and composite video input on the MPS to be converted to DigitalMedia<sup>[3]</sup>. Analog audio is converted similarly through a simple unbalanced stereo audio cable. The DM-TX-201-S's HDMI input may also be used to expand the input capabilities of the MPS system to handle digital AV sources.

Please refer to the [DigitalMedia Resources Webpage](#) at <http://www.crestron.com/dmresources/> for additional design tools and reference documents.

## SPECIFICATIONS

### Video

**Switcher:** 2x1 combination digital/analog switch, Crestron QuickSwitch HD<sup>®</sup>

**Input Signal Types:** HDMI<sup>®</sup>, DVI<sup>[2]</sup>, DisplayPort Multimode<sup>[2]</sup>, RGB/VGA, component<sup>[3]</sup>, S-Video<sup>[3]</sup>, composite<sup>[3]</sup>

**Output Signal Types:** DM 8G<sup>®</sup> Fiber (DigitalMedia™ over one multimode fiber optic strand), HDMI, DVI<sup>[2]</sup>

**Formats:** DM 8G Fiber, HDMI, DVI, HDCP content protection support, RGBHV, RGBS, RGsB, YPbPr, Y/C, NTSC, PAL

**Input Resolutions, HDMI & DVI, Progressive:** 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock

**Input Resolutions, HDMI & DVI, Interlaced:** 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock

**Input Resolutions, RGB:** 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 1024x768@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz,

# DM-TX-201-S DigitalMedia 8G™ Fiber Transmitter 201

1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1152@60Hz  
**Input Resolutions, Component<sup>[3]</sup>:** 480i, 576i, 480p, 576p, 720p50, 720p60, 1080p24, 1080i25 (1125 lines), 1080i30, 1080p30, 1080p50 (1125 lines), 1080p60  
**Input Resolutions, Composite and S-Video<sup>[3]</sup>:** 480i, 576i  
**Output Resolutions:** Matched to inputs  
**Analog-To-Digital Conversion:** 10-bit 165 MHz per each of 3 channels

## Audio

---

**Switcher:** 2x1 combination digital/analog switch  
**Input Signal Types:** HDMI, DisplayPort Multimode<sup>[2]</sup>, analog stereo  
**Output Signal Types:** DM 8G Fiber, HDMI  
**Formats, HDMI:** Dolby Digital<sup>®</sup>, Dolby Digital EX, DTS<sup>®</sup>, DTS-ES, DTS 96/24, up to 8ch PCM  
**Formats, Analog:** Stereo 2-channel  
**Analog-To-Digital Conversion:** 24-bit 48 kHz  
**Performance (analog):**  
Frequency Response: 20Hz to 20kHz ±0.75dB;  
S/N Ratio: >90dB, 20Hz to 20kHz A-weighted;  
THD+N: <0.05% @ 1kHz;  
Stereo Separation: >90dB

## Communications

---

**Ethernet:** 10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP  
**USB:** Supports signal extension of USB HID class devices, expandable to support virtually any USB 1.1 or 2.0 device using Crestron USB-EXT-DM USB over Ethernet Extenders<sup>[4]</sup>  
**DigitalMedia:** DM 8G Fiber, HDCP, EDID, CEC, Ethernet  
**HDMI:** HDCP, EDID, CEC

NOTE: Supports management of HDCP and EDID; supports pass-through and management of CEC between HDMI source and sink, or between HDMI source and a control system

## Connectors

---

**LAN:** (1) 8-wire RJ45 female, shielded;  
10Base-T/100Base-TX Ethernet port  
**DM OUT MMF/SC:** (1) SC female optical fiber connector;  
DM 8G Fiber output ;  
Connects to DM 8G Fiber input of a DM switcher, receiver/room controller, or other DM device via CresFiber 8G fiber optic cable<sup>[1]</sup>  
**HDMI OUT:** (1) 19-pin Type A HDMI female;  
HDMI digital video/audio output;  
Also supports DVI<sup>[2]</sup>  
**PWR 24VDC 0.75A:** (1) 2.1 x 5.5 mm DC power connector;  
24 Volt DC power input;  
PW-2407WU power pack included  
**Ground:** (1) 6-32 screw, chassis ground lug

**USB HID:** (1) USB Type B female;  
USB 2.0 device port for connection to the USB host interface of a computer or other USB HID-compliant host

**HDMI IN:** (1) 19-pin Type A HDMI female;  
HDMI digital video/audio input;  
Also supports DVI and DisplayPort Multimode<sup>[2]</sup>

**RGB IN:** (1) DB15HD female;  
RGB (VGA), component, S-Video, or composite video input<sup>[3]</sup>;  
Formats: RGBHV, RGBS, RGsB, YPbPr, Y/C, NTSC, PAL;  
Input Levels: 0.5 to 1.5 Vp-p with built-in DC restoration;  
Input Impedance: 75 Ohms;  
Sync Input Type: Autodetect RGBHV, RGBS, RGsB, YPbPr;  
Sync Input Level: 3 to 5 Vp-p;  
Sync Input Impedance: 1k Ohms

**AUDIO IN:** (1) 3.5mm TRS mini phone jack;  
Unbalanced stereo line-level audio input;  
Input Level: 2 Vrms maximum;  
Input Impedance: 10k Ohms

## Controls & Indicators

---

**LAN:** (2) LEDs, green LED indicates Ethernet link status, amber LED indicates Ethernet activity  
**DM OUT:** (1) green LED, indicates DM link status  
**PWR:** (1) green LED, indicates operating power supplied via local power pack  
**HDMI IN:** (1) green LED, indicates HDMI input is selected  
**RGB IN:** (1) green LED, indicates RGB input is selected  
**SETUP:** (1) red LED and (1) miniature recessed pushbutton for Ethernet setup  
**RESET:** (1) miniature recessed pushbutton for hardware reset

## Power Requirements

---

**Power Pack:** 0.75 Amps @ 24 Volts DC;  
100-240 Volts AC, 50/60 Hz power pack, model PW-2407WU included

## Environmental

---

**Temperature:** 32° to 104°F (0° to 40°C)  
**Humidity:** 10% to 90% RH (non-condensing)  
**Heat Dissipation:** 61 BTU/Hr

## Enclosure

---

**Chassis:** Metal, black finish, with (2) integral mounting flanges, vented sides  
**Mounting:** Freestanding, surface mount, or attach to a single rack rail

## Dimensions

---

**Height:** 6.47 in (165 mm)  
**Width:** 7.36 in (187 mm)  
**Depth:** 1.24 in (32 mm)

# DM-TX-201-S DigitalMedia 8G™ Fiber Transmitter 201

## Weight

---

24.3 oz (689 g)

## MODELS & ACCESSORIES

### Available Models

---

DM-TX-201-S: DigitalMedia 8G™ Fiber Transmitter 201

### Included Accessories

---

PW-2407WU: Wall Mount Power Pack 24VDC, 0.75A, Universal (Qty. 1 included)

### Available Accessories

---

**CRESFIBER8G-NP:** CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, non-plenum

**CRESFIBER8G-P:** CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, plenum

**CRESFIBER-CONN-SC50UM-12:** CresFiber® Fiber Optic Cable Connector (AFL Telecommunications™), SC 50µm, 12-Pack

**CRESFIBER-TK:** CresFiber® Termination Kit (AFL Telecommunications™)

**CRESFIBER-SINGLE-SC-P:** CresFiber® Simplex Fiber Optic Cable Assembly, 50/125, SC, Plenum

**CRESFIBER-SINGLE-SC-ARMORED-P:** CresFiber® ARMORED Simplex Fiber Optic Cable Assembly, 50/125, SC, Armored, Plenum

**CRESFIBER-SINGLE-SC-CLEAR-NP:** CresFiber® CLEAR Simplex Fiber Optic Cable Assembly, 50/125, SC, Non-Plenum

**CBL Series:** Crestron® Certified Interface Cables

**MP-WP Series:** Media Presentation Wall Plates

**MPI-WP Series:** Media Presentation Wall Plates - International Version

**USB-EXT-DM:** USB over Ethernet Extender with Routing

## Notes:

1. The maximum cable length for DigitalMedia 8G Fiber (DM 8G Fiber) is 1000 ft (300 m) using Crestron [CRESFIBER8G](#) multimode fiber optic cable, or 500 ft (150 m) using Crestron [CRESFIBER](#), Crestron [CRESFIBER-SINGLE-SC](#), or third-party OM3 simplex multimode fiber optic cable. Refer to the [Crestron DigitalMedia Design Guide, Doc. #4546](#) for complete system design guidelines. All wire and cables are sold separately.
2. HDMI requires an appropriate adapter or interface cable to accommodate a DVI signal. [CBL-HD-DVI](#) interface cables are available separately.
3. The RGB/VGA input can actually accept component, composite, and S-Video signals through an appropriate adapter (not included), or via direct interface to Crestron [MPS Series](#) products. However, input sync detection is not provided for composite or S-Video signal types through this connection.
4. Compatible with Crestron [USB-EXT-DM-LOCAL](#) and [USB-EXT-DM-REMOTE](#) USB over Ethernet Extender modules, sold separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron, the Crestron logo, CresFiber, DigitalMedia, DigitalMedia 8G, DM, DM 8G, QuickMedia, and QuickSwitch HD are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby Digital is either a trademark or registered trademark of Dolby Laboratories in the United States and/or other countries. DTS is either a trademark or registered trademark of DTS, Inc. in the United States and/or other countries. HDMI and the HDMI Logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

# DM-TX-201-S DigitalMedia 8G™ Fiber Transmitter 201

