

## 8-Channel 4K HDMI® Input Blade for DM® Switchers

- > Modular input blade for a DM-MD64X64 or DM-MD128X128 switcher
- > Provides eight independent 4K HDMI® inputs
- > Handles video resolutions up to 4K and Ultra HD
- > Handles 3D video and Deep Color
- > Handles Dolby® TrueHD, DTS-HD®, and uncompressed 7.1 linear PCM audio
- > Handles stereo analog audio signals via the optional AUD-BOB-1602 breakout box<sup>[1]</sup>
- > HDCP compliant
- > Occupies a single input blade slot

The DMB-4K-I-HD is an input blade designed for use with any blade-based Crestron® DigitalMedia™ Switcher. It provides eight independent HDMI® inputs with associated analog audio inputs<sup>[1]</sup>. Each HDMI input handles Full HD 1080p, Ultra HD, 2K, and 4K video signals with support for HDCP, Deep Color, 3D, and high-bitrate 7.1 audio. The analog audio inputs are enabled using the optional Analog Audio Breakout Box (model [AUD-BOB-1602](#)<sup>[1]</sup>), providing support for balanced or unbalanced stereo line-level signals.

Please refer to the DigitalMedia Resources Webpage at <http://www.crestron.com/dmresources/> for additional design tools and reference documents.

### SPECIFICATIONS

#### Video

**Input Signal Types:** HDMI®, DVI<sup>[2]</sup>, DisplayPort Multimode<sup>[2]</sup>  
**Formats:** HDMI w/Deep Color, 3D, & 4K; HDCP content protection support  
**Maximum Resolutions:**

Scan Type	Maximum Resolution	Frame Rate	Color Sampling
Progressive	4096x2160 4K DCI	Up to 24 Hz	4:4:4
Progressive	3840x2160 Ultra HD	Up to 30 Hz	4:4:4
Progressive	2560x1600 WQXGA	Up to 60 Hz	4:4:4
Progressive	4096x2160 4K DCI	Up to 60 Hz	4:2:0 <sup>[3]</sup>
Progressive	3840x2160 Ultra HD	Up to 60 Hz	4:2:0 <sup>[3]</sup>
Interlaced	1920x1080 1080i30	Up to 30 Hz	4:4:4

NOTE: Common resolutions are shown; other custom resolutions are supported at pixel clock rates up to 300 MHz

#### Audio

**Input Signal Types:** HDMI, DisplayPort Multimode<sup>[2]</sup>, analog stereo<sup>[1]</sup>  
**Formats, HDMI:** Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby® TrueHD, DTS®, DTS-ES, DTS 96/24, DTS-HD High Res, DTS-HD Master Audio™, Up to 8ch PCM  
**Formats, Analog:** Stereo 2-channel<sup>[1]</sup>  
**Analog-To-Digital Conversion:** 24-bit 48 kHz



**Performance (analog):** Frequency Response: 20Hz to 20kHz ±0.5dB;  
 S/N Ratio: >95dB, 20Hz to 20kHz A-weighted;  
 THD+N: <0.005% @ 1kHz;  
 Stereo Separation: >80dB

**Input Compensation (analog):** ±10 dB

#### Communications

**HDMI:** HDCP, EDID, CEC

#### Connectors

**INPUT HD 1 – 8:** (8) 19-pin Type A HDMI female;  
 HDMI digital video/audio inputs;  
 Also support DVI and DisplayPort Multimode<sup>[2]</sup>

# DMB-4K-I-HD 8-Channel 4K HDMI® Input Blade for DM® Switchers

**ANALOG AUDIO INSERT:** (1) 68-pin VHDCI female;  
Connects to external analog audio breakout box, model AUD-BOB-1602<sup>[1]</sup>;  
Input Impedance: 10k Ohms balanced/unbalanced;  
Maximum Input Level: 4 Vrms balanced, 2 Vrms unbalanced

## Indicators

**ACT:** (1) green LED, indicates blade activity  
**MSG:** (1) red LED, indicates an error message has been generated  
**INPUT HD 1 – 8:** (8) dual-color red/green LEDs, indicate video lock and HDCP status for each corresponding input

## Construction

Plug-in blade, occupies (1) DM switcher input blade slot, includes metal faceplate w/black finish

## Weight

1.6 lb (726 g)

## MODELS & ACCESSORIES

### Available Models

**DMB-4K-I-HD:** 8-Channel 4K HDMI® Input Blade for DM® Switchers

### Available Accessories

**AUD-BOB-1602:** 16-Channel Analog Audio Breakout Box  
**CBL Series:** Crestron® Certified Interface Cables  
**MP-WP Series:** Media Presentation Wall Plates  
**MPI-WP Series:** Media Presentation Wall Plates – International Version

## Notes:

1. Analog audio input capability requires the optional Analog Audio Breakout Box, model AUD-BOB-1602, sold separately.
2. HDMI requires an appropriate adapter or interface cable to accommodate a DVI or DisplayPort Multimode signal. CBL-HD-DVI interface cables are available separately.
3. Support for 4K and UHD at 50/60 Hz with 4:2:0 color sampling will be enabled through a future firmware update.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron, the Crestron logo, DigitalMedia, and DM are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS-HD, and DTS-HD Master Audio are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI and the HDMI Logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

