

## HDMI® Input Card w/Down-mixing for DM® Switchers

The DMC-HD-DSP is an input card for a Crestron® DigitalMedia™ Switcher, providing one HDMI® input. The HDMI input supports HD 1080p60 video and WUXGA computer signals with HDCP, Deep Color, 3D, and multi-channel HD lossless audio - all through a single HDMI cable. The HDMI input can also handle DVI and DisplayPort Multimode signals using an appropriate adapter or interface cable<sup>[1]</sup>.

The DMC-HD-DSP provides all of the features of the [DMC-HD](#) with the addition of internal surround sound down-mixing to enable the simultaneous distribution of uncompressed 7.1 surround sound and 2-channel down-mix signals. The DMC-HD-DSP is recommended for use with Blu-ray Disc® players and other HD sources that output multi-channel surround sound audio via HDMI, allowing the multi-channel signal to reach the surround sound system without requiring any decoding, while also providing a 2-channel down-mix to feed a stereo zone or audio distribution system.

In addition to the HDMI input, the DMC-HD-DSP also includes HDMI and stereo analog audio outputs, and a USB HID device port. The HDMI output can be used to pass the input signal through to a local audio processor or video monitor, or to feed a second DM switcher for output expansion purposes. The analog audio output, which features programmable volume control, breaks out the stereo audio signal from the HDMI input and passes it through to feed a multi-room audio distribution system.

The USB HID port connects to the source device (i.e. computer or media server) at the central equipment rack, allowing it to be controlled by a mouse or keyboard located in another room, or at a presentation lectern, conference table, or some other remote location.

The DMC-HD-DSP may also be used with the [DMCI](#) DigitalMedia Card Interface to create a very handy problem-solving tool with many useful functions. For instance, it can be used to extract an analog audio signal from an HDMI or DisplayPort Multimode stream, and down-mix multi-channel surround sound signals to stereo. As part of a complete Crestron control system, it can be used to detect and manage EDID and input source format information, to enable CEC device control, to assess a device's HDCP capabilities, and to extend a USB HID mouse/keyboard signal over Ethernet.

Please refer to the [DigitalMedia Resources Webpage at <http://www.crestron.com/dmresources/>](#) for additional design tools and reference documents.

### SPECIFICATIONS

#### Video

**Input Signal Types:** HDMI®, DVI<sup>[1]</sup>, DisplayPort Multimode<sup>[1]</sup>

**Output Signal Types:** HDMI or DVI<sup>[1]</sup> to switcher backplane and HDMI OUT connector

**Formats:** HDMI w/Deep Color & 3D, DVI, HDCP content protection support

**Input Resolutions, Progressive:** 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz,



852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock

**Input Resolutions, Interlaced:** 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock

**Output Resolutions:** Matched to inputs

#### Audio

**Input Signal Types:** HDMI or DisplayPort Multimode<sup>[1]</sup> supporting HD lossless multi-channel up to 7.1

**Output Signal Types:** HDMI (simultaneous multi-channel and 2-channel down-mix) to switcher backplane, HDMI (multi-channel pass-thru from input) at HDMI OUT, analog stereo 2-channel, allows audio breakaway

**Formats:** Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby® TrueHD, DTS®, DTS-ES, DTS 96/24, DTS-HD High Res, DTS-HD Master Audio™, Up to 8ch PCM

**Decoder:** Cirrus Logic® CS49700 HD Audio Decoder DSP with dual 32-bit cores

**Digital-To-Analog Conversion:** 24-bit 48 kHz

**Performance (analog):** Frequency Response: 20Hz to 20kHz ±0.5dB;  
S/N Ratio: >95dB, 20Hz to 20kHz A-weighted;

THD+N: <0.005% @ 1kHz;

Stereo Separation: >90dB

**Volume Gain Range (analog):** -80dB to 0dB, adjustable from 0% to 100%

#### USB

**Protocols:** Supports USB HID class devices

# DMC-HD-DSP HDMI® Input Card w/Down-mixing for DM® Switchers

## Connectors

**HDMI OUT:** (1) 19-pin Type A HDMI female;  
HDMI digital video/audio output;  
Also supports DVI<sup>[1]</sup>

**HDMI IN:** (1) 19-pin Type A HDMI female;  
HDMI digital video/audio input;  
Also supports DVI and DisplayPort Multimode<sup>[1]</sup>

**USB HID:** (1) USB Type B female, USB device port for connection to the USB host interface of a computer or other USB HID-compliant host

**AUDIO OUT:** (2) RCA female;  
Unbalanced stereo line-level audio output with level control;  
Maximum Output Level: 2 Vrms;  
Output Impedance: 100 Ohms nominal

## Construction

Plug-in card, occupies (1) DM Switcher input card slot, includes metal faceplate w/black finish

## Weight

8.0 oz (227 g)

## MODELS & ACCESSORIES

### Available Models

DMC-HD-DSP: HDMI® Input Card w/Down-mixing for DM® Switchers

### Available Accessories

**CBL Series:** Crestron® Certified Interface Cables

**MP-WP Series:** Media Presentation Wall Plates

**MPI-WP Series:** Media Presentation Wall Plates - International Version

**DMCI:** DigitalMedia™ Card Interface

## Notes:

1. HDMI requires an appropriate adapter or interface cable to accommodate a DVI or DisplayPort Multimode signal. [CBL-HD-DVI](#) interface cables available separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

Specifications subject to change without notice. Crestron is not responsible for errors in typography or photography.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron, DigitalMedia, DM, and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Blu-ray Disc is either a trademark or registered trademark of the Blu-ray Disc Association in the United States and/or other countries. Cirrus Logic is either a trademark or registered trademark of Cirrus Logic, Inc. in the United States and/or other countries. Dolby and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS and DTS-HD Master Audio are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI and the HDMI Logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. ©2012 Crestron Electronics, Inc.

