

EXCITE IC5

Excite™ 5.25" 2-Way In-Ceiling Speakers

- > High-performance 2-way in-ceiling loudspeakers
- > 5.25" polypropylene woofers for deep, solid bass
- > Treated cloth dome tweeters for natural high-end extension
- > Swivel tweeters for precise coverage optimization
- > Steel composition woofer baskets for increased rigidity
- > Paintable ABS plastic baffle with aluminum grilles
- > Easy-to-install toggle clamp mounting system
- > Front accessible high and low frequency contour switches
- > 60 Watts program power handling
- > 50Hz-20kHz frequency response
- > 8 Ohms nominal impedance
- > Sold in pairs

Excite™ speakers by Crestron® offer excellent sound quality and flexible installation in a range of popular sizes and configurations. In addition to multiroom audio, Excite speakers provide an appropriate and affordable choice for multimedia presentation and home theater applications.

The Excite IC5 model provides a pair of 2-way in-ceiling loudspeakers featuring 5-1/4 inch woofers and 3/4 inch dome tweeters. Power handling is an ample 60 Watts (program), with an impressive frequency response from 60 Hz to 20 kHz (-3 dB).

Rigidly constructed, Excite speakers are designed to enable a nearly flush installation when mounted in a typical drywall surface. A professional installation is easily achieved utilizing four toggle clamps integrated into each speaker baffle. Additional suspension hangers assist in the installation by preventing the speaker from falling out of the hole prior to tightening the toggle clamps. The white textured finish blends cleanly into any neutral-colored ceiling, and may be painted for an inconspicuous appearance against any colored surface. For indoor use only.

SPECIFICATIONS

Features & Performance

Woofer: 5.25 inch (134 mm) polypropylene w/rubber surround & steel basket

Tweeter: 0.79 inch (20 mm) treated cloth dome w/swivel

Crossover: 2nd order Linkwitz-Riley

Impedance: 8 Ohms nominal

Frequency Response: 60 Hz to 20 kHz (-3 dB)

Power Handling: 60 Watts program

Sensitivity: 87 dB @ 1W/1m

Coverage: 100° conical (nominal)

Controls

LF: (1) 3-position low-frequency contour switch

HF: (1) 3-position high-frequency contour switch



Connections

Input: (2) spring terminals

Environmental

Temperature: 41° to 104°F (5° to 40°C)

Humidity: 10% to 90% RH (non-condensing)

For indoor use only

Construction

Baffle: ABS plastic, white textured outer flange with black inner baffle, paintable

Grille: Perforated aluminum, white textured, paintable

Mounting: Flush ceiling mount using 4 integral toggle clamps, 1.5 in (39 mm) maximum surface thickness, 3.99 in (102 mm) minimum mounting depth, 7.4 in (188 mm) diameter recommended cutout

Dimensions

Diameter: 8.72 in (222 mm)

Depth: 4.26 in (109 mm)

Dimensions shown are per speaker

Weight

3.5 lb (1.6 kg)

MODELS & ACCESSORIES

Available Models

EXCITE_IC5-W-T: Excite™ 5.25" 2-Way In-Ceiling Speakers, White Textured, Pair

Available Accessories

SPKA-NCTP-IC500: New-Construction Speaker Templates for Excite™, Aspire™, & Essence™ IC5, 1 Pair

EXCITE IC5 Excite™ 5.25" 2-Way In-Ceiling Speakers

Notes:

Creston warrants to the original end purchaser that this Creston Speaker Product, when purchased directly from Creston or an authorized Creston Dealer, will be free from defects in material and workmanship for the life of the product except for speaker grills and outdoor rated speakers, which are warranted for five (5) years. Creston will at its option and expense either repair the defect or replace the Speaker Product with a new or remanufactured Product or a reasonable equivalent. In cases where a new model is substituted, a modification to the mounting surface may be required. If mounting surface modification is required, Creston assumes no responsibility or liability for such modifications.

This product may be purchased from an authorized Creston dealer. To find a dealer, please contact the Creston sales representative for your area. A list of sales representatives is available online at www.creston.com/salesreps or by calling 800-237-2041.

Specifications subject to change without notice. Creston is not responsible for errors in typography or photography.

The specific patents that cover Creston products are listed online at: patents.creston.com.

Creston, Excite, and the Creston logo are either trademarks or registered trademarks of Creston Electronics, Inc. in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Creston disclaims any proprietary interest in the marks and names of others.

©2012 Creston Electronics, Inc.

