

EXCITE IW8

Excite™ 8" 2-Way In-Wall Speakers

- > High-performance 2-way in-wall loudspeakers
- > 8" polypropylene woofers for deep, solid bass
- > Treated cloth dome tweeters for natural high-end extension
- > Swivel tweeters for precise coverage optimization
- > Steel composition woofer baskets for increased rigidity
- > Paintable ABS plastic baffle with aluminum grilles
- > Easy-to-install toggle clamp mounting system
- > Front accessible high and low frequency contour switches
- > 125 Watts program power handling
- > 50Hz-20kHz frequency response
- > 8 Ohms nominal impedance
- > Sold in pairs

Excite™ speakers by Crestron® offer excellent sound quality and flexible installation in a range of popular sizes and configurations. In addition to multiroom audio, Excite speakers provide an appropriate and affordable choice for multimedia presentation and home theater applications.

The Excite IW8 model provides a pair of 2-way in-wall loudspeakers featuring 8 inch woofers and 1 inch dome tweeters. Power handling is an impressive 125 Watts (program), with a wide frequency response from 50 Hz to 20 kHz (-3 dB).

Rigidly constructed, Excite speakers are designed to enable a nearly flush installation when mounted in a typical drywall surface. A professional installation is easily achieved utilizing six toggle clamps integrated into each speaker baffle. The white textured finish blends cleanly into any neutral-colored wall, and may be painted for an inconspicuous appearance against any colored surface. For indoor use only.

SPECIFICATIONS

Features & Performance

Woofer: 8 inch (203 mm) polypropylene w/rubber surround & steel basket

Tweeter: 0.98 inch (25 mm) treated cloth dome w/swivel

Crossover: 2nd order Linkwitz-Riley

Impedance: 8 Ohms nominal

Frequency Response: 50 Hz to 20 kHz (-3 dB)

Power Handling: 125 Watts program


Sensitivity: 89 dB @ 1W/1m

Coverage: 100° H & V (nominal)

Controls

LF: (1) 3-position low-frequency contour switch

HF: (1) 3-position high-frequency contour switch



Connections

Input: (2) spring terminals

Environmental

Temperature: 41° to 104°F (5° to 40°C)

Humidity: 10% to 90% RH (non-condensing)

For indoor use only

Construction

Baffle: ABS plastic, white textured outer flange with black inner baffle, paintable

Grille: Perforated aluminum, white textured, paintable

Mounting: Flush wall mount using 6 integral toggle clamps, 1.5 in (39 mm) maximum surface thickness, 4.11 in (105 mm) minimum mounting depth, 13.3 in (338 mm) high x 9.8 in (249 mm) wide recommended cutout

Dimensions

Height: 14.47 in (368 mm)

Width: 11.02 in (280 mm)

Depth: 4.43 in (113 mm)

Dimensions shown are per speaker, positioned vertically

Weight

5.0 lb (2.3 kg)

EXCITE IW8 Excite™ 8" 2-Way In-Wall Speakers

MODELS & ACCESSORIES

Available Models

EXCITE IW8-W-T: Excite™ 8" 2-Way In-Wall Speakers, White Textured, Pair

Available Accessories

SPKA-NCTP-IW800: New-Construction Speaker Templates for IW8, 1 Pair

Notes:

Crestron warrants to the original end purchaser that this Crestron Speaker Product, when purchased directly from Crestron or an authorized Crestron Dealer, will be free from defects in material and workmanship for the life of the product except for speaker grills and outdoor rated speakers, which are warranted for five (5) years. Crestron will at its option and expense either repair the defect or replace the Speaker Product with a new or remanufactured Product or a

reasonable equivalent. In cases where a new model is substituted, a modification to the mounting surface may be required. If mounting surface modification is required, Crestron assumes no responsibility or liability for such modifications.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

Specifications subject to change without notice. Crestron is not responsible for errors in typography or photography.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, Excite, and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others.
©2012 Crestron Electronics, Inc.

