

Saros® 8" 2-Way In-Ceiling Speaker

- > High-performance 2-way in-ceiling loudspeaker
- > 8" polypropylene woofer with damped cloth surround for tight, controlled bass and clear midrange
- > Optimized dual front ports for enhanced low-frequency response
- > Wide-dispersion, horn-loaded titanium dome tweeter for crisp, clear high-end and enhanced pattern control
- > Built-in 60 Watt 70/100V multi-tap transformer
- > "Zero-bezel" frameless grille for a clean, contemporary appearance
- > Integral metal back can with top and side conduit knockouts
- > Two-step toggle clamps for fast, easy installation
- > Includes tile bridge for installation in a drop-tile ceiling
- > Meets the requirements for installation in an environmental air-handling space
- > 150 Watts program power handling at 8 Ohms
- > 50Hz-20kHz frequency response
- > 95° nominal coverage pattern
- > Available in black or white
- > Paintable to blend with surroundings
- > Sold individually

Saros® speakers by Crestron® deliver professional grade performance and flexible installation in a range of popular sizes for demanding commercial applications. Solid construction, easy installation, and high-end components are hallmarks of the Saros speaker line. Ideal for use in background or foreground music, paging, and sound reinforcement systems, Saros speakers are engineered to achieve smooth, even coverage, high output, and clear, natural sound quality through the employment of horn-loaded titanium dome tweeters, high-efficiency damped cone woofers, ported enclosures, and precisely tuned crossovers.

The Saros IC8T model is a 2-way in-ceiling loudspeaker featuring an 8 inch woofer and wide-dispersion, horn-loaded 1 inch dome tweeter. A built-in 60 Watt multi-tap transformer allows for use with 70 and 100 Volt distributed speaker systems. Power handling at 8 Ohms is an impressive 150 Watts (program), with a wide frequency response from 50 Hz to 20 kHz (± 3 dB).

The Saros IC8T is smartly designed for quick and easy installation and years of reliable performance. Its "zero-bezel" frameless grille achieves an unobtrusive and contemporary appearance well-suited for use in restaurants and night clubs, retail spaces, houses of worship, convention facilities, universities, and office buildings. Installing the grille requires no hardware or tools, utilizing powerful magnets to hold it in place. A safety tether is included to prevent the grille from ever falling from the ceiling.

Unitized construction of the speaker enclosure simplifies specification and installation for use in new and existing ceilings. Mounting the speaker is facilitated using rugged, 2-step toggle clamps integrated into the enclosure. Each toggle clamp offers two positions to accommodate standard and extra thick surfaces up to 2.4 inches (61 mm). A tile bridge



is included to provide proper support when installed in a typical drop-tile ceiling. The tile bridge is adjustable to enable off-center speaker positioning, and can be folded to fit through the speaker cutout in blind-mount situations. Two rigging points are also provided on the top of the speaker enclosure for securing to the building structure using the optional safety tether kit ([SPKA-ST-15^{\(1\)}](#)).

An integral metal back can is employed to meet the requirements for installation in an environmental air-handling (plenum) space. The wiring connection is accessible behind a rear cover panel by removing a single screw. Top and side knockouts are provided on the cover panel to accommodate 1/2" or 3/4" flexible conduit. A cable clamp is also provided. Connecting the wiring behind the cover panel is facilitated using a detachable screw terminal block with provisions for easy parallel wiring in a multi-speaker application. Setting the 70/100V transformer tap is performed via a screwdriver-adjustable control located on the front baffle behind the grille.

Saros IC8T speakers are available in white or black, and can be painted to blend with the ceiling surface. They are priced and sold individually.

SPECIFICATIONS

Features & Performance

- Woofer:** 8 inch (203 mm) polypropylene w/ring mode decoupled cloth surround & steel basket
- Tweeter:** 0.98 inch (25 mm) titanium dome, horn loaded
- Crossover Frequency:** 2.5 kHz
- Impedance:** 8 Ohms nominal with transformer set to "8 Ω "

SAROS IC8T Saros® 8" 2-Way In-Ceiling Speaker

Transformer Taps: 3.75W/7.5W/15W/30W/60W at 70V;
7.5W/15W/30W/60W at 100V

Frequency Response: 50 Hz to 20 kHz (± 3 dB)

Frequency Range: 40 Hz to 20 kHz (-10 dB)

Power Handling: 150 Watts program (8 Ohms)

Sensitivity: 90.5 dB @ 1W/1m


Coverage: 95° conical (nominal)

Connections


Input: (1) 4-pin 5mm detachable terminal block with screw-down flanges;

Speaker input with parallel pass-thru;


Maximum Wire Size: 12 AWG



SAROS IC8T – Frequency Response



SAROS IC8T – Dispersion Pattern, 500 Hz - 1000 Hz



SAROS IC8T – Dispersion Pattern, 3150 Hz - 6300 Hz

Controls

Transformer Tap: (1) Recessed screwdriver-adjustable rotary switch on baffle; used to select 70/100V tap or 8 Ohms (bypass)

Environmental

Temperature: -2° to 120°F (-19° to 49°C)


Humidity: 5% to 95% RH (non-condensing)

Construction


Enclosure: Zinc-plated steel, plenum-rated, 1/2" or 3/4" conduit knockout top and side, (1) cable clamp included

Baffle: ABS UL94V-0 plastic


Grille: Steel with textured finish, paintable, magnetically-held "zero-bezel" frameless, safety tether



SAROS IC8T – Dispersion Pattern, 200 Hz - 400 Hz



SAROS IC8T – Dispersion Pattern, 1250 Hz - 2500 Hz



SAROS IC8T – Dispersion Pattern, 8000 Hz - 16000 Hz

SAROS IC8T Saros® 8" 2-Way In-Ceiling Speaker

Mounting: Flush ceiling mount using 4 integral 2-step toggle clamps, 2.4 in (61 mm) maximum surface thickness, 8.9 in (226 mm) minimum mounting depth, 11.2 in (285 mm) diameter recommended cutout, tile bridge included, (2) rigging points for safety tether (SPKA-ST-15 sold separately)

Dimensions

Diameter: 12.07 in (307 mm) not including toggles

Depth: 9.10 in (231 mm)

Weight

12.5 lb (5.7 kg)

MODELS & ACCESSORIES

Available Models

SAROS_IC8T-B-T-EACH: Saros® 8" 2-Way In-Ceiling Speaker, Black Textured, Single

SAROS_IC8T-W-T-EACH: Saros® 8" 2-Way In-Ceiling Speaker, White Textured, Single

Available Accessories

SPKA-ST-15: Safety Tether/Tie Down Kits, 10 Sets

SPKA-NCTP-IC810: New-Construction Speaker Templates, Flat

SPKA-NCTP-IC811: New-Construction Speaker Templates, Collared

Notes:

1. Item(s) sold separately.

Crestron warrants to the original end purchaser that this Crestron Speaker Product, when purchased directly from Crestron or an authorized Crestron Dealer, will be free from defects in material and workmanship for the life of the product except for speaker grills and outdoor rated speakers, which are warranted for five (5) years. Crestron will at its option and expense either repair the defect or replace the Speaker Product with a new or remanufactured Product or a reasonable equivalent. In cases where a new model is substituted, a modification to the mounting surface may be required. If mounting surface modification is required, Crestron assumes no responsibility or liability for such modifications.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, and Saros are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

SAROS IC8T Saros® 8" 2-Way In-Ceiling Speaker

