

SAROS SR6T

Saros® 6.5" 2-Way Surface Mount Speaker

- > High-performance 2-way surface mount loudspeaker
- > Designed for high reliability in both indoor and outdoor applications
- > 6.5" polypropylene woofer with damped cloth surround for tight, controlled bass and clear midrange
- > Optimized dual front ports for enhanced low-frequency response
- > Horn-loaded titanium dome tweeter for crisp, clear high end and enhanced pattern control
- > Built-in 60 Watt 70/100V multi-tap transformer
- > Rigid ABS plastic construction with powder coated aluminum grille
- > Versatile and easy-to-install "QuickBall" mounting system
- > Allows 360° rotation and continuously variable positioning
- > 150 Watts program power handling at 8 Ohms
- > 70Hz-18kHz frequency range
- > Available in black or white
- > Paintable to blend with surroundings



Saros® speakers by Crestron® deliver professional grade performance and flexible installation in a range of popular sizes for demanding commercial applications. Solid construction and high-end components are hallmarks of the complete Saros speaker line. Ideal for use in background or foreground music, paging, and sound reinforcement systems, Saros speakers are engineered to achieve smooth, even coverage, high output, and clear, natural sound quality through the employment of horn-loaded titanium dome tweeters, high-efficiency damped cone woofers, ported enclosures and precisely tuned crossovers.

The Saros SR6T model is a 2-way surface-mount loudspeaker featuring a 6-1/2 inch woofer and horn-loaded 1 inch dome tweeter. A built-in 60 Watt multi-tap transformer allows for use with 70 and 100 Volt distributed speaker systems. Power handling at 8 Ohms is an impressive 150 Watts (program), with a frequency range from 70 Hz to 18 kHz (-10 dB).

The Saros SR6T is smartly designed for quick and easy installation and years of reliable performance. Its clean, contoured enclosure achieves an attractive appearance in restaurants and night clubs, retail spaces, houses of worship, convention facilities, universities and office buildings. Weatherized construction allows for use in outdoor entertainment venues, patios, locker rooms and swimming pools.

Featuring a unique "QuickBall" mounting system, the Saros SR6T can be mounted to any solid flat surface with the ability to orient and aim the speaker in virtually any position. The QuickBall bracket achieves a very clean and stable installation using a tool-free ball-and-socket mechanism. Simply position the speaker as desired and flip the clamp lever closed. A security screw is included to deter theft by preventing the lever from being released.

The QuickBall mounting bracket can be mounted over a 1-gang US, UK, or European electrical box, allowing wiring to be run through the wall and exit cleanly through the included cover plate. It can also be mounted to a light pole or post using pole-mounting straps (not included). A rear rigging point is also provided for securing the speaker using the optional safety tether kit ([SPKA-ST-15^{\(1\)}](#)).

Connecting the wire at the back of the speaker is facilitated using a detachable screw terminal block with provisions for easy parallel wiring in multi-speaker applications. A weather boot is included to protect the wiring connections from moisture. Setting the 70/100V transformer tap is done via a recessed screwdriver-adjustable control on the rear.

Saros SR6T speakers are available in white or black, and can be painted to blend with the surrounding architecture. They are priced individually, but must be ordered in pairs.

SAROS SR6T Saros® 6.5" 2-Way Surface Mount Speaker

SPECIFICATIONS

Features & Performance

Woofers: 6.5 inch (165 mm) polypropylene w/ring mode decoupled cloth surround & steel basket

Tweeter: 0.98 inch (25 mm) titanium dome, 90° conical horn loaded

Crossover Frequency: 2 kHz

Impedance: 8 Ohms nominal with transformer set to "8Ω"

Transformer Taps: 3.75W/7.5W/15W/30W/60W at 70V;
7.5W/15W/30W/60W at 100V

Frequency Response: 90 Hz to 16 kHz (± 3 dB)

Frequency Range: 70 Hz to 18 kHz (-10 dB)

Power Handling: 150 Watts program (8 Ohms)

Sensitivity: 90 dB @ 1W/1m

Connections

Input: (1) 4-pin 5mm detachable terminal block with screw-down flanges and weather boot;

Speaker input with parallel pass-thru;

Maximum Wire Size: 12 AWG

Controls

Transformer Tap: (1) Recessed screwdriver-adjustable rotary switch on rear; Used to select 70/100V tap or 8 Ohms (bypass)

Environmental

Temperature: -2° to 120°F (-19° to 49°C)

Humidity: 5% to 95% RH (non-condensing)

Construction

Enclosure: ABS plastic, textured finish, paintable

Grille: Aluminum, powder coated, paintable

Mounting: Surface mount to a solid flat surface with option to position over a flush-mounted 1-gang electrical box, 1-gang UK (BS 4662) electrical box, or 1-gang European (DIN 49073) electrical box; pole mount (straps not included); rigging point for safety tether (SPKA-ST-15 sold separately); theft-resistant security screw

Positioning

Yaw (Horizontal): $\pm 30^\circ$

Pitch (Vertical): $\pm 30^\circ$

Roll (Rotation): 360°

Dimensions

Height: 11.19 in (285 mm)

Width: 8.08 in (205 mm)

Depth: 6.75 in (172 mm), 8.86 in (225 mm) with mounting bracket

Weight

8.3 lb (3.8 kg)



Black model – shown
with cover removed



White model – shown
with cover installed

QuickBall Mounting Bracket (included)



SAROS SR6T – Shown in White

SAROS SR6T Saros® 6.5" 2-Way Surface Mount Speaker

MODELS & ACCESSORIES

Available Models

SAROS_SR6T-B-T-EACH: Saros® 6.5" 2-Way Surface Mount Speaker, Black Textured, Single (must be ordered in multiples of 2)


SAROS_SR6T-W-T-EACH: Saros® 6.5" 2-Way Surface Mount Speaker, White Textured, Single (must be ordered in multiples of 2)

Available Accessories


SPKA-ST-15: Safety Tether/Tie Down Kits, 10 Sets

Notes:


1. Item(s) sold separately.



SAROS SR6T – Frequency Response



SAROS SR6T – Dispersion Pattern, 500 Hz - 1000 Hz




SAROS SR6T – Dispersion Pattern, 3150 Hz - 6300 Hz

Creston warrants to the original end purchaser that this Creston Speaker Product, when purchased directly from Creston or an authorized Creston Dealer, will be free from defects in material and workmanship for the life of the product except for speaker grills and outdoor rated speakers, which are warranted for five (5) years. Creston will at its option and expense either repair the defect or replace the Speaker Product with a new or remanufactured Product or a reasonable equivalent. In cases where a new model is substituted, a modification to the mounting surface may be required. If mounting surface modification is required, Creston assumes no responsibility or liability for such modifications.


This product may be purchased from an authorized Creston dealer. To find a dealer, please contact the Creston sales representative for your area. A list of sales representatives is available online at www.creston.com/salesreps or by calling 800-237-2041.

The specific patents that cover Creston products are listed online at: patents.creston.com.


Creston, the Creston logo, and Saros are either trademarks or registered trademarks of Creston Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Creston disclaims any proprietary interest in the marks and names of others. Creston is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Creston Electronics, Inc.



SAROS SR6T – Dispersion Pattern, 200 Hz - 400 Hz



SAROS SR6T – Dispersion Pattern, 1250 Hz - 2500 Hz



SAROS SR6T – Dispersion Pattern, 8000 Hz - 16000 Hz

SAROS SR6T Saros® 6.5" 2-Way Surface Mount Speaker

