

ST-BTPN

Battery Pack for SmarTouch™ Wireless Touchpanels

The ST-BTPN is a high-performance NiMH (Nickel Metal Hydride) rechargeable battery pack for Crestron SmarTouch wireless touchpanels. The battery pack is easily installed and removed without tools from the bottom panel of the touchpanel. One (1) ST-BTPN is included with each SmarTouch wireless touchpanel. Additional spares or replacements may be purchased individually.

SPECIFICATIONS

General

Output Voltage: 4.8 Volts DC nominal
Capacity: 4100 mAh fully charged
Composition: Nickel-metal hydride (NiMH)
Estimated Life: 500 charging/discharging cycles
Charging Time: 2.7 to 6 hours (depending upon touchpanel use while charging)
Docking Station/Charger: ST(I)-DSN (sold separately)

Environmental

Operating Temperature: ~ 50° to 104° F (10° to 40° C)
Charging Temperature: ~ 50° to 95° F (10° to 35° C)
Storage Temperature: ~ -4° to 113° F (-20° to 45° C)

Dimensions

Height: 1.16 in (2.94 cm)
Width: 4.25 in (10.78 cm)
Depth: 2.28 in (5.79 cm)

Weight

0.79 lb (0.36 kg)

Available Models

ST-BTPN: Battery Pack for SmarTouch 1550 and 1700 wireless model touchpanels



ST-BTPN

