

TST-600-DS

TableTop Docking Station for TST-600

The TST-600-DS is the tabletop docking station that is included as standard with the TST-600 Wireless Touch Screen. It is also available separately to provide a second charging location, or to provide a tabletop docking option for the TST-600-WALL Wall Mount Wireless Touch Screen.

The TST-600-DS features a low-profile design, allowing it to fit easily in a cabinet or drawer, or on a countertop or side table. Placing the touch screen onto the docking station charges its internal battery while allowing full operation. The docking station can also provide a wired Ethernet connection for the touch screen while docked.

For easy, versatile placement, the docking station features a single flexible hookup cable. The 9 ft (2.75 m) cable extends from the rear of the docking station to a compact interface module (TST-600-IMCW, included), which may be mounted conveniently in a wall box or attached to any flat surface or rack rail. The interface module provides wired connections for power and Ethernet.^[1]

The optional swivel mount kit (TST-600-SMK, sold separately) allows the docking station to be affixed to the tabletop, with the ability to rotate it up to 330 degrees.

SPECIFICATIONS

Note: See also TST-600-IMCW for additional specifications.

Connectors

Integral 9 ft (2.75 m) cable with 10-pin RJ50 male connector;
Connects to TST-600-IMCW interface module (included)

Power Requirements

The TST-600-DS docking station is a passive device requiring no power; a TST-600-IMCW interface module and power pack are included to provide power and other connectivity for the TST-600 touch screen; refer to TST-600 and TST-600-IMCW specifications for additional power requirements

Environmental

Temperature: 32° to 112°F (0° to 45°C), 50° to 104°F (10° to 40°C) while charging

Humidity: 10% to 90% RH (non-condensing)

Enclosure

Plastic, angled cradle, integral cable assembly

Dimensions

Height: 1.82 in (47 mm)

Width: 4.90 in (125 mm)

Depth: 5.84 in (149 mm)

Note: Combined height of the TST-600-DS docking station with TST-600 touch screen docked is 3.30 in (84 mm).

Weight

7.8 oz (222 g)



Available Models

TST-600-DS-B-S: TableTop Docking Station for TST-600, Black Smooth
TST-600-DS-B-T: TableTop Docking Station for TST-600, Black Textured
TST-600-DS-W-S: TableTop Docking Station for TST-600, White Smooth

Included Accessories

TST-600-IMCW Interface Module for TST-600-DS [Included Quantity for TST-600-DS-B-S, TST-600-DS-B-T, TST-600-DS-W-S: 1]

PW-2407WU Wall Mount Power Pack 24VDC, 0.75A, Universal [Included Quantity for TST-600-DS-B-S, TST-600-DS-B-T, TST-600-DS-W-S: 1]

Available Accessories

TST-600-SMK: Swivel Mount Kit for TST-600-DS

CBL-CAT5E-P-50: Ethernet LAN Cable, Plenum, 50 ft

Notes:

1. See TST-600-IMCW specifications for additional information.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

Specifications subject to change without notice. Crestron is not responsible for errors in typography or photography.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. ©2012 Crestron Electronics, Inc.

TST-600-DS TableTop Docking Station for TST-600

