## (ompressor DW-CP04 Compressor


















### Summary

The CP-04 is an Analog to IP signal compressor, converting up to 4 analog cameras into IP signal at a maximum of 120fps at D1 resolution. The Compressor offers strong features such as Two-Way Audio, PTZ control, Micro SD Card for local backup, Intelligent motion detection, and Single Streaming with Dual Codec. The Compressor is a perfect solution for applications that have both analog and network surveillance solutions, and are looking to get the most out of both platforms.

#### **Features**

- OnVIF Compliant
- 4CH BNC In
- 120fps @ D1 Resolution
- Dual Codec (H.264/ MJPEG) with Single Stream
- Motion Detection
- Two- Way Audio
- Micro SD Card Interface
- RS-232/ RS-485 PTZ Control
- PSIA (v1.0) Conformant
- Search and Playback from the software interface
- Framerate& Bandwidth Control
- 4 Alarm Inputs, 4 Alarm Outputs
- Event Notifications via E-mail with Image
- Fully Compatible with Digital Watchdog's DW Spectrum IPVMS

# Dimensions (unit : mm)





### **Specifications**

VIDEO		
Video Input		4 Channels Analog
Video Enconding		Dual Codec (H.264 or MJPEG) with Single Stream Setup
Resolution		D1 (704x480), CIF (352x288), 160x112
Live Casting		Streaming up 120fps @ D1 Resolution
Audio	Input	1 Channel Input
	Output	1 Channel Output
	Codec	8bit G.711, 8Khz, 8KByte/sec
SystemInfo	Memory	32bit RISC CPU, 128MByte Flash
	OS	Embedded Linux
	RAM	128MByte SDRAM
Performand	ce	
Recording	Compression	H.264 or MJPEG
	Recording Mode	Scheduled, Motion, Event
	Recording Rate	120fps @ D1 Resolution
Playback	Playback Rate	120fps @ D1 Resolution
Tidyback	Fast Forward Functions	Fast Forward, Fast Rewind, Frame-by-Frame Forward,
		Frame-by-Frame Rewind
	Search Modes	Date, Time, Event Preview
Storage	External Storage	Supports Micro SDHC for onboard storage ( up to 32 GB
	- Littoria Otorago	* SD Card not included
Interface	Alarm Input	4 Input
	Alarm Output	4 Output
	RS-232	1 Port
	110 202	For UART device Control
	RS-485	1 Port
	110 700	PTZ Support: Digital Watchdog's PTZ Series, Pelco P,
		Pelco D, Samsung and Honeywell PTZ
Features	Alarm Management	Video Loss, Video Recovered, Motion Detection, Alarm
i oaturos		Activation, Reboot Complete, Serial Input, Schedule
Network		Alarm Report
	Notifications	E-mail & FTP notifications with Image attached (Including
	INOUIIIGAUOIIG	Pre & Post Alarm Buffering)
	Security	Channel-based user password protection for live video,
	Security	PTZ, alarm output, and audio options
		1 12, alaim output, and addio options
Network Conr	nection	Ethernet (1 x Megabyte 10/100 Base-T)
Streaming Streaming	Transmission Speed Live	120/100fps @ D1 (NTSC/ PAL)
outaming	Protocols	
	PTULUCOIS	HTTP, RTP/RTSP, TCP/IP, FTP, Telnet, RARP, PPPoE,
Access	Web Viewer	SNMP, PAP, CHAP, DHCP, NTP, SMTP client, uPNP
MUCESS	vven viewer	Live, PTZ Control, Playback up to 16 Channels
		Minimum PC Requirements: Windows XP, or higher/
		IE 6.x, or later/ Pentium4, 2GHz, 2G(RAM)
	011 0 6	Video Card(256MB RAM, 1024x768)
	Client Software	DW Spectrum
General		
Operating Temperature		-10 ~ 50°C (14 ~ 122°F)
Operating Hur		Less than 90% (Non-Condensing)
Electrical	Power Requirement	12V (1A) [AC100~240V, 50/60Hz, 300mA]
	Power Consumption	DC12: 600mA
Dimensions		5.82 X 4.64 X 0.98 in (148(W)x118(D)x25(H) mm)
Weight		0.55lb (0.25Kg)

### Accessories (Optional)



DW-C19F Rack Mount for CP04 Compressor

> **AUDIOVIDEO**SUPF 1-800-284-2288 sales@avsupply.com

> > www.avsupply.com