




Dimensions

unit: Inch (mm)



Summary

This MEGApix® IP camera provides 4MP resolution at real-time 30fps with multiple analytics features that elevate the camera to the next level. Added intelligence includes line crossing, perimeter intrusion and video tampering detection. The IP66-rated outdoor bullet housing features a 100ft range IR, True WDR, and H.265 codec support. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 4MP 1/3" image sensor at real-time 30fps
- 3.6mm fixed lens
- True Wide Dynamic Range (WDR)
- Multiple codecs (H.265, H.264, MJPEG) with simultaneous dual-stream
- 100ft range IR
- Line crossing video analytics
- Perimeter intrusion video analytics
- Video tampering with scene change detection video analytics
- Video tampering with video blur detection video analytics
- Video tampering with abnormal color detection video analytics
- Smart DNR™ 3D digital noise reduction
- True day/night with mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Backlight compensation (BLC)
- Auto white balance (AWB)
- Motion detection
- Audio input
- Web server built-in
- PoE class 2 and DC12V
- Waterproof cabling
- ONVIF conformant, profile S
- IP66 certified weather and tamper resistant
- 5 year warranty



Specifications

IMAGE	
Image sensor	1/3" CMOS
Total pixels	2688 (H) x 1520 (V)
Minimum scene illumination	0.045 lux (color) 0.0 lux (B&W)
S/N ratio	50dB
Video output	CVBS video output (BNC D1)
LENS	
Focal length	3.6mm, F1.6
Lens type	Fixed lens
Field of view (FoV)	72°
IR distance	100ft range
I/O	
Audio in / out	1/0
Audio compression	G.711A / U
OPERATIONAL	
Shutter mode	Auto, manual
Shutter speed	1/25s - 1/100000s
Auto gain control	Auto
Day / night	Auto, day (color), night (B/W), schedule
Smart DNR™ 3D digital noise reduction	2D / 3D DNR
Wide Dynamic Range (WDR)	True WDR low, middle, high
Wide Dynamic Range (WDR) dB	120dB
Privacy zone	4 programmable privacy masks
Camera analytics	Line crossing, perimeter intrusion, video tampering detection (scene change, video blur, abnormal color detection)
Alarm notifications	Notifications via e-mail or FTP server
NETWORK	
LAN	802.3 compliance 10/100 LAN
Video compression type	H.265, H.264 or MJPEG
Resolution	4MP (2592x1520) at 30fps
Frame rate	Up to 30fps at all resolutions
Video bitrate	64 Kbps - 10 Mbps
Bitrate control	Multi-streaming CBR/VBR at H.264/ H.265 (controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTp, FTP
Security	IP filtering, MAC filtering, authentication (ID/PW), SSL/TSL
ONVIF conformance	Yes
Web viewer	OS: Windows® Browser: Internet Explorer®
Video management software	DW Spectrum® IPVMS
ENVIRONMENTAL	
Operating temperature	-4°F - 122°F (-20°C - 50°C)
Operating humidity	10-90% RH (non-condensing)
IP rating	IP66 certified weather and tamper resistant
Other certifications	CE, FCC, RoHS
ELECTRICAL	
Power requirement	DC12V, PoE (IEEE 802.3af class 2).
Power consumption	LED on: 6W LED off: 2.5W
MECHANICAL	
Material	Metal bullet housing
Dimensions	3.41" x 8.03" inch (86.7 x 204mm)
Weight	1.34 lb (0.609kg)

Mounting accessories (Optional)

