1080p Mini Indoor Dome IP Camera

**DWC-MD724V** 















## Summary


MEGApix® 2.1MP network cameras provide real-time 1080p High Definition video at 30fps. Advanced technologies include Digital Slow Shutter and Electronic Day/Night for clear images in challenging lighting conditions. A built-in Web-Server and user-friendly interface make these cameras easy to use. Power over Ethernet simplifies installation by providing both power and the network connection through a single cable. All cameras are ONVIF conformant, assuring their successful integration with other open platform video surveillance products. Housed in our attractive dome enclosure, these cameras provide the industry-leading benefits of MEGApix® technology at an affordable price.


## **Features**

- 2.1 Megapixel Image Sensor (1080p, 30fps)
- Real-time 1080p 30fps High Definition
- · Dual Codecs (H.264, MJPEG) with Simultaneous Streaming
- 4.0mm Fixed Lens
- · Electronic Day/Night
- Auto Gain Control (AGC)
- · Back Light Compensation (BLC)
- · Auto White Balance (AWB)
- Motion Detection
- Web Server Built-in
- PoE and DC12V
- OnVIF Compliant, Profile S

## Dimensions (unit: mm [inch])







## Specifications

UNVIF	0	n	VI	F
-------	---	---	----	---

IMAGE		
Image Sensor	1/2.7" 2.1M CMOS	
Total Pixels	1930 x 1088	
Minimum Scene Illumination	F2.0 (30IRE): 1.4 Lux [Color]	
LENS		
Foral Longth	4.0mm Lens, F2.0	
l ens Type	Fixed Lens	
Angle of View	82°	
CPERATIONAL		
Shutter Mode	Auto	
Shutter Speed	1/30(25)sec ~ 1/10,000sec	
White Balance	Auto Indoor/Auto Outdoor/Push/Manual/Hold	
Auto Gain Control	Max 64dB	
Day and Night	Auto, Day, Night, Schedule	
NETWORK		
LAN	802.3 Compliance 10/100 base T LAN	
Video Compression Type	H.264, MJPEG	
Resolution	1080p/ D1/VGA/CIF/QVGA	
Frame Rate	1-30fps	
Streaming Capability	Multi Streaming CBR/VBR (Controllable frame rate and Bandwidth)	
IP	IPv4, IPv6	
Protocol	ONVIF, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTSP, NTP, HTTP, DNS DDNS, DHCP	
Maximum User Access	4 Users	
OnVIF Conformance	OnVIF Profile S	
Web Viewer	Browser: Internet Explorer, Google Chrome, Firefox OS: Windows 7	
ENVIRONMENTAL		
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)	
Operating Humidity	Less than 90% (Non-Condensing)	
Other Certifications	FCC, CE, ROHS	
ELECTRICAL		
Power Requirements	DC 12V, POE IEEE 802.3af Class 2	
Power Consumption	2W, 165mA	
MECHANICAL		
Material	Plastic	
Dimensions	4.13 x 2.93 in (105 x 74.6mm)	
Weight	0.55lbs (250g)	

\*Specifications subject to change without notice.