

DW-VAONE 8





DW-VAONE 8















Summary

The VMAX A1™ Digital Video Recorder supports all HD Analog formats and all analog to 960H via coaxial cables, offering a seamless upgrade to HD resolution. Up the Coax (UTC) remote configuration is available with all compatible cameras. The A1™ is available with up to 8TB of storage.


Features


- Universal HD DVR Records all HD Analog Formats and All Analog to 960H
- Real Time 30fps Recording up to 1080p
- Support up to 3MP HD Analog Cameras (Limited Support)
- Pivot™ Central Management Software up to 128 Channels
- Event Camera Group Recording
- Mobile Application for iPhone®, iPad®, iPod®, Android® Smart Phones and Tablets and Apple TV
- Mac® Compatible Remote ACS Software
- VMAX 2.0 Intuitive Graphical User Interface (GUI)
- OSD and PTZ Control via Coax (UTC)
- Signal Hybrid Detects Any Camera at Any Input Automatically.
- True HD 4K Output
- HDD Calculation and Auto Recording Configuration
- Event Notifications via Email, Text and Pivot™ CMS
- Advanced H.264 Embedded DVR
- Multiplex Live, Playback, Recording, Backup, Network, Configuration
- USB 3.0
- 1 Audio Input, 1 Audio Output
- 4 Sensor Input, 1 Relay Output
- Digital Spot Monitoring Output at D1 resolution
- · Simple & Free DDNS Service
- Easy Web-Based Client with Multi-User Access
- Help Menu on Major Functions
- Auto & Manual Firmware Upgrade Available
- 5 Year Limited Warranty

Available Models

- · DW-VAONE81T 1TB Internal Storage
- · DW-VAONE82T 2TB Internal Storage
- · DW-VAONE83T 3TB Internal Storage
- DW-VAONE84T 4TB Internal Storage
- DW-VAONE86T 6TB Internal Storage
- · DW-VAONE88T 8TB Internal Storage

Dimensions unit: Inches (mm)





Specifications

VIDEO		
Video signals s	upported	Analog signal up to 960H, all HD Analog
Video input		8 Channels
	Frame rate	1~30fps
Video live	Resolution	All HD Analog 720p, 1080p, and 3MP (limited support) cameras and all analog resolutions up to 960H
Video output		HD output (MAX resolution : 3840 x 2160@30 fps), spot output (D1 display resolution), VGA
	Input	1 input
Audio	Output	1 output
	Audio codec	PCM
Alarm	Sensor input	4 input
Alarm out		1 output
Operating syste	em	Embedded Linux*
Serial		Control I/O, 2x RS485 for keyboard and PTZ control
User intertace	Menu display	Graphical user interface (GUI)
OSCI III CITACC	Control methods	IR remote control, USB mouse
Screen display mode		1, 4, 9 sequence
Sc. een resoluti	on	3840 x 2160, 1920x1080P, 1280x1024, 1024x768
PERFORMANC		
	Compression	H.264
	Recording mode	Schedule, event, panic, continuous, pre & post event, motion, recording configuration per channel
	Pre recording	1~5 seconds
Recording	Post recording	5-15 seconds
	Recording rate	Up to 240fps total at up to 1080p
		Up to 160fps total at 3MP
	Recording resolutions	All HD Analog 720p, 1080p, and 3MP (limited support) cameras and all analog resolutions up to 960H
	Playback rate	Up to 240fps total at up to 1080p
Playback		Up to 160fps total at 3MP
	Playback resolution	All HD Analog 720p, 1080p, and 3MP (limited support) cameras and all analog resolutions up to 960H
	Fast forward functions	x1/16, x1/8, x1/4, x1/2, x1, x2, x4, x8, x16, x32
	Playback functions	First data, last data, date/time, record table, calendar, bookmark, system log
	HDD interface	1 HDD
C+	Max. internal HDDs	Up to 8TB
Storage	HDD interface type	SATA-II, SATA-III
	HDD health check	Temperature, S.M.A.R.T. with e-mail notifications
Features	Camera color control	Brightness, contrast, saturation, hue
	Digital zoom	Yes (live & playback)
	Software upgrade	USB Flash drive, network upgrade, FTP remote upgrade
	Mobile client	Mobile app for Apple* & Android* Smart Phones & tablets
	Covert channel	Yes (live & playback)
NETWORK		
Network connection		Ethernet (1 x Gigabit 10/100/1000 Gpbs)
Maximum user connections		5 simultaneous connections
Streaming	Transmission speed live	Up to 240fps total at up to 1080p Up to 160fps total at 3MP
Protocols		Static, DDNS, DHCP, uPnP, RTSP
	Web viewer	Live, playback, & configuration up to 10
Access	Client monitoring software	multiple connections Mac* (Apple* S/W), Pivot™ (CMS S/W)
GENERAL		
Operating temperature / humidity		41°F ~ 104°F (5°C ~ 40°C), less than 80% (non-condensing)
Electrical	Power requirement	12V DC
	Power consumption	36W, 3A
Dimensions Weight		11.02 x 9.65 x 1.89 inch(280 x 245 x 48mm) 5.56lbs (2.52 kg)

