

## HQView510

Universal HQV™ Scaler–Switcher-Scan Converter with  
Geometry Correction, Edge Blend & 3G-SDI In/Out



Harnessing the power of the Reon™ video processor running state of the art HQV™ algorithms with expertly designed hardware and firmware from Calibre, HQView510 is a highly flexible image scaler and scan converter which provides stunning image quality for professional, broadcast and corporate AV users.

HQView510 features 4-sided soft edge blend with multi-region black level correction for seamless blending of multiple projectors and includes flexible geometry correction functions able to correct image shape and projector misalignment by dragging and dropping each image corner, or by pin/barrel, rotation or by keystone and rotation.

HQView510 provides 3G-SDI input and out connectivity with backwards compatibility with HD-SDI and SD-SDI. A Genlock input is provided for studio/staging use which can accept bi-level or tri-level sync or black & burst.

- Best in class professional image processing in a compact affordable 1U format
- Use as a routing switcher and universal interface for 3G-SDI, HD-SDI, DVI or HDMI switching and distribution systems, projectors and displays
- Improve video image quality with better detail and clarity
- Superior de-interlacing reduces image flicker and artefacts
- Remove picture noise from poor quality video sources
- Powerful geometry correction for off-axis projection, pin/barrel, image rotation
- 4-Sided soft edge blend for tiling multiple projectors to produce large images
- Genlock and I/O Lock for in-camera use

- 3G-SDI, HDMI, DVI, VGA Analog, Component YPbPr, RGsB/RGBS, Composite & S-Video inputs with signal compatibility up to 1080p & WUXGA
- 3G-SDI, HDMI/DVI & VGA Analog outputs
- Motion adaptive per pixel video de-interlacing, HD & SD
- Multi-directional diagonal de-interlace filter
- Automatic 3:2 & 2:2 pull-down detection with automatic film, video and video over film detection
- Chroma and Luma transient improvement
- Edge anti-aliasing
- 4-field full resolution SD & HD processing
- 4D Motion, Noise Adaptive HQV noise reduction for spatial and temporal noise
- Codec noise reduction for mosquito and block compression noise
- Direct input selection keys allow input selection without using menu system
- Flexible color calibration controls
- Gamma controls
- 10-bit signal inputs, 12-bit accurate internal processing
- Selectable processing versus latency: best picture and low latency modes
- Latency as low as 0.25-frame progressive inputs, 1.25-frames interlaced inputs
- I/O Lock, Genlock/Frame Sync and Free Run selectable output modes
- Flicker filter for interlaced output modes
- USB port for in-field firmware updates
- Programmable customer logo on menu
- TCP/IP remote control and Web Server
- Easy to navigate self-explanatory OSD menus
- Powerful geometry correction capabilities
- Pan, Zoom, Tilt
- Image rotation, pin/barrel correction
- 4-Sided edge blend with 48-bit processing & multi-region black level correction

Calibre UK Ltd,  
Cornwall House, Cornwall Terrace,  
Bradford,  
West Yorkshire  
BD8 7JS

Europe: [proavsales@calibreuk.com](mailto:proavsales@calibreuk.com)  
+44 1274 394125

USA: [usasales@calibreuk.com](mailto:usasales@calibreuk.com)

Web: [www.calibreuk.com](http://www.calibreuk.com)

## HQView510

### Universal HQV™ Scaler–Switcher-Scan Converter with Geometry Correction, Edge Blend & 3G-SDI In/Out

#### Inputs

2x Composite Video CVBS (NTSC, PAL & SECAM),  
 1x via BNC jack and 1x via Cinch/RCA  
 1x YC/S-Video via 4 pin mini DIN  
 1x Component analog video YPbPr(S) or RGB/RGBS  
 via 3 or 4 x BNC jack  
 1x HDMI with HDCP, 8/10/12 bit video compatible, 10-bit internal  
 processing depth. Audio strip-off of SPDIF compatible formats  
 1x DVI with HDCP  
 1x VGA Analog via 15HDD  
 1 x 3G-SDI, accepts 3G, HD and SD SDI signals via BNC  
 supports 4:2:2 and 4:4:4 formats with audio de-embed

1x Genlock (V-Lock) input via BNC, accepts bi-level, tri-level sync  
 or black & burst, 50/59.94/60Hz formats

#### Supported video formats

HD 720p, 1080i, 1080psf (psf digital only), 1080p23.97/24/25/30,  
 1080p30, 1080p50, 1080p59.94, 1080p60  
 ED 480p, 576p (not via SDI)  
 SD 625i (576i), 525i (480i)  
 Common VESA graphics formats from 640x480 to 1920x1200  
 (with reduced blanking for 1920x1200 and 1600x1200 modes)

Multi standard support for CVBS & YC in PAL, NTSC, SECAM  
 formats with selectable 3D comb for composite

*Note: PIP and edge blend are mutually exclusive so cannot be used  
 simultaneously*

#### Outputs

1x 3G-SDI  
 1x DVI/HDMI with HDCP  
 (HDMI with deep color 8/10/12 bit support, via DVI connector)  
 1x VGA Analog via 15HDD  
 1x S/PDIF digital audio via RCA  
*NB: 3G-SDI and VGA Analog outputs are disabled with HDCP-encrypted  
 input. Not all outputs are available simultaneously*

#### Supported Output formats:

DVI/VGA common VESA formats 640x480 to 1920x1200, 720p, 1080p  
 3G-SDI in SMPTE formats 480i, 576i, 720p, 1080i, 1080p with selectable  
 audio embed  
 Selectable Genlock (V-Lock), I/O lock or frame rate conversion mode  
 Selectable aspect ratio conversion  
 Selectable vertical temporal filter for flicker reduction of interlaced outputs  
 (edge blend not available in this mode)

#### User Controls

Remote control via RS232, TCP/IP API and Web Server.  
 Keypad for direct input selection and control of common adjustments as well  
 as OSD menu access  
 USB port for uploading software updates and new features

#### Power Requirements

100-264VAC, 35W typical

#### Warranty

3-years return to base warranty covers parts and labor.

HQView model >	100S	200S	210	300S	310	320	325	400S	410	420	500S	510	520	530
Front LCD menu or OSD control	OSD	OSD	OSD	OSD	OSD	OSD	OSD	OSD	OSD	OSD	OSD	OSD	OSD	OSD
DVI/HDMI Inputs				x	x	x	x	x	x	x	x	x	x	x
Component Input				x	x	x		x	x	x	x	x	x	x
Composite/S-Video Inputs	x							x	x	x	x	x	x	x
VGA Analog Input				x	x	x		x	x	x	x	x	x	x
HD-SDI Input								x	x	x				
3G-SDI Input		x	x								x	x	x	x
DVI/HDMI Output	x	x	x	x	x	x	x	x	x	x	x	x	x	x
VGA Analog Output								x	x	x				
3G-SDI Output											x	x	x	x
3G-SDI Audio embed/de-embed											x	x	x	x
HQV Processing	x	x	x	x	x	x	x	x	x	x	x	x	x	x
PIP/POP/PAP								x	x	x	x	x	x	x
TCP/IP Control	x	x	x	x	x	x	x	x	x	x	x	x	x	x
Low Latency Mode	x	x	x	x	x	x	x	x	x	x	x	x	x	x
Flicker Filter for Interlaced Output Modes											x	x	x	x
Geometry Correction, 4-Corner, Rotate			x		x	x	x		x	x		x	x	x
Genlock (V-Lock)											x	x	x	x
Pan, Zoom, Tilt	x	x	x	x	x	x	x	x	x	x	x	x	x	x
Edge Blending					x	x	x		x	x		x	x	x
Edge Blend Black Level Correction								x				x	x	x
Auto pan/zoom/tilt of content for blending					x	x	x		x	x		x	x	x
Warp Mapping						x	x			x			x	x



Calibre UK Ltd,  
 Cornwall House, Cornwall Terrace,  
 Bradford,  
 West Yorkshire  
 BD8 7JS

Europe: [proavsales@calibreuk.com](mailto:proavsales@calibreuk.com)  
 +44 1274 394125  
 USA: [usasales@calibreuk.com](mailto:usasales@calibreuk.com)  
 Web: [www.calibreuk.com](http://www.calibreuk.com)

