

EZ-PlateCam2

Outdoor Long Range License Plate Camera



Features

- · High Resolution Technology with 600 TVL!
- · Vari-focal 5-50mm lens
- · Easy to use OSD setup menu
- Cable Management bracket included
- IP66 weather resistant rating means that it will withstand the elements of outdoor conditions
- 16-90 feet of IR distance













Specifications

Part Number	EZ-PlateCam2
Pickup Device	1/3" Sony Super HAD CCD II
Video Format	NTSC or Pal
Picture Elements	811 x 508 (NTSC) 811 x 508 (NTSC)
Effective Pixels (NTSC I PAL)	768 x 494 (NTSC) I 752 x 582 (PAL)
Scanning System	2:1 Interlace
Scanning Frequency	15.734 KHz (H), 59.94 Hz (V) I 15.625 KHz (H), 50 Hz (V)
Horizontal Resolution	600 TVL
Sensitivity IR on	0 Lux
S/N Ratio	Over 50dB (AGC off)
Electronic Shutter	1/10,000s
Video Output	BNC 1.0Vp-p 75Ω
Local Video Output	Local test output
Gamma Correction	0.45
Lens Type	5-50mm
Lens Options	Vari-focal lens
Sync Mode	Internal
IR LED	100 high illuminating LEDs
IR Wave Length	850nm
IR Distance	Up to 50M/164 ft
OSD Menu	Yes
Environmental	IP65 Weather Resistance
Power Source	12VDC/24VAC
Power Consumption	12VDC: 1.6A max 24VAC: 17W max
Operating Temp	14°F~122°F I -10°C~50°C
Humidity	<80%
Dimensions (in I mm)	4.54" x 6.48" 115.2mm x 164.5mm
Weight (lbs I gm)	4lbs I 1800g
Mount	Mount Bracket Included
Certifications	CE/FCC



