

FUJINON

Premier PL 4K+



24-180 mm T2.6 Primarily Versatile

The FUJINON PREMIER 24-180 T2.6 is the high-quality general purpose member of the family of four 4K+ PL Cine zoom lenses. Identified by their gold band, Fujinon Premier PL 4K+ lenses consistently match each other superbly for focus, iris, zoom, color, contrast, and performance.

With outstanding resolution, uniform MTF and illumination across the entire image area at all focal lengths, all four Fujinon Premier PL 4K+ zooms have 136 mm front diameters. Focus, zoom, and iris gears are all in the same position—which speeds up lens changes, since follow focus accessories and lens motors can stay in the same position on the rods. Focus barrel rotation is a uniform 280 degrees on all four lenses.

A net and filter holder is included with each zoom. The aluminum ring slides onto the rear element cover of the lens. This makes mounting and changing nets much faster and cleaner. Extra net holders are available from your rental house or Fujifilm Optical Devices distributor.



Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

FUJIFILM
expect INNOVATION™

Technology That Inspires...

For design help, accessories or pricing, please contact:
sales@avsupply.com or call: 1-858-565-1101

FUJINON
AUDIOVIDEO SUPPLY
1-800-284-2288 sales@avsupply.com
www.avsupply.com

FUJINON

Premier PL 4K+



24-180mm/T2.6





75-400mm/T2.8-3.8



18-85mm/T2.0



14.5-45mm/T2.0



| Lens | 14.5-45 mm T2.0 | 18-85 mm T2.0 | 24-180 mm T2.6 | 75-400 mm T2.8-T3.8 |
|---|-----------------------|---------------------|---------------------|--------------------------------|
| Focal length | 14.5-45 mm | 18-85 mm | 24-180 mm | 75-400 mm |
| Zoom ratio | 3.1 | 4.7x | 7.5x | 5.3x |
| Max Iris | T2.0 | T2.0 | T2.6 | T2.8 (75-270) T3.8 (400 mm) |
| Min Iris | T22 | T22 | T22 | T22 |
| Iris Blades | 9 | 9 | 9 | 9 |
| Close focus (from image plane) | 0.71 m (2.3ft) | 0.82 m (2.7ft) | 1.24 m (4.1ft) | 2 m (6.6ft) |
| Object size at close focus (wide end)* | 14.5 mm: 693 x 390 mm | 18 mm: 656 x 369 mm | 24 mm: 924 x 520 mm | 75 mm: 580 x 326 mm |
| Object size at close focus (tight end)* | 45 mm: 215 x 121 mm | 85 mm: 139 x 78 mm | 180 mm: 119 x 67 mm | 400 mm: 113 x 64 mm |
| Angular field of view (wide end)* | 14.5 mm: 79° 13' | 18 mm: 67° 23' | 24 mm: 53° 08' | 75 mm: 18° 11' |
| Angular field of view (tight end)* | 45 mm: 29° 52' | 85 mm: 16° 04' | 45 mm: 7° 38' | 400 mm: 3° 26' |
| Front Diameter | 136 mm | 136 mm | 136 mm | 136 mm |
| Length | 310 mm | 352 mm | 405 mm | 444 mm |
| Weight | 6.5 kg / 14.3 lbs | 6.9 kg / 15.2 lbs | 8.9 kg / 19.6 lbs | 8.9 kg / 19.7 lbs |
| Focus Rotation (degrees) | 280° | 280° | 280° | 280° |
| Zoom Rotation (degrees) | 160° | 160° | 160° | 160° |
| Model Number | HK3.1x14.5 | HK4.7x18 | HK7.5x24 | HK5.3x75 |

* Calculated for 16:9 Aspect ratio with S35 24.0 x 13.5 mm gate

Available with feet or meters focus scales

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

FUJIFILM
expect INNOVATION™

Technology That Inspires...

FUJINON
www.Fujinon.com

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101