

EVERY PIXEL TELLS A STORY  
Select models



Gang box not included



White, silver and Ivory faceplates included

## Speciality Cameras

In Wall Camera Kits

# GBK Series


Ganz gang box camera kits are designed to fit into most single electrical boxes, making them ideal for discrete surveillance in a wide range of environments. The kits include a white, ivory and silver faceplate as well as a clear and tinted window. Two camera options are available, a 690 TVL Pixim Seawolf WDR camera for tough backlight applications and a 700TVL camera for standard interior use. The camera can be tilted and swiveled inside the gangbox to achieve the desired angle of view. Both models include a day/night mode for excellent low light performance.

### Features:

- 690 TVL Pixim Seawolf WDR and 700 TVL standard models
- 3.6mm lens standard (other lens options available)
- Tamper-Resistant mounting screws
- 3 faceplates included (white, silver and ivory)
- Clear and tinted windows included
- Fits most single gang electrical boxes (not included)
- 12VDC Power Input



**CBC AMERICA Corp.**



# GBK Kits

## In Wall Camera Kits

### Expanded and Dimensional Views



### Specifications

General	GBK-36W	GBK-36X
Image Picture Element	Pixim Seawolf Sensor	1/3" 960H Super HAD CCD II (Sony)
Resolution	690TVL (Horizontal)	700TVL (Horizontal)
Effective Pixels	758 (H) x 540 (V)	976 (H) x 494 (V)
Scanning System	2:1 Interlace	
Lens	3.6mm wide angle fixed (Horizontal Angle of View 71.2°)	
<b>Functional</b>		
Wide Dynamic Range	120 db (102 dB typical)	-
White Balance	ATW, AWB, Manual	ATW, Push, User1, User2, Anti CR, Manual, Push Lock
Day/Night Function	Digital Day/Night	
OSD	Yes (Multi-Language)	
Image Flip	Yes	On/Off
Motion Detection	On/ Off, 4 Programmable zones	On/Off (4 areas)
Backlight Compensation	Off/ On, adjustable backlight zone	BLC / HLC / Off
Shutter Speed	1/25-1/30,720 sec	1/60 ~ 1/100,000 sec
Digital Slow Shutter	Off / 2x-32x	-
Minimum Illumination	0.1 lux @ F1.2	0.1Lux @ F2.0
AGC	Up to 50dB	Off / 0.25 / 0.50 / 0.75 / 1.00
S/N Ratio	Up to 53dB Digital	50dB or more (AGC Off)
<b>Physical/Additional</b>		
Power Input	12VDC	
Power Consumption	4.2W max.	80mA max
Faceplate Dimensions	4.5" H x 2.8" W x 1.6" D	
Weight	Approx. 0.1lbs (50g)	
Operating Temperature	14° ~ 122° F ( -10° ~ 50° C)	
Storage Temperature	-4° ~ 140° F ( -20° ~ 60° C)	
Face Plates	Three included: White, Silver and Ivory	
Window Lens	Two included: Clear and Tinted	

All specifications are subject to change without notice