



HS Series Features a
Full HD Pinhole IP Camera
(3.7mm - ZN1-V4FN4 or 2.8mm ZN1-V4FN4)

ONVIF
Profile (S) Compliant


IP Height Strip Camera Series with GXi Technology

ANZ
PixelPro
WITH
GXi
TECHNOLOGY

The HS Series features a full HD pinhole IP camera with GXi Technology maximizing the camera's surveillance capabilities by bringing an added feature set of Imbedded Intelligence and full video recording to SD card to this already full-featured camera. The Imbedded Intelligence provides analysis of video with application areas including intrusion detection, people counting and loitering detection, as well as camera tampering and failure detection.

Features:

- Full HD 1080p @ 30fps
- Easy and Flexible Installation
- Imbedded Intelligence Technology
- Image Rotation for vertically oriented space
- 3.7mm or 2.8mm Fixed Lens
- Digital Day/Night and WDR
- SDXC Edge Recording (up to 64GB)
- Power over Ethernet (IEEE 802.3af)
- Available in white, black and silver
- Metric and "dummy" models also available



CBC AMERICA Corp.

www.avsupply.com | email: sales@avsupply.com | Ph: 858.565.1101



IP Height Strip Camera with GXi Technology

■ Specifications

MODEL		HSW-H28-4	HSW-H37-4	
Pinehole Camera Module	Image Sensor	1/3" 1080p CMOS		
	Effective Pixels	1920 x 1080		
	Scanning System	Progressive scanning		
	AGC control	Auto		
	Minimum Illumination	Color: 1.0 lux / BW: 0.007 lux (DSS ON)	Color: 1.4 lux / BW: 0.01 lux (DSS ON)	
	Lens	2.8mm , F2.0		
	Field of View	Horizontal: Approx. 82° Vertical: Approx. 43°	Horizontal: Approx. 63° Vertical: Approx. 33°	
	Day & Night Performance	Digital Day & Night		
	WDR	Digital WDR		
	DNR (Digital Noise Reduction)	Supported		
	DSS (Digital Slow Shutter)	2X ~ 16X		
	White Balance	ATW / Manual		
	BLC	On (possible to designate zone) / Off		
	DC auto Iris	Supported		
IR LEDs	-			
Video	Compression Format	H.264 Baseline, Main, High profile (MPEG-4 Part 10 / AVC), MJPEG (Motion JPEG)		
	Number of Streams	Dual Stream, Configurable streams in H.264, MJPEG H.264: Controllable frame rate, bandwidth (VBR/CBR) MJPEG: Controllable frame rate, JPEG quality		
	Resolutions	1920 x 1080, 1280 x 720, 1120 x 630, 960 x 540, 800 x 450, 640 x 360, 480 x 270, 320 x 180		
	Frame rate	H.264: Max 30fps in all resolution MJPEG: Max 30fps in all resolution		
	Motion Detection	Supported		
	Text Overlay	-		
	Analog Output	Time stamp and text caption overlay		
Audio	Input	-		
	Output	-		
	Compression Format	-		
Function	DI	1 Channel		
	DO	1 Channel		
	RS-485	-		
	Network	10 / 100 Base-T		
	Protocol	QoS Layer 3 DiffServ, TCP/IP, UDP/IP, HTTP, HTTPS, RTSP, RTP, RTCP, RTP/UDP, RTP/TCP, mDNS, UPnP™, SMTP, DHCP, DNS, DynDNS, NTP, SNMPv1/v2c/v3(MIBII), IGMP, ICMP, SSLv2/v3, TLSv1		
	USB 2.0	-		
	SD Memory Card Slot	microSD slot (up to 64GB)		
Electrical	Power Source	12VDC, PoE		
	Power Over Ethernet	Supported (IEEE 802.3af)		
	Power Consumption (Approx.)	3W @ 12VDC		
Environmental	Operating Temperature (Not including cold start)	0°C ~ 40°C (32°F ~ 122°F)		
	Operating Humidity	Humidity up to 90% RH (non-condensing)		
Mechanical	Dimensions	1.7" W x 1.4" D x 34.1" H		
	Colors	Standard color white (HSW-Hxx). Also available in black (HSB-Hxx) and silver (HSS-Hxx)		
	Weight (approx)	2 lbs. / 907g		
	Additional models	Metric models - HSx-Mxx-4, Dummy models - HSx-MD (x=color, xx=lens)		
Certifications	OnVIF Compliant (Profile S), FCC, CE			

All specifications are subject to change without notice

