GAMAUDIO VIDEO SUPPLY





Features:

- Supports 4K Live display
- Up to 4K recording
- 3TB-20TB HDD
- Built-in PoE switching hub
- Automatic router port forwarding
- FW Upgradable by USB or network
- Supports P2P network setup by QR code scan
- Network ports (WAN/LAN) 1 each
- HDD failure notification (S.M.A.R.T)
- PC & web based remote agent, smartphone applications
- Plug and play PixelPro IP cameras with no configuration required





NR-16F85-8PRA

16 Channel 4K Embedded NVRs

■ Specifications

	MODEL	NR-16F85-8PRA
	Channels	16CH
	Input Signal	16 x IP Camera (Max 8MP)
	Main Monitor	VGA or HD Display
VIDEO	Main Monitor Resolution	2160p / 1080p / 720p / SXGA
	Spot	-
	Motion Detection	Yes (From IP Camera)
	Input Signal	16 CH (From IP Camera)
AUDIO	Output Signal	1CH
AUDIO	Microphone	1CH
	CODEC	G.711
	CODEC	H.264 / H.265
RECORDING	Rec. Rate	Max. 30 FPS@8MP/CH (Depends on IP Camera)
	Rec. Resolution	Max. 8MP (Depends on IP Camera)
ALARM I/O	Alarm Input	16 CH (IP) + 2 CH (Internal) (Depends on IP Camera)
	Alarm Out	16 CH (IP) + 1 RELAY (Internal) (Depends on IP Camera)
	Internal HDD	5 EA
STORAGE	External Storage	YES (eSATA, NAS (for backup))
	Internal ODD	NONE
	USB	3 ports
INITEDEACE	Interface	3 ports 1 RS-485 / 1 RS-232 8 (IP Camera, PoE (802.3at)) + 1 (LAN) + 1 (WAN) YES 2GE + 8GE(PoE) 72W ARM9 interior 48V, 96W YES 1EA SMPS 12V 100W + SMPS 52V 100W 15W max. without HDD
INTERFACE	LAN	8 (IP Camera, PoE (802.3at)) + 1 (LAN) + 1 (WAN)
	Remote Control	YES
	Network	2GE + 8GE(POE)
LUID	Total PoE Power	*\dagger* 72W
HUB	Manageable by IPX	ARM9 interior
	Adaptor	9 48V, 96W
ABBITIONAL	Watchdog	YES
ADDITIONAL	Cooling Fan	1EA
DOLLIED	Power Supply	SMPS 12V 100W + SMPS 52V 100W
POWER	Power Consumption	15W max. without HDD
ENVIRONMENT	Temperature / Humidity	32°F~104°F (0°C ~ 40°C) / 10 ~ 90% NC
	Dimensions (mm)	2U - 16.9" x 14.4" x 3.5" (430 x 367 x 88.4mm)
CHASSIS	Weight	11 lbs. (5 Kg)
CERTIFICATIONS	UL, CUL, FCC, CE	UL, cUL, FCC, CE, KC, C-tick
	Display Rate	Up to 480fps/400fps (Real-time)
	Decoding Rate	Max Total 120fps @ 8M
	Display Resolution	2160p / 1080p / 720p / SXGA
	Display Mode	1,4,8,9,16
	Sequence	Programmable Sequence
MONITODING	Digital Zoom	YES
MONITORING	Covert	YES
	Camera Color Control	Yes (Contrast, Hue, Tiny, Brightness) (Depending on IP Camera)
	Camera Image Control	Yes (White Balance, Exposure, Flickerless) Depending on IP Camera
	Audio Monitoring	Yes (From IP Camera)
	Microphone	Yes (MIC to IP Camera)
	PTZ Camera Support	YES (IP, RS485)
	Schedule Method	Daily/Weekly Each Hour
	Programmable For Ch	Yes
	Record Time Limit	Yes
RECORD	Event Recording	Yes
	Intensive Recording	Yes (Motion / Alarm)
	Pre-Event Recording	0/1/2/3/4/5/10/15 Sec
	Panic Recording	Yes
	Display Mode	1,4,9,16
	Playback Rate	Up To 480FPs
ARCH & PLAYBACK	Playback Speed	X1, X2, X4, X16, X32, X64
	Туре	Calendar / Event / Time / Thumbnail
	Playback Zoom	Yes
	Snapshot	Yes (JPEG)

All specifications are subject to change without notice.







NR-16F85-8PRA

16 Channel 4K Embedded NVRs

■ Specifications

	MODEL	NR-16F85-8PRA
	Archiving Devices	USB Memory, FTP
	Remote Archiving	Yes (WEB RA, VMS, FTP)
	Snapshot Archiving	Yes
	Data Reserving	Yes
ARCHIVING	Reserved Data List Management	Yes
	Backup Data Format	AVI, RAW
	Watermark	MD5
	Watermark Verification	Yes
	Archived Data Playback	Yes
	Max. Connections	32 Users
	DHCP	Yes
	HTTPS	Yes
	SSL	Yes
	DDNS	Yes
	Transmission Rate	MAX 480 FPS
	Bandwidth Control	Yes
	Web Brower Access	Yes
	Remote Monitoring	Yes
	Remote Playback	Yes
NETWORK	Remote Archiving	Yes
	Remote Health Check	Yes Yes Yes Yes Yes Yes Yes Yes Yes (Profile-S) Yes Yes Yes Yes Yes Yes Yes Yes (iPhone, iPad, Android) Yes Yes Yes Yes Yes Yes (HTTP Based SDK, PC Codec Library) Yes
	VMS Support	Yes
	Onvif Camera Support	Yes (Profile-S)
NETWORK	Two-Way Audio	Yes
	PC Based Remote Agent	Yes
	Smart Phone Application	Yes (iPhone, iPad, Android)
	Web Based Remote Agent	Yes
	SDK	Yes (HTTP Based SDK, PC Codec Library)
	IP Filtering	Yes
	Auto Router Port Forwarding	Yes
	Dual Streaming	Yes
	FTP Client	Yes (For Archiving)
	E-Mail	Yes (SMTP Client)
	Authority Control	ie (simi eini)
	· · · · · · · · · · · · · · · · · · ·	Admin / Manager / User
	Auto IP Cam Installation (Plug and Display)	Yes
	Protocols	WS-Discovery, RTP, RTSP, RTCP,S MTP, NTP, HTTP, FTP, DDNS, DHCP, uPNP (Router Port Forwarding), HTTP
	WiFi	-
	Alarm Out	Yes
	Event Notification	Yes
	Video Popup	Yes
	Alarm Sensor Event	Yes
EVENT & ACTIONS	Video Loss Event	Yes
	Motion Detection Event	Yes
	Motion Sensor Area	Dependant on IP Camera
	Disk Event	Yes
	System Event	Yes
	Network Event	Yes
STORAGE	Disk S.M.A.R.T Check	Yes (Dependant on HDD Spec)
	External Storage	Yes (eSATA, NAS (for Backup))
	Auto Disk Recovery	Yes
	Deleting Partial Data	Yes
USER	Group Authority	Yes (Admin / Manger / User)
ADDITIONAL	Operating System	LINUX®
	F/W Upgrade	Yes (USB / Network)
	Setup Import/Export	Yes
	Keyboard Controller	No No
	Backup Viewer	Yes (Multi-channel Playback Support)
	Language	Multi-Language
	Video Analytics	Yes, in combination with 4MP Ganz PixelPro Cameras

All specifications are subject to change without notice.



