

## Accessories & Kits


Short Range White Light Illuminators

# WL-S Series

Short Range white light illuminators are designed to provide superior visible lighting for CCTV systems. These vandal-resistant all-weather lights can handle a variety of security applications. All Illuminators have a built-in photocell and are supplied with a wall mounting bracket. They can also be pre-assembled with our ProPak and iPak housing kits.

### Features:

- 8 LEDs provide up to 59 ft. range
- 30° & 120° beam angles
- Visible Spectrum 400-750nm
- Automatic photocell
- 12VDC /24VAC input
- IP67 rating for all weather outdoor performance
- Available pre-installed in ProPak & iPak





## WL-S Series

## Short Range White Light IR Illuminators

### ■ Specifications

Model	WL-S3	WL-S12
Number of LEDs	8	8
Electronics	High efficiency, high power surface mount LEDs with advanced current limited integral control circuitry	
Lumen Output	928nm	
Wavelength	Visible Spectrum (400-750nm)	
Color Temperature	6500K	
Color Rendering Index (CRI)	Color Rendering Index (CRI) 74-80+	
Angle	30°	120°
Distance	59 ft (18m)	30 ft (9m)
HOV	32 ft (10m)	102 ft (31m)
Cabling	9 ft (3m) connection lead	
Photocell	Adjustable via pot	
Illumination	Adjustable via pot	
Interface Connector	Photocell following contact & remote telemetry input	
Equalization Vent	Prevents thermal expansion & pressure cycling	
Construction	High quality aluminum extrusion	
Finish	Silver anodized aluminum	
Front Window	Polycarbonate high transmittance protective (vandal-proof) clear	
Mount	Silver powder coated stainless steel wall mount - Adjustable via M6 Allen key (included)	
Input Voltage	12VDC/24VAC	
Input Current	0.6A @ 24VAC	
Power Consumption	15W	
Operating Temp.	-58°F ~ 140°F (-50°C ~ 60°C)	
IP Rating	IP67	
Weight	1.7 lbs	
Dimensions	2.7" x 4.3" x 3.1" (68 x 110 x 78mm)	
Certifications	EMC, FCC, WEEE, RoHS	

*All specifications are subject to change without notice*

