



The GV-IO Box 8 provides 8 inputs and 8 relay outputs. It supports both DC and AC output voltages, and provides a USB port for PC connection.

Specifications						
OS Supported	32-bit	Windows XP / Vista / 7 / 8 / 8.1 / 10 / Server 2008				
	64-bit	Windows 7 / 8 / 8.1 / 10 / Server 2008 R2 / Server 2012 / Server 2012 R2				
Compatible S/W	GV-System version 8.2 or above					
Input	Input	8				
	Input Signal	Dry Contact Wet Contact, 9-30V AC / DC				
Communication	Relay Output	8				
	Relay Status	Normal open				
	Relay Capacitance	<table border="1"> <tr> <td>USB Connection</td> <td>30V DC, 3A</td> </tr> <tr> <td rowspan="2">RS-485 Connection</td> <td>125 / 250V AC, 3A</td> </tr> <tr> <td>30V DC, 3A</td> </tr> </table>	USB Connection	30V DC, 3A	RS-485 Connection	125 / 250V AC, 3A
USB Connection	30V DC, 3A					
RS-485 Connection	125 / 250V AC, 3A					
	30V DC, 3A					
Ethernet	RJ-45, 10/100 Mbps (Optional)					
DC IN	DC 12V, 1A					
Address	0-9, A-F					
Terminal Resistance	120 ohm					
Environmental Conditions	0 ~ 50 °C / 32 ~ 122 °F 5% ~ 95% (non-condensing)					
Dimensions (W x H x D)	135 x 28 x 145 (mm) / 5.31x 1.10 x 5.70 (in)					
Installation Guide	GV-IO Box 8					

Note: All specifications are subject to change without notice.