



SRX-Pro Rackmount Series 9E3200

i3 Part# 9E3200



Features

- Accepts 32 analog (optional 28 analog + 4IP)
- Upgradable to an additional 32IP
- JBOD storage and optional RAID5* configuration
- Analytics support, up to 16 video channels
- VGA and DVI-D ports for local live viewing
- Removable storage 1 to 8 HDD
- 2 sensor inputs and 2 control outputs
- Optional multiplexed or switched spot outputs
- Embedded OS
- CMS Support
- Keylock access front panel

Application & Benefits

Global market adoption of IP and megapixel camera technologies drives the need for new surveillance capabilities offered by the SRX-Pro Hybrid 9E3200. Supporting both analog and IP cameras, SRX-Pro is ideal for systems requiring transition to IP to maximize the cost-savings benefits associated with IP networking. Additional benefits are realized for systems adding new capabilities such as unparalleled image clarity using megapixel cameras.

The SRX-Pro hardware enhancements ensure efficient multi-tasking of simultaneous operations including network cameras, megapixel cameras, point-of-sale, video analytics and more. Dual video ports have also been added.

The front panel provides easy access to the standard DVD-RW drive, dual USB ports and up to eight field-replaceable hard drives. Applications include educational, municipal and corporate campus environments, large retail with IDM (Integrated Data Manager) point-of-sale integration, and hotels or resorts. When the need is for a hybrid digital recording solution, the answer is the SRX-Pro DVMS.

Recommended Products



i3-400E
i3-400E External
Expansion Chassis



L-NSARK-PI
L-NSARK-PI Pre-
Installed SATA Box




EPCI-NIC
EPCI-NIC Pre-Installed
Additional Network Card



L-NSAARRK
L-NSAARRK 2nd SATA
Back Box



WM-BRK
WM-BRK Wallmount
Bracket



CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4
USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004
www.i3international.com

© 2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice.

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101



1-800-284-2288 sales@avsupply.com
www.avsupply.com

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com



SRX-Pro Rackmount Series
9E3200
i3 Part# 9E3200

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

Software Configuration	
Number of analog channels	32
Number of VideoLogix channels	Up to 16
Number of VisionCount channels	Up to 16
Other IP and megapixel cameras supported	i3international.com
Recording modes video analytic (VAR)	Optional 1-16 channels (CPU & Memory upgrade is a MUST)
Recording modes (Time/Date - with time zone ref., sensor, motion detection, or continuous)	Yes
Screen display	1, 4, 6, 9, 10, 13, 16, 25, 36, and up to 64
Pre-alarm/Post-alarm recording	Yes
Emergency frame rate recording	Yes
Backup video format	i3 Encrypted, AVI, BMP, or JPEG
Number of IP video inputs	4 (Upgradeable to 32)
Hardware Configuration	
Operating system	Win 7 Embedded, Optional Win 2008 Server on IP
Standard SATA storage size	1HD w/OS for NON RAID5* and Optional RAID5*
Max. number of additional HDD	8
Operating devices (CPU, graphics, RAM)	Xeon Intel Processor, PCI Express Video Card, 4 GB RAM DDR 3
Analog video loop out (75 Ohm, dip switch controlled)	32
VGA resolution requirement	1024 x 768
Number of spot monitors	2
Number of audio inputs (DB9 to RCA)	8
Number sensor in/out (12VDC & 500mA Terminal Blocks)	2/2 [Optional UIO8 = 4/4 (TCP/IP)]
Number of RS485 ports (PTZ)	2 [Optional UIO8 = 1 (TCP/IP)]
Connectivity (LAN/WAN)	1Gb/sec
Resolution and Compression	
Type of Compression	MJPEG, MPEG4 or H.264
Analog display speed NTSC/PAL	up to 960/800
IP camera display speed (depending on screen division)	1, 4, 6, 9 = up to 30 fps per channel (depending on bandwidth & fps setting on cameras) or 10, 13, 16, 25, 36, 48 = 1-2 fps/ per camera
Client Applications	
Remote viewing	IE 6.0, Proprietary Software, & SRX-Pro Player, i3Display
IE 6.0, Proprietary Software, & SRX-Pro Player, i3Display	Optional 8 lanes serial or 16 lanes TC/IP
CMS (Central Monitoring Software)	Yes
Physical Environment and Certifications	
Type of chassis	Rackmount Aluminum
Physical dimensions (LxWxH)	22" x 17" x 7" (577.9 mm x 431.8 mm x 190.5 mm)
Power	115-230 VAC, 50-60 Hz, 550 W (auto switch)
Operating temperature & relative humidity	20 - 25C or 68 - 77F < 80%, non-condensing
Certification	UL/ULc, Fcc, CE
Warranty	
Standard Warranty	3 yr parts, 1 yr labour

CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4
USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004
www.i3international.com

©2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice. This data sheet may not be reproduced without permission.

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101