



## Ax40W8 1MP 8mm Wedge

i3 Part# C-Ax40W8



### Features

- Delivers 1 Megapixel resolution (1280x780) at 30 frames per second
- 8mm fixed lens
- PoE
- H264-MJPEG
- IP66
- A low profile IP camera, only 46 mm (1.8 inches) in height

### Application & Benefits

The Ax40W8 provides 8mm fixed lens focus ready for a simple installation. Ax40W series camera offers 720P, a progressive HDTV signal format with 720 horizontal lines and an aspect ratio of 16:9.

The Ax40W series is a low profile IP camera, only 46 mm (1.8 inches) in height which makes it very effective for discreet security installations. This camera series delivers 1 Megapixel resolution (1280x780) at 30 frames per second. In addition, the Ax40W supports MJPEG compression, which provides flexibility to meet various system requirements as well as h.264 compression allowing the video to transfer quicker over the Internet.

Built-in support for Power-over-Ethernet reduces cost and adds flexibility to the camera. A single cable connection is used to power, view, and control the camera. Installation cost is reduced since there is no need for separate cable installation. A 12 VDC is also available for installations that may require separate power.

The Ax40W is ideally suited for use within the video surveillance and security industry. It is made for both indoor and environments and works well with i3 software applications: SRX-Pro, iDisplay, Video Pilot and VideoLogix.

### Recommended Products



DB60  
DB60 Wallmount Goose  
Neck Camera Bracket



DB60CPM  
DB60CPM Corner / Pole  
Mount Bracket



International Standards  
Organization Registered Firm  
ISO 9001 Quality System

CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4  
USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004

[www.i3international.com](http://www.i3international.com)

© 2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice.

For design help, accessories or pricing, please contact:  
[sales@avsupply.com](mailto:sales@avsupply.com) or call: 1-858-565-1101

**AUDIO VIDEO SUPPLY**

1-800-284-2288 [sales@avsupply.com](mailto:sales@avsupply.com)  
[www.avsupply.com](http://www.avsupply.com)

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- [www.avsupply.com](http://www.avsupply.com)



## Ax40W8 1MP 8mm Wedge

i3 Part# C-Ax40W8

Image System	
Image Sensor	CMOS 1/4" OV9715
Video Streaming and Compression Method	Triple Streaming: H.264 / Motion JPEG
Maximum Framerate vs Resolution	NTSC: 720P (1280x720) @ 30 fps; PAL: 720P (1280x720) @ 25 fps
Resolutions	720P(1280x720), SVGA(800x600), VGA(640x480), D1(NTSC:720x480 / PAL:720x576), 4CIF(NTSC: 704x480 / PAL: 704x576), CIF(NTSC: 352x240 / PAL: 352x288)
Lens	Built-in Fixed Lens f=8mm, F1.8
Day/Night Mode	Digital D/N
View Angle	16.5 degree (H), 29.5 degree (V)
Angular DOF Range	Pan:+20, Tilt:0~110, Rotation:360
FOV 1280x720	H:28, V:16, D:31
Electric	
Shutter Time	1/30~ 1/8000 sec. (NTSC); 1/25 ~ 1/8000 sec. (PAL)
Minimum Illumination	0.15Lux
S/N Ratio	50dB (AGC off)
Gain Control	Off/ On, selectable
White Balance	ATW(2800K~8500K) /Manual
Image Enhancements	Backlight Compensation: Off / On (6 Area selectable); Exposure Mode: Auto/Manual; Sharpness, Saturation, Brightness, Contrast, Hue; Noise Reduction; WDR: Digital WDR. Off/High/Mid/Low; Digital Noise Reduction: 3D
Other Features	
Privacy Zone	Yes
Gamma Correction	0.45
Motion Detection	Yes
Image Orientation	Mirror, Flip
Other	System Log, FTP Record, Email Notification, User Management
Network Specifications	
Network Protocols	IPv4, HTTP/HTTPS, TCP, RTSP/RTCP/RTP, ICMP, UDP, IGMP, DNS, DHCP, ARP, NTP, SNMP, UPnP, SMTP
Security Access	Two user access levels with password protection. 1 Administrator, 5 Viewers
Web Browsing Requirements	Internet Explorer 8.0 or above
Mechanism	
Dimensions	110 mm x 46 mm (H) (4.33inch x 1.8inch (H))
Weight	approx. 340g (0.75lb)
Connectors	Network: RJ45 (Female); Buttons: Reset, Default (On top)
Video Port/Output	1 x Inside Service Port with 2 pin connector, 1.0Vp-p, 75
Power Supply	
Power Requirement	PoE IEEE 802.3af Class 0, DC 12V
Power Consumption (max.)	6.6W
Environment	
Operating Temperature	-10 C degrees - 40 C degrees (14 F degrees - 104 F degrees)
Operating Humidity	10~ 90% RH
Regulations, Ratings	
Protection Class	CE, FCC, Class B, ONVIF, IP66, UL (if used indoors)

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- [www.avsupply.com](http://www.avsupply.com)

CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4  
USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004  
[www.i3international.com](http://www.i3international.com)

©2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice. This data sheet may not be reproduced without permission.

For design help, accessories or pricing, please contact:  
[sales@avsupply](mailto:sales@avsupply) or call: 1-858-565-1101