

## D-i3-6800 Camera Housing

i3 Part# D-i3-6800HB



## **Features**

- Completely weather resistant
- Protects your valuable camera investments

## **Application & Benefits**

The D-i3-6800 is a light duty wall mount camera housing designed specifically for use with any of the i3s camera series. Manufactured from die cast aluminium, the D-i3-6800 is capable of supporting a maximum load of 20 pounds (9 kg) and can be safely mounted to any vertical loadbearing surface. D-i3-6800 is beige color and IP66.

D-i3-6800 camera enclosures is constructed from die cast and extruded aluminium without heater and blower while it counter part D-i3-6800-HB does. The D-i3-6800 has a lower body length of 16 inches. The front hinged lid provides easy access to the removable camera sled. Two adjustable (PG13.5) glands on the bottom of the enclosure allow for easy installation of the power and video cables. The rear link-lock latch can be used with a padlock of suitable size to secure the enclosure.

The D-i3-6800-HB (heater and blower) does require 24AC and less than 1AMP. It is used for outdoor while the D-i3-6800 is indoor housing.





ISO 9001 Quality System

CANADA | 780 Birchmount Road, Unit 16, Scarborough. ON, M1K 5H4 USA | 1967 Wehrle Drive, Suite 1 Williamsville. NY, 14221

1.866.840.0004 www.i3international.com





## D-i3-6800 Camera Housing

i3 Part# D-i3-6800HB

Specification	
Dimensions	413mm L x250mm W x119 mm D (16"x5.75"x4.25")
Weight	bracket and housing: 1.56kg or 3.45lbs
Camera bracket length	286 mm or 11.25 inches
Construction	Die-cast Aluminum
Colour	white

CANADA | 780 Birchmount Road, Unit 16, Scarborough. ON, M1K 5H4 USA | 1967 Wehrle Drive, Suite 1 Williamsville. NY, 14221

1.866.840.0004

www.i3international.com