

i3C762 PTZ Camera Joystick

i3 Part# i3C762



Features

- Multifunctional
- Two-line LCD Display
- Three-Axis Control

Application & Benefits

The i3C762 PTZ Camera joystick delivers easy access to and management of all standard PTZ camera functions, including the recall of presets, alarm functions, and pan, tilt and zoom. The joystick also controls higher-level speed-dome functions, including home presets, remote resets, mini tours and privacy zones.

Unlike LED design, two-line LCD has 32 characters to display functions which make users easily understand what functions they operate. Also provides direct control over camera pan/tilt/zoom functions.





ISO 9001 Quality System

CANADA | 780 Birchmount Road, Unit 16, Scarborough. ON, M1K 5H4 USA | 1967 Wehrle Drive, Suite 1 Williamsville. NY, 14221

1.866.840.0004 www.i3international.com





i3C762 PTZ Camera Joystick

i3 Part# i3C762

General	
Serial interfaces	1 x control unit interface with two physical connections PORT1 and PORT2
Connections	terminal block, 2 x RS485
Control elements	32 keys, 1 joystick(3-axis)
LCD display	two-line LCD display
Dimensions (WxHxD)	350mm x 106mm x 200mm (13.88" x 4.2" x 7.9")
Power requirement	DC12V, 150mA
Power consumption	1.8W
Weight	950 g (2.1 lb)
Communication	
Protocol	Pelco D/P, MESSOA D/P(selectable via menu)
Baud rate	2400, 4800, 9600 (selectable via menu)
Environment	
Operating temperature	-5C ~ 50C (23F~122F)
Operating humidity	10%~90% RH, no-condensing
Storage temperature	-20C ~ 60C (-4F~140F)
Housing	High impact ABS

CANADA | 780 Birchmount Road, Unit 16, Scarborough. ON, M1K 5H4 USA | 1967 Wehrle Drive, Suite 1 Williamsville. NY, 14221

1.866.840.0004