



i3S730Pro PTZ  
i3 Part# i3S730Pro



## Features

- Special Order Only
- Vandal resistance up to 750 kg of impact
- 312x zoom (26x optical and 12x digital zoom)
- Pan speed: 430/sec; tilt speed: 200/sec
- Accurately pan at +/- 0.02
- Supports 256 pre-sets and four (4) 6-minute programmable tours
- Supports 24x privacy zones and schedules
- Motion detection, 6 alarm inputs, 1 alarm output
- IP67 compliant water proofing

## Application & Benefits

i3 International is introducing a new vandal resistant dome camera i3S730PTZP. It is ideal for installations where structural integrity and resistance to vandalism are a priority.

The i3S730PTZP is an IP67 waterproof vandal resistant speed dome camera. This camera is made for rugged conditions and is ideal for high-security installations. With 26x optical zoom and 12x digital zoom, i3S730PTZP provides a clear picture from great distances with its 3.5 to 91mm lens.

In addition, this cameras stepping motor and speed-optimized microprocessor allow users to pan the speed dome with the +/- 0.02 accuracy. The i3S730PTZP is built with precision panning and produces outstanding images.

This camera allows simple setup of up to 256 pre-set positions and up to four 6-minute tours, which makes it one of the most versatile speed dome cameras in its class. Each pre-set can be maximized by the cameras 360 auto flip function. The i3S730PTZP camera comes with an automatic day/night mode function, which allows the camera to switch to colour mode during the day time and to black/white imaging at night for better night-time viewing performance.

The main advantage of the i3S730PTZP is an easy installation, simplified with a single cable for power, video, and communication. Installation and servicing the i3S730PTZP is simple as 1-2-3!

## Recommended Products



i3D702  
i3D702 Pendant Pipe  
Mount



i3D703  
i3D703 Simple Wall  
Mount Bracket




i3D704  
i3D704 Goose Wall  
Mount with Power Box



i3D705  
i3D705 Pendant Pipe  
Mount with Power Box



i3D706  
i3D706 Parapet Wall  
Mount



CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4  
USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004  
www.i3international.com

© 2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice.

For design help, accessories or pricing, please contact:  
sales@avsupply or call: 1-858-565-1101

**AUDIO VIDEO SUPPLY**

1-800-284-2288 sales@avsupply.com  
www.avsupply.com

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com



## i3S730Pro PTZ

i3 Part# i3S730Pro

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

Features	
Focus	Auto (sensitivity: normal, low), one-push AF, manual, infinity, interval AF, zoom trigger AF
Zoom Limit	Up to 312x (optical 26x, digital 12x)
Focal Length	f=3.5 mm (wide) to 91.0 mm (tele)
Signal system	NTSC/PAL
Scanning system	2:1 Interlace V: 59.94Hz, H: 15.734KHz/2:1 Interlace V: 50Hz, H: 15.625KHz
Image sensor	1/4" SONY Ex-view HAD CCD
Effective pixels	380K pixels/440K pixels approx.
Minimum illumination	Normal mode: 0.1 lux (F1.6, 1/60(1/50) sec. ICR OFF, 10 IRE) / Slow shutter mode: 0.007 lux (F1.6, 1/4(1/3) sec. ICR OFF, 10 IRE) / Night mode: 0.035 lux (F1.6, 1/60(1/50) sec. ICR ON, 10 IRE) / Slow shutter mode: 0.0025 lux (F1.6, 1/4(1/3) sec. ICR ON, 1
Horizontal resolution	560 TV lines
Privacy zone	ON/OFF, up to 24 zones (3D Privacy Zone)
Motion detection	Yes
Day & Night mode	Auto / manual
White balance	Auto, ATW, Indoor, outdoor, one-push, manual
AGC, BLC, Flickerless	AGC: Auto/Manual (-3 to 28 dB, 2 dB steps), BLC: ON/OFF, Flickless: Yes
Video output level	1 Vpp composite output, 75Ohm
Electric	
Shutter time	ON/OFF (max 1.0S)
Functions	
Pan, Tilt range	Pan: 360 continuous, Tilt: 92
Manual pan speed	0.1 - 90/s, 0.1o/s: max dig. zoom ; 0.4o/s :max opt. zoom
Manual tilt speed	0.1 - 45/s, 0.1/s: max dig. zoom ; 0.4/s :max opt. Zoom
Auto flip	ON/OFF
Programmable presets	256 points
Programmable tours	4 pattern tours memorizing up to 6 minutes of manual control
Password protection	Alphanumerical Dome OSD setup protection
Power supply	
Power requirement	24VAC 10%
Power consumption	46W (max.)
I/O connector	
Alarm	6 inputs / 1 output
Interface	RS485 (2-wire)
Baud Rate	2400, 4800, 9600, 19200 bit/s (DIP-switch selectable)
Camera Control Protocol	Supports Pelco - P/D, GE, Bosch, Ernitec
Environment	
Operating temperature	-40C ~ 60C (-40F~140F)
Operating humidity	20% ~ 80% RH
Dimensions (xH)	216.6mm x 324.0mm (8.52" x 12.75")
Storage temperature	-20C~60 C (-4F~140F)
Weight	3800g approx (8.377lb)
Protection Class	CE, FCC, Class A
Water Resistance	IP67 (with heater and blower)
Vanadal Resistance	750KG (1653 lb) impact resistance
Warranty	
Standard Warranty	1 year limited warranty

CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4  
 USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004  
 www.i3international.com

©2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice. This data sheet may not be reproduced without permission.

For design help, accessories or pricing, please contact:  
 sales@avsupply or call: 1-858-565-1101