



## Network Storage iS28

i3 Part# iS28



### Features

- Backplane design supports eight (8) to sixteen (16) SATA II 3Gbps drives (based on model)
- Front-end Dual Gigabit Ethernet TCP/IP offload device
- Hardware RAID Intel IOP 331 64-bit processor
- Supports RAID levels JBOD, 1, 6, 10 or 0+1
- Event notification via Email, SNMP trap, Windows & bower
- Dual/quad GbE ports with load-balancing and failover for high availability

### Application & Benefits

i3s iS28 Storage Array Network (SAN) enclosures are cost-effective 2U-8 bay iSCSI-to-SATA IP RAID storage devices. This enclosure comes with the built-in dual Gigabit Ethernet ports for convenient connectivity and fast data transfer through networking infrastructure and provide a user-friendly GUI and an easy-to-read blue LCD panel for ease-of-control. The server-grade redundant 400W universal power supply ensures running reliability and dual Gigabit iSCSI ports ensure high speed data transfer rate and sharing. iS28 uses Intel 331, 64-bit Xscale processor as the core engine that delivers excellent performance. The enclosures support RAID 1, 5, 6, 10 or JBOD storage structures.

i3s iSCSI/IP SAN series enclosures offer high-performance storage while providing a form factor selection of 2U rackmount 8-drive, featuring embedded hardware RAID controller with two/four Gigabit Ethernet ports. The 2U rackmount design can be integrated easily into any existing storage infrastructure or a standardized 19-inch rack, featuring easy management with a single logic volume shared by as many as 32 hosts.

#### Web-based User Interface:

i3s iSCSI/IP SAN storage solution not only provides an LCD panel for quick configuration but also offers a friendly and easy to use web-based GUI that allows users to manage storage settings such as RAID settings, storage control and monitoring anytime and anywhere through Internet.



International Standards  
Organization Registered Firm  
ISO 9001 Quality System

CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4  
USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004  
www.i3international.com

©2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice.

For design help, accessories or pricing, please contact:  
sales@avsupply or call: 1-858-565-1101

**AUDIO VIDEO SUPPLY**  
1-800-284-2288 sales@avsupply.com  
www.avsupply.com

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com



## Network Storage iS28

i3 Part# iS28

Specification	
Chassis Description	2U 8 bay
Host Interface	Dual port iSCSI Gigabit Ethernet
HDD Interface	SATA (3/6 Gbps)
No. of Disks	Up to 8
RAID Function	RAID 0, 1, 0+1, 6, 10 or JBOD
CPU & Memory	Intel IOP 341 800 MHz and 1 GB DDR2-533
LED Display for Each Tray	White - power-on indicator; Blue - busy (HDD access) indicator
Material	Heavy-duty cold-rolled steel
Power Supply	Redundant 400 W (IPC-grade) Input: 90-230 V AC, 50/60 Hz (iS28/iS216)
Alarm	Buzzer Beeping for Fan-fail or over temperature(over 50)
External Enclosure Management	Fast Ethernet port for web-based management; Event notification via e-mail, SNMP trap, and Net Messenger
System Requirement	Host RAID Card / eSATA card or on-board system must support Port Multiplier function
O.S. Support	O.S. independent, compatible with Windows, Mac OS and Linux
Warranty	3 yr parts, 1 yr labour
LED Display for Enclosure	Power-On LED - White, FAN Normal -Green; FAN Fail - Red, TEMP. Normal -Green; TEMP. over 50 - Red
Cooling	Power-On LED - White, FAN Normal -Green; FAN Fail - Red, TEMP. Normal -Green; TEMP. over 50 - Red
Dimension	559(D)482(W)88(H) mm; 22(D)19(W)3.5(H) inch

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4  
 USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004  
 www.i3international.com

©2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice. This data sheet may not be reproduced without permission.

For design help, accessories or pricing, please contact:  
 sales@avsupply or call: 1-858-565-1101